

Package ‘GAabbreviate’

October 12, 2022

Type Package

Version 1.3

Date 2016-06-22

Title Abbreviating Items Measures using Genetic Algorithms

Description Scale abbreviation using Genetic Algorithms that maximally capture the variance in the original data.

Depends R (>= 3.0), GA (>= 3.0), psych (>= 1.4.3)

Imports stats, graphics, grDevices, utils

License GPL (>= 2)

ByteCompile true

LazyLoad yes

NeedsCompilation no

Author Luca Scrucca [aut],
Baljinder K. Sahdra [aut, cre]

Maintainer Baljinder K. Sahdra <baljinder.sahdra@acu.edu.au>

Repository CRAN

Date/Publication 2016-06-23 00:41:26

R topics documented:

GAabbreviate	2
Index	6

GAabbreviate	<i>Abbreviating items (from questionnaire or other) measures using Genetic Algorithms (GAs)</i>
--------------	---

Description

The GAabbreviate uses Genetic Algorithms as an optimization tool for scale abbreviation or subset selection that maximally captures the variance in the original data.

Usage

```
GAabbreviate(items = NULL,
             scales = NULL,
             itemCost = 0.05,
             maxItems = 5,
             maxiter = 100,
             popSize = 50,
             ...,
             plot = FALSE,
             verbose = interactive(),
             crossVal = TRUE,
             impute = FALSE,
             pairwise = FALSE,
             minR = 0,
             sWeights = NULL,
             nSample = NULL,
             seed = NULL)
```

Arguments

items	A matrix of subjects x item scores.
scales	A matrix of subjects x scale scores.
itemCost	The fitness cost of each item. This will usually need to be determined by trial and error.
maxItems	The maximum number of items used to score each scale.
maxiter	Number of generations of GA to run.
popSize	Size of population in each generation of the GA.
...	further arguments passed to ga for tuning GAs.
plot	Logical; if TRUE, plot results after every generation (this will slow down the process).
verbose	Logical; by default in interactive sessions is set to TRUE, so some info during the search is displayed.
crossVal	Logical; if TRUE, cross-validation will be performed. Note that if you turn this off, the predictive fit of the resulting measure will be biased by overfitting.

impute	Logical; if TRUE, the mean value will be imputed for any missing item or scale scores. This is NOT recommended. Instead, you should decide how to handle missing values yourself before passing the items and scales variables.
pairwise	Logical; if TRUE, the GA will use pairwise deletion to select items, i.e. some scales/items may have different NAs than others. If FALSE, the GA will crash if any NAs are passed. It's recommended to leave this off, as NAs should really be handled separately.
minR	The minimum bivariate item-scale correlation required in order to retain an item. Note that if this is set above 0, the number of items retained can be lower than the value of maxItems.
sWeights	Weighting of scales. By default, all scales will have unit weighting, but if you want to emphasize some scales more heavily, pass a vector with length equal to the number of scales.
nSample	For extremely large datasets, you may wish to use only a subset of observations to generate a measure. Passing any non-zero number will randomly select nSample observations to use instead of drawing on the full dataset.
seed	An integer value containing the random number generator state. Set this argument to make the results exactly reproducible.

Details

The GAabbreviate uses Genetic Algorithms (GAs) as an optimization tool for shortening a large set of variables (e.g., in a lengthy battery of questionnaires) into a shorter subset that maximally captures the variance in the original data. An exhaustive search of all possible shorter forms of the original measure would be time consuming, especially for a measure with a large number of items. For a long form of length L (e.g., 100 items of a self-report scale), the size of the search space is 2^L (1.26e+30) and forms a hypercube of L dimensions. The GA uses hypercube sampling by sampling the corners of the L -dimensional hypercube. It optimizes the search by mimicking Darwinian evolution mechanisms (of selection, crossover, and mutation) while searching through a "landscape" of the collection of all possible fitness values to find an optimal value. This does not imply that the GA finds the "best" possible solution. Rather, the GA is highly efficient in quickly yielding a "good" and "robust" solution rated against a user-defined fitness criterion.

The GAabbreviate uses the GA package (Scrucca, 2013) to efficiently implement Yarkoni's (2010) scale abbreviation cost function:

$$Cost = Ik + \sum_{i=1}^s w_i(1 - R_i^2)$$

where I represents a user-specified fixed item cost, k represents the number of items retained by the GA (in any given iteration), s is the number of subscales in the measure, w_i are the weights (by default $w_i = 1$ for any i) associated with each subscale (if there are any subsets to be retained), and R_i^2 is the amount of variance in the i th subscale that can be explained by a linear combination of individual item scores. Adjusting the value of I low or high yields longer or shorter measures respectively. When the cost of each individual item retained in each generation outweighs the cost of a loss in explained variance, the GA yields a relatively brief measure. When the cost is low, the GA yields a relatively longer measure maximizing explained variance (Yarkoni, 2010).

Sahdra, Ciarrochi, Parker & Scrucca (2016) contains an example of how GAabbreviate can be used for item-reduction of a multidimensional scale.

Value

An object of class 'GAabbreviate' providing the following information:

data	The input data.
settings	The input settings.
results	The results obtained.
best	The cost and fit of the final solution.
GA	An object of class 'GA'.
measure	A list of measure values.

A summary and plot methods are available to inspect the results. See example section.

Author(s)

Luca Scrucca, Department of Economics, University of Perugia, Perugia, ITALY

Baljinder K. Sahdra, Institute for Positive Psychology and Education, Australian Catholic University, Strathfield, NSW, AUSTRALIA

Send inquiries to <baljinder.sahdra@acu.edu.au>.

References

Sahdra B. K., Ciarrochi J., Parker P. and Scrucca L. (2016). Using genetic algorithms in a large nationally representative American sample to abbreviate the Multidimensional Experiential Avoidance Questionnaire. *Frontiers in Psychology*, Volume 7(189), pp. 1–14. http://www.frontiersin.org/quantitative_psychology_and_measurement/10.3389/fpsyg.2016.00189/abstract

Scrucca, L. (2013). GA: a package for genetic algorithms in R. *Journal of Statistical Software*, 53(4), 1-37, <http://www.jstatsoft.org/v53/i04/>.

Yarkoni, T. (2010). The abbreviation of personality, or how to measure 200 personality scales with 200 items. *Journal of Research in Personality*, 44(2), 180-198.

See Also

[ga](#)

Examples

```
### Example using random generated data
nsubject = 100
nitems = 15
set.seed(123)
items = matrix(sample(1:5, nsubject*nitems, replace = TRUE),
               nrow = nsubject, ncol = nitems)
scales = cbind(rowSums(items[,1:10]), rowSums(items[,11:15]))

GAA = GAabbreviate(items, scales, itemCost = 0.01, maxItems = 5,
                  popSize = 50, maxiter = 300, run = 100)

plot(GAA)
```

```
summary(GAA)  
# more info can be retrieved using  
GAA$best  
GAA$measure
```

Index

* **multivariate**

GAabbreviate, 2

* **optimize**

GAabbreviate, 2

* **survey**

GAabbreviate, 2

ga, 2, 4

GAabbreviate, 2