

Package 'redcapAPI'

September 13, 2023

Type Package

Title Interface to 'REDCap'

Version 2.8.0

Maintainer Shawn Garbett <shawn.garbett@vumc.org>

Description Access data stored in 'REDCap' databases using the Application Programming Interface (API). 'REDCap' (Research Electronic Data CAPture; <<https://projectredcap.org>>, Harris, et al. (2009) <doi:10.1016/j.jbi.2008.08.010>, Harris, et al. (2019) <doi:10.1016/j.jbi.2019.103208>) is a web application for building and managing online surveys and databases developed at Vanderbilt University. The API allows users to access data and project meta data (such as the data dictionary) from the web programmatically. The 'redcapAPI' package facilitates the process of accessing data with options to prepare an analysis-ready data set consistent with the definitions in a database's data dictionary.

License GPL-2

Depends R (>= 3.5.0)

Imports checkmate, chron, httr, labelVector, lubridate, keyring, getPass, yaml

LazyLoad yes

Suggests testthat (>= 3.0.0), Hmisc, rstudioapi, mockery

URL <https://github.com/vubiostat/redcapAPI>

BugReports <https://github.com/vubiostat/redcapAPI/issues>

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Author Shawn Garbett [cre, ctb] (<<https://orcid.org/0000-0003-4079-5621>>), Benjamin Nutter [ctb, aut], Stephen Lane [ctb], Will Beasley [ctb], Jeffrey Horner [aut], Will Gray [ctb],

Jeremy Stephens [ctb],
 Marcus Lehr [ctb],
 Cole Beck [ctb],
 Savannah Obregon [ctb]

Repository CRAN

Date/Publication 2023-09-12 23:50:02 UTC

R topics documented:

allocationTable	3
armsMethods	6
checkboxbox_suffixes	9
cleanseMetaData	10
createFileRepositoryFolder	10
dagAssignmentMethods	12
dagMethods	15
deleteRecords	17
deprecated_redcapProjectInfo	19
dropRepeatingNA	20
eventsMethods	21
exportBulkRecords	24
exportBundle	26
exportFieldNames	27
exportFileRepositoryListing	29
exportInstruments	31
exportLogging	32
exportPdf	34
exportVersion	36
Extraction	37
fieldCastingFunctions	37
fieldChoiceMapping	41
fieldToVar	42
fieldValidationAndCasting	43
fileMethods	47
fileRepositoryMethods	50
fileRepositoryPath	54
filterEmptyRow	54
fromFileRepositoryMethods	55
getProjectIdFields	58
importRecords	59
invalidSummary	62
isZeroCodedCheckField	62
makeApiCall	64
mappingMethods	67
massert	69
metaDataMethods	70
missingSummary	73

parseBranchingLogic	75
prepUserImportData	76
projectInformationMethods	77
purgeRestoreProject	81
recodeCheck	84
reconstituteFileFromExport	85
recordsManagementMethods	86
recordsMethods	88
recordsTypedMethods	93
redcapConnection	99
redcapDataStructures	103
redcapError	104
redcapFactorFlip	105
repeatingInstrumentMethods	105
reviewInvalidRecords	107
splitForms	109
stringCleanup	110
stripHTMLandUnicode	111
surveyMethods	112
switchDag	115
syncUnderscoreCodings	117
unlockREDCap	118
userMethods	119
userRoleAssignmentMethods	124
userRoleMethods	126
validateImport	131
vectorToApiBodyList	132
widerRepeated	133
writeDataForImport	134
Index	135

allocationTable

Generate Allocation Tables for the Randomization Module

Description

These methods enable the user to generate allocation tables for the REDCap randomization module. Randomization may be stratified by other (categorical) variables in the data set as well as by Data Access Group. Additionally, randomization may be blocked to ensure balanced groups throughout the allocation

Usage

```
allocationTable(  
  rcon,  
  random,  
  strata = NULL,  
  group = NULL,  
  dag.id = NULL,  
  replicates,  
  block.size,  
  block.size.shift = 0,  
  seed.dev = NULL,  
  seed.prod = NULL,  
  weights = NULL,  
  ...  
)  
  
## S3 method for class 'redcapApiConnection'  
allocationTable(  
  rcon,  
  random,  
  strata = NULL,  
  group = NULL,  
  dag.id = NULL,  
  replicates,  
  block.size,  
  block.size.shift = 0,  
  seed.dev = NULL,  
  seed.prod = NULL,  
  weights = c(1, 1),  
  ...  
)  
  
allocationTable_offline(  
  meta_data,  
  random,  
  strata = NULL,  
  group = NULL,  
  dag.id = NULL,  
  replicates,  
  block.size,  
  block.size.shift = 0,  
  seed.dev = NULL,  
  seed.prod = NULL,  
  weights = c(1, 1),  
  ...  
)
```

Arguments

<code>rcon</code>	A redcapConnection object.
<code>random</code>	character(1). The field name to be randomized.
<code>strata</code>	character. Field names by which to stratify the randomization.
<code>group</code>	character(1). A field name giving a group by which randomization should be stratified. This could also be listed in <code>strata</code> , but the argument is provided to remain consistent with the REDCap user interface.
<code>dag.id</code>	integerish. Data Access Group IDs.
<code>replicates</code>	integerish(1). The number of randomizations to perform within each stratum
<code>block.size</code>	integerish. Block size for the randomization. Blocking is recommended to ensure balanced groups throughout the randomization. This may be a vector to indicate variable block sizes throughout the randomization.
<code>block.size.shift</code>	numeric on the interval $[0, 1]$. A vector the same length as <code>block.size</code> where the first element is 0. This controls when the block size changes as a proportion of the total sample size. When <code>block.size=c(8, 4, 2)</code> and <code>block.size.shift=c(0, .5, .9)</code> , the first half of the randomization is performed in blocks of 8, then the next 40 percent of the randomization is performed in blocks of 4, with the last ten percent performed in blocks of 2.
<code>seed.dev</code>	integerish. At least one value is required. If only one value is given, it will be converted to a vector with length equal to the number of strata. Values will be incremented by 100 to provide independent randomizations. This may also have length equal to the number of strata.
<code>seed.prod</code>	integerish. Same as <code>seed.dev</code> , but used to seed the production allocation. No pairwise elements of <code>seed.dev</code> and <code>seed.prod</code> may be equal. This guarantees that the two randomization schemes are unique.
<code>weights</code>	An optional vector giving the sampling weights for each of the randomization groups. There must be one number for each level of the randomization variable. If named, the names must match the group labels. If unnamed, the group labels will be assigned in the same order they appear in the data dictionary. The weights will be normalized, so they do not need to sum to 1.0. In other words, <code>weights=c(3, 1)</code> can indicate a 3:1 sampling ratio.
<code>...</code>	Arguments to pass to other methods
<code>meta_data</code>	character(1). For the offline method, a text string giving the location of the data dictionary downloaded from REDCap.

Details

Each element in `block.size` must be a multiple of the number of groups in the randomized variable. The 'offline' version of the function operates on the data dictionary file downloaded from REDCap. This is made available for instances where the API cannot be accessed for some reason (such as waiting for API approval from the REDCap administrator).

The value of `replicates` controls how many allocations are generated. It is possible to get slightly more replicates than requested if your blocking design cannot exactly match replicates. For example, if the users asks for 30 replicates in blocks of 8, a warning will be printed and 32 replicates will be returned in the randomization table.

Value

Returns a list with the elements

dev_allocation	data.frame with the randomization allocations for the development environment.
prod_allocation	data.frame with the randomization allocations for the production environment.
dev_seed	The random seed values for the development environment.
prod_seed	The random seed values for the production environment.
blocks	Blocking scheme used to generate the randomization.
weights	Weighting scheme for the randomization.

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

allocationTable(rcon,
               random = "treatment_assignment",
               strata = c("demographic_group", "hospital_group"),
               replicates = 12,
               block.size = 4,
               seed.dev = 12345,
               seed.prod = 54321)

## End(Not run)
```

 armsMethods

Export, Import, and Delete Arms from a Project

Description

These methods enable the user to export the current arms from a project, import new arms, and modify or delete existing arms.

Usage

```
exportArms(rcon, ...)

importArms(rcon, data, override = FALSE, ...)

deleteArms(rcon, arms, ...)

## S3 method for class 'redcapApiConnection'
```

```

exportArms(
  rcon,
  arms = character(0),
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
importArms(
  rcon,
  data,
  override = FALSE,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
deleteArms(
  rcon,
  arms,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

<code>rcon</code>	A <code>redcapConnection</code> object.
<code>arms</code>	character or integerish identifying the arm numbers to export or delete.
<code>data</code>	A <code>data.frame</code> with two columns. The first column (<code>arm_num</code>) is an integerish value. The second (<code>name</code>) is a character value. For backward compatibility, this may also be passed as <code>arms_data</code> .
<code>override</code>	logical(1). By default, data will add to or modify existing arms data. When TRUE, all the existing arms data is deleted and replaced with the contents of <code>data</code> .
<code>refresh</code>	logical(1) If TRUE, the cached arms data will be refreshed after the API action is complete.
<code>...</code>	Arguments to pass to other methods
<code>error_handling</code>	character(1). One of <code>c("error", "null")</code> . An option for how to handle errors returned by the API. see redcapError() .

config	A named list. Additional configuration parameters to pass to <code>httr::POST()</code> . These are appended to any parameters in <code>rcon\$config</code> .
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by <code>redcapAPI</code> .

Details

Exporting arms is not supported for classical REDCap projects. If the user attempts to export arms for a classical project, a data frame will be returned with zero rows.

When importing, arms are added when the value of `arm_num` does not already exist in the project.

Arm names may be modified by altering the name value associated with an existing `arm_num` value.

Deleting arms—whether by `deleteArms` or `importArms` with `override = TRUE`—is a destructive act that also deletes events and records associated with the arm. This is irreversible data loss. REDCap will only permit these actions to occur in projects in Development status.

Value

`exportArms` returns a `data.frame` with columns:

<code>arm_num</code>	The ID number for the arm in the project.
<code>name</code>	The display name of the arm.

`importArms` has no return and prints a message indicating the number of arms imported.

`deleteArms` has no return and prints a message indicating the number of arms deleted.

Functions

- `exportArms()`: Export the arms defined in a project.
- `importArms()`: Import and modify the arms definitions in a project.
- `deleteArms()`: Delete arms from a project.

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export all of the Arms
exportArms(rcon)

# Export only a subset of arms
exportArms(rcon,
           arms = c(1, 3))
```



```
# Import a new arms
# Assume arms 1, 2, and 3 exist in the project already
NewData <- data.frame(arm_num = 4,
                      name = "Arm Four Name")
importArms(rcon,
           data = NewData)

# Change the name of an existing arm
NewData <- data.frame(arm_num = 1,
                      name = "New Arm Name")
importArms(rcon,
           data = NewData)

# Delete all arms and replace with a new specification
NewData <- data.frame(arm_num = c(1, 2),
                      name = c("Treatment Arm", "Control Arm"))
importArms(rcon,
           data = NewData,
           override = TRUE)

# Delete an existing arm
deleteArms(rcon,
           arms = 4)

# Delete multiple existing arm
deleteArms(rcon,
           arms = c(2, 3))

## End(Not run)
```

checkbox_suffixes *Checkbox Suffixes*

Description

Checkbox variables return one vector of data for each option defined in the variable. The variables are returned with the suffix `__[option]`. `exportRecords` needs these suffixes in order to retrieve all of the variables and to apply the correct labels.

Usage

```
checkbox_suffixes(fields, meta_data)
```

Arguments

<code>fields</code>	The current field names of interest
<code>meta_data</code>	The metadata data frame.

cleanseMetaData	<i>Clean Meta Data of UTF Characters</i>
-----------------	--

Description

There have been isolated cases observed where certain characters in the data dictionary prevent it from being downloaded correctly. In one case, the data dictionary could not be downloaded at all through the API. It is suspected that these problematic characters are a result of copying and pasting text out of word processing programs. The problematic characters are not necessarily visible and their exact location can be difficult to identify. As a last resort, `cleanseMetaData` can read a meta data file downloaded through the user interface, purge it of any UTF-8 characters, and write an alternate data dictionary that contains only ASCII characters.

Usage

```
cleanseMetaData(meta_data_file, meta_data_clean, overwrite = FALSE)
```

Arguments

<code>meta_data_file</code>	character(1) the path to a meta data file that has been downloaded using the REDCap user interface.
<code>meta_data_clean</code>	character(1) the path of the file to which the cleaned meta data will be written.
<code>overwrite</code>	logical(1) Permit the new file to overwrite an existing file.

createFileRepositoryFolder	<i>Create a Folder in the File Repository</i>
----------------------------	---

Description

This method enables the user to create a folder in the file repository. The folder created may also be a subfolder of an existing folder.

Usage

```
createFileRepositoryFolder(
  rcon,
  name,
  folder_id = numeric(0),
  dag_id = numeric(0),
  role_id = numeric(0),
  ...
)
```

```

## S3 method for class 'redcapApiConnection'
createFileRepositoryFolder(
  rcon,
  name,
  folder_id = numeric(0),
  dag_id = numeric(0),
  role_id = numeric(0),
  ...,
  refresh = TRUE,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
name	character(1) The name of the folder. If a folder by this name already exists, no action will be taken.
folder_id	integerish(0/1). The ID of the parent folder. When length is 0, the new folder is placed in the top-level.
dag_id	integerish(0/1) The ID of a data access group. When provided, access to the folder will be restricted to the DAG.
role_id	integerish(0/1) The ID of a role. When provided, access to the folder will be restricted to users with that role.
...	Arguments to pass to other methods
refresh	logical(1) When TRUE (default), the cached File Repository data on rcon will be refreshed.
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Value

Returns a data frame with the columns

folder_id	The REDCap assigned ID value for the newly created folder.
name	The name assigned to the folder by the user.

See Also

```
exportFromFileRepository(),  
importToFileRepository(),  
deleteFromFileRepository(),  
exportFileRepository(),  
importFileRepository(),  
deleteFileRepository(),  
exportFileRepositoryListing()
```

Examples

```
## Not run:  
unlockREDCap(connections = c(rcon = "project_alias"),  
              url = "your_redcap_url",  
              keyring = "API_KEYS",  
              envir = globalenv())  
  
# Create a folder in the top-level directory  
createFileRepositoryFolder(rcon,  
                           name = "New Folder Name")  
  
# Create a folder in a subfolder  
createFileRepositoryFolder(rcon,  
                           name = "New Folder Name",  
                           folder_id = 12345)  
  
# Create a folder assigned to a Data Access Group  
createFileRepositoryFolder(rcon,  
                           name = "New Folder Name",  
                           dag_id = 678)  
  
## End(Not run)
```

dagAssignmentMethods *Export and Import Users Assigned to Data Access Groups*

Description

These methods enable the user to export existing assignments of users to Data Access Groups, or import new or updated assignments to the project.

Usage

```
exportUserDagAssignments(rcon, ...)  
  
importUserDagAssignments(rcon, data, ...)
```

```

## S3 method for class 'redcapApiConnection'
exportUserDagAssignments(
  rcon,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
importUserDagAssignments(
  rcon,
  data,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
data	data.frame with the columns username and redcap_data_access_group. The should only be one row per user name.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

When modifying existing assignments using the import method, the user must provide the unique user name and the group name. If the redcap_data_access_group column is not provided, the REDCap user will not be assigned to any group.

Value

exportUserDagAssignments method returns a data frame with two columns:

username	The unique user name for each user in the project.
redcap_data_access_group	The unique Data Access Group name to which the user is assigned.

dagMethods

Export, Import, Delete Data Access Groups from a Project

Description

These methods enable the user to export existing Data Access Groups, import new Data Access Groups, or delete Data Access Groups from a project.

Usage

```
exportDags(rcon, ...)
```

```
importDags(rcon, data, ...)
```

```
deleteDags(rcon, dags, ...)
```

```
## S3 method for class 'redcapApiConnection'  
exportDags(  
  rcon,  
  ...,  
  error_handling = getOption("redcap_error_handling"),  
  config = list(),  
  api_param = list()  
)
```

```
## S3 method for class 'redcapApiConnection'  
importDags(  
  rcon,  
  data,  
  refresh = TRUE,  
  ...,  
  error_handling = getOption("redcap_error_handling"),  
  config = list(),  
  api_param = list()  
)
```

```
## S3 method for class 'redcapApiConnection'  
deleteDags(  
  rcon,  
  dags,  
  refresh = TRUE,  
  ...,  
  error_handling = getOption("redcap_error_handling"),  
  config = list(),  
  api_param = list()  
)
```

Arguments

rcon	A redcapConnection object.
dags	character vector of names matching the unique_group_name.
data	A data.frame with two columns: data_access_group_name and unique_group_name.
refresh	logical(1). When TRUE, cached data access group data will be refreshed after the import.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

To import new data access groups, the user must provide a value for data_access_group_name with no value (NA) for unique_group_name.

To modify a group name, provide a new value for data_access_group_name with the associated unique_group_name. If unique_group_name is provided, it must match a value currently in the project.

Value

exportDags with the columns

data_access_group_name	The human readable name for the data access group.
unique_group_name	The internal unique group name.
data_access_group_id	The internal numeric identifier.

importDags has no return, but will print a message indicating the number of Data Access Groups imported.

deleteDags has no return, but will print a message indicating the number of Data Access Groups deleted.

Functions

- `exportDags()`: Export Data Access Groups from a REDCap Project
- `importDags()`: Import Data Access Groups to a project.
- `deleteDags()`: Delete Data Access Groups from a project.

See Also

```
switchDag(),
exportUserDagAssignments(),
importUserDagAssignments()
```

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

exportDags(rcon)

# Import a new Data Access Group
NewData <- data.frame(data_access_group_name = "New DAG Name",
                     unique_group_name = NA_character_)
importDags(rcon,
          data = NewData)

# Modify an existing Data Access Group Name
# The user will need to match the unique_group_name to the existing DAGs
ChangeData <- data.frame(data_access_group_name = "Altered DAG Name",
                        unique_group_name = "new_dag_name")
importDags(rcon,
          data = ChangeData)

# Delete a Data Access Group
deleteDags(rcon,
          dags = c("new_dag_name"))

## End(Not run)
```

deleteRecords

Delete Records from a Project

Description

These methods enable the user to delete records from a project.

Usage

```
deleteRecords(rcon, records, arm = NULL, ...)

## S3 method for class 'redcapApiConnection'
deleteRecords(
```

```

    rcon,
    records,
    arm = NULL,
    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list(),
    api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
records	character or integerish. Record ID's to be returned.
arm	integerish. the arm number of the arm in which the record(s) should be deleted. This can only be used if the project is longitudinal with more than one arm. If the arm parameter is not provided, the specified records will be deleted from all arms in which they exist. Whereas, if arm is provided, they will only be deleted from the specified arm.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Value

deleteRecords returns a character value giving the number of records deleted.

See Also

[exportRecords\(\)](#),
[importRecords\(\)](#),
[exportRecordsTyped\(\)](#)

Examples

```

## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Delete records
deleteRecords(rcon,
              records = c("1", "2"))

```

```
## End(Not run)
```

```
deprecated_redcapProjectInfo
```

Deprecated Functions

Description

The `redcapProjectInfo` function has been deprecated to avoid confusion with the API method now executed by `exportProjectInformation`. The replacement function is [exportBundle\(\)](#).

Usage

```
redcapProjectInfo(  
  rcon,  
  date = TRUE,  
  label = TRUE,  
  meta_data = TRUE,  
  users = TRUE,  
  instruments = TRUE,  
  events = TRUE,  
  arms = TRUE,  
  mappings = TRUE,  
  version = TRUE,  
  ...  
)  
  
## S3 method for class 'redcapApiConnection'  
redcapProjectInfo(  
  rcon,  
  date = TRUE,  
  label = TRUE,  
  meta_data = TRUE,  
  users = TRUE,  
  instruments = TRUE,  
  events = TRUE,  
  arms = TRUE,  
  mappings = TRUE,  
  version = TRUE,  
  ...,  
  v.number = ""  
)
```

Arguments

rcon	A REDCap connection object as generated by redcapConnection
date	Logical. If TRUE, user expiration dates are converted to POSIXct objects.
label	Logical. If TRUE, the user form permissions are converted to labeled factors.
meta_data	Logical. Indicates if the meta data (data dictionary) should be exported.
users	Logical. Indicates if the users table should be exported.
instruments	Logical. Indicates if the instruments table should be exported.
events	Logical. Indicates if the event names should be exported.
arms	Logical. Indicates if the arms table should be exported.
mappings	Logical. Indicates if the form-event mappings should be exported.
version	Indicates if the REDCap version number should be exported. Only applicable in REDCap 6.0.0 and higher.
...	Arguments to be passed to other methods
v.number	A character string given the desired version number should the API method not be available.

 dropRepeatingNA

Drop Row Where Repeat Instrument Is NA

Description

Drops rows where the repeat instrument is NA. Returns a data frame of records where repeat instruments have a value.

Usage

```
dropRepeatingNA(Records, rcon, quiet = FALSE)
```

Arguments

Records	A data.frame containing the records from exportRecordsTyped()
rcon	A redcapConnection object.
quiet	logical(1). When FALSE, a message is printed indicating how many rows were in Records at the start and completion of the subset.

See Also

[exportRecordsTyped\(\)](#),
[exportReportsTyped\(\)](#)

Description

These methods enable the user to export event settings, import new events, update settings for existing events, or delete events.

Usage

```
exportEvents(rcon, ...)
```

```
importEvents(rcon, data, override = FALSE, ...)
```

```
deleteEvents(rcon, events = NULL, ...)
```

```
## S3 method for class 'redcapApiConnection'  
exportEvents(  
  rcon,  
  arms = NULL,  
  ...,  
  error_handling = getOption("redcap_error_handling"),  
  config = list(),  
  api_param = list()  
)
```

```
## S3 method for class 'redcapApiConnection'  
importEvents(  
  rcon,  
  data,  
  override = FALSE,  
  refresh = TRUE,  
  ...,  
  error_handling = getOption("redcap_error_handling"),  
  config = list(),  
  api_param = list()  
)
```

```
## S3 method for class 'redcapApiConnection'  
deleteEvents(  
  rcon,  
  events = NULL,  
  refresh = TRUE,  
  ...,  
  error_handling = getOption("redcap_error_handling"),  
  config = list(),  
  api_param = list()  
)
```

)

Arguments

rcon	A redcapConnection object.
arms	character or integerish identifying the arm numbers for which event data will be exported.
events	character giving the unique event names of the events to be deleted.
data	data.frame. Must have columns event_name and arm_num. To modify existing events, it must also have a column unique_event_name. It may optionally have columns for days_offset, offset_min, offset_max. For backward compatibility, this argument may be passed as event_data.
override	logical(1). By default, data will add to or modify existing arms data. When TRUE, all the existing arms data is deleted and replaced with the contents of data.
refresh	logical(1). When TRUE, the cached arms data will be refreshed after the API action is complete.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

Exporting events is not supported for classical REDCap projects. If the user attempts to export arms for a classical project, a data frame will be returned with zero rows.

Additionally, in order for events to be exported, the project must be longitudinal, have at least one arm, and at least one event defined. When these conditions are not satisfied, exportEvents will return a data frame with zero rows.

To import new events, the user must provide data with the unique_event_name set to NA (REDCap assigns the unique event name automatically from the user provided event_name).

To modify existing events, the user must provide the unique_event_name. The other fields in the data provided will overwrite the current values for the matching event.

Deleting events—whether by deleteEvents or importEvents with override = TRUE—is a destructive act that also deletes arms and records associated with the event. This is irreversible data loss. REDCap will only permit these actions to occur in projects in Development status.

Value

exportEvents returns a data frame with the columns:

event_name	The user provided name for the event.
arm_num	The arm number the event is associated with.
unique_event_name	The REDCap generated event name.
custom_event_label	An optional user provided label that may be used in place of the event name.
event_id	REDCap's internal event identifier.
days_offset	The number of days since time zero (start of the study or project period) an event is scheduled to occur.
offset_min	The number of days before the days_offset during which the event may occur. This field is only provided for events with a days_offset.
offset_max	The number of days before the days_offset during which the event may occur. This field is only provided for events with a days_offset.

importEvents has no return and prints a message indicating how many events were added or modified.

deleteEvents has no return and prints a message indicating how many events were deleted.

Functions

- exportEvents(): Export events from a REDCap project.
- importEvents(): Add events to a project or modify existing events.
- deleteEvents(): Delete events from a project.

See Also

[exportMappings\(\)](#),
[importMappings\(\)](#)

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export all events
exportEvents(rcon)

# Export events for a subset of arms
exportEvents(rcon,
            arms = c(1, 3))

# Import new events
NewEvents <- data.frame(event_name = c("Event 1",
                                       "Event 2"),
                       arm_num = c(1, 1))
importEvents(rcon,
            data = NewEvents)

# Modify existing events
UpdateEvents <- data.frame(event_name = "Event 2 New Name",
                          arm_num = 1,
```

```

        unique_event_name = "event_2_arm_1",
        custom_event_label = "The second visit")
importEvents(rcon,
             data = UpdateEvents)

# Replace all events with a new set
NewEvents <- data.frame(event_name = c("Event 1",
                                       "Event 2",
                                       "Event 1"),
                       arm_num = c(1, 1, 2))
importEvents(rcon,
             data = NewEvents,
             override = TRUE)

# Delete events
deleteEvents(rcon,
             events = c("event_1_arm_1", "event_1_arm_2"))

## End(Not run)

```

exportBulkRecords	<i>A helper function to export multiple records and forms using a single call.</i>
-------------------	--

Description

Exports records from multiple REDCap Databases using multiple calls to [exportRecordsTyped\(\)](#)

Usage

```

exportBulkRecords(
  rcon,
  forms = NULL,
  envir = NULL,
  sep = "_",
  post = NULL,
  ...
)

```

Arguments

rcon	A redcapConnection object.
forms	A named list that is a subset of rcon's names. A specified rcon will provide a list of forms for repeated calls to exportRecordsType. If a connection reference is missing it will default to all forms. To override this default specify a connection's forms with NA to just get all data.

envir	A environment to write the resulting Records in as variables given by their name in rcon or if from a form their rcon named pasted to their form name joined by sep. If not specified the function will return a named list with the results. Will accept a number of the environment.
sep	A character string to use when joining the rcon name to the form name for storing variables.
post	A function that will run on all returned sets of Records.
...	Any additional variables to pass to <code>exportRecordsTyped()</code> .

Value

Will return a named list of the resulting records if `envir` is `NULL`. Otherwise will assign them to the specified `envir`.

Examples

```
## Not run:
unlockREDCap(c(test_conn = 'TestRedcapAPI',
               sandbox_conn = 'SandboxAPI'),
             keyring = 'MyKeyring',
             envir = globalenv(),
             url = 'https://<REDCAP_URL>/api/')

# After user interaction to unlock the local encrypted keyring
# the global environment will contain the REDCap connections
# `test_conn` and `sandbox_conn`
#
# Next the user wants to bulk specify importing all the forms
# of interest and post process

exportBulkRecords(
  rcon = list(test = test_conn,
             sand = sandbox_conn),
  forms = list(test = c('form1', 'form2')),
  envir = globalenv(),
  post = function(Records, rcon)
    {
      Records          |>
      mChoiceCast(rcon) |>
      guessDat(rcon)   |>
      widerRepeating(rcon)
    }
)

# The environment now contains the data.frames: `test.form1`, `test.form2`, `sand`.
# Each of these were retrieved, possibly using the forms argument and all were
# post processed in the same manner as specified by `post`.

## End(Not run)
```

exportBundle	<i>Perform a bundle of API calls.</i>
--------------	---------------------------------------

Description

This function is deprecated and will be removed with the release of redcapAPI 3.0.0. Its functionality is built into caching of data onto the redcapConnection object.

Several of the API calls return objects that can be used to perform various validations in exportRecords, exportReports, and other methods. Using an export bundle allows the user to call these methods once and store the result instead of issuing an additional call to the API each time a method is invoked.

For example, if the user is uploading several files to the API, without an export bundle, importFiles will utilize the exportMetaData on each call in order to perform validations. Using a bundle allows the user to download the meta data once and refer to it on every subsequent call that requires the data dictionary.

Usage

```
exportBundle(
  rcon,
  date = TRUE,
  label = TRUE,
  meta_data = TRUE,
  users = TRUE,
  instruments = TRUE,
  events = TRUE,
  arms = TRUE,
  mappings = TRUE,
  version = TRUE,
  ...
)

## S3 method for class 'redcapApiConnection'
exportBundle(
  rcon,
  date = TRUE,
  label = TRUE,
  meta_data = TRUE,
  users = TRUE,
  instruments = TRUE,
  events = TRUE,
  arms = TRUE,
  mappings = TRUE,
  version = TRUE,
  ...,
  return_object = TRUE
)
```

Arguments

rcon	A REDCap connection object as generated by redcapConnection
date	Logical. If TRUE, user expiration dates are converted to POSIXct objects.
label	Logical. If TRUE, the user form permissions are converted to labeled factors.
meta_data	Logical. Indicates if the meta data (data dictionary) should be exported.
users	Logical. Indicates if the users table should be exported.
instruments	Logical. Indicates if the instruments table should be exported.
events	Logical. Indicates if the event names should be exported.
arms	Logical. Indicates if the arms table should be exported.
mappings	Logical. Indicates if the form-event mappings should be exported.
version	Indicates if the REDCap version number should be exported. Only applicable in REDCap 6.0.0 and higher.
...	Arguments to be passed to other methods
return_object	Logical. When TRUE, the exportBundle object is returned to the workspace.

Details

The project information is stored in the option redcap_project_info. If the project is not longitudinal, the events, arms, and event-form mappings elements will be assigned character vectors instead of data frames.

exportFieldNames	<i>Export the Complete Field Names for a REDCap Project</i>
------------------	---

Description

This method enables the user to access the complete field names utilized during export and import methods. These are especially relevant when working with checkbox fields.

Usage

```
exportFieldNames(rcon, ...)

## S3 method for class 'redcapApiConnection'
exportFieldNames(
  rcon,
  fields = character(),
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)
```

Arguments

rcon	A redcapConnection object.
fields	NULL or character(1). Field name to be returned. By default, all fields are returned.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

exportFieldNames returns a data frame of the field names the user may use when performing export and import functions. This is most useful when working with checkbox fields, which have a different field name than the one used in the Meta Data. The exported/imported field names for checkbox fields have the pattern [field_name]__[coded_checkbox_value] (there are exactly three underscores separating the field name and the coded value).

Fields of types "calc", "file", and "descriptive" are not included in the export. (Signature fields also have the "file" type and are not included)

Value

exportFieldNames returns a data frame with the columns:

original_field_name	The field name as recorded in the data dictionary
choice_value	represents the raw coded value for a checkbox choice. For non-checkbox fields, this will always be
export_field_name	The field name specific to the field. For non-checkbox fields, this is the same as original_field_n

See Also

[exportMetaData\(\)](#),
[importMetaData\(\)](#),
[exportInstruments\(\)](#),
[exportMappings\(\)](#),
[importMappings\(\)](#),
[exportPdf\(\)](#)

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
```

```

        keyring = "API_KEYS",
        envir = globalenv())

# Export all of the field names
exportFieldNames(rcon)

# Export MetaData for a specific field
exportFieldNames(rcon,
                 fields = "checkbox_test")

## End(Not run)

```

exportFileRepositoryListing

Export a Listing of Folders and Files in the File Repository

Description

This method enables the user to export a list of folders and files saved to the File Repository. The listing may optionally include contents of subfolders.

Usage

```

exportFileRepositoryListing(
  rcon,
  folder_id = numeric(0),
  recursive = FALSE,
  ...
)

## S3 method for class 'redcapApiConnection'
exportFileRepositoryListing(
  rcon,
  folder_id = numeric(0),
  recursive = FALSE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
folder_id	integerish(0/1). The folder ID of a specific folder in the File Repository for which a list of files and subfolders will be exported. By default, the top-level directory of the File Repository will be used.

recursive	logical(1). When TRUE, content of subfolders will be retrieved until a full listing is produced. If FALSE, only the contents of the requested folder will be returned.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in <code>rcon\$config</code> .
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by <code>redcapAPI</code> .

Value

Returns a data frame with the columns

folder_id	The REDCap assigned ID value for the folder. Will be NA if the item is a file.
doc_id	The REDCap assigned ID value for the file. Will be NA if the item is a folder.
name	The name of the folder of file.
parent_folder	The ID of the parent folder of the item. The top-level folder is represented as 0.

See Also

[exportFromFileRepository\(\)](#),
[importToFileRepository\(\)](#),
[deleteFromFileRepository\(\)](#),
[exportFileRepository\(\)](#),
[importFileRepository\(\)](#),
[deleteFileRepository\(\)](#),
[createFileRepositoryFolder\(\)](#)

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export the top-level listing of the File Repository
exportFileRepositoryListing(rcon)

# Export the complete listing of the File Repository
exportFileRepositoryListing(rcon,
                           recursive = TRUE)

# Export the listing of a subfolder in the File Repository
```

```
exportFileRepositoryListing(rcon,
                           folder_id = 12345)

## End(Not run)
```

exportInstruments *Export Instruments Defined in a Project*

Description

These methods enable the user to view the instruments defined in the project.

Usage

```
exportInstruments(rcon, ...)

## S3 method for class 'redcapApiConnection'
exportInstruments(
  rcon,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)
```

Arguments

rcon	A redcapConnection object.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Value

Returns a data frame with the columns:

instrument_name	The REDCap generated instrument name.
instrument_label	The user provided instrument label.

See Also

```
exportMetaData(),
importMetaData(),
exportInstruments(),
exportMappings(),
importMappings(),
exportPdf()
```

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

exportInstruments(rcon)

## End(Not run)
```

exportLogging

Export Logging Records

Description

These methods enable to user to export the logging (audit trail) of all changes made to a project, including data exports, data changes, project metadata changes, modification of user rights, etc.

Usage

```
exportLogging(
  rcon,
  logtype = character(0),
  user = character(0),
  record = character(0),
  dag = character(0),
  beginTime = .POSIXct(character(0)),
  endTime = .POSIXct(character(0)),
  ...
)

## S3 method for class 'redcapApiConnection'
exportLogging(
  rcon,
  logtype = character(0),
  user = character(0),
```



```

    record = character(0),
    dag = character(0),
    beginTime = as.POSIXct(character(0)),
    endTime = as.POSIXct(character(0)),
    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list(),
    api_param = list()
  )

```

Arguments

rcon	A redcapConnection object.
logtype	character(0/1). The log event types to export. When the length is zero, all event types are exported. Otherwise, it must be one of c("export", "manage", "user", "record", "record_add", "record_edit", "record_delete", "lock_record", "page_view")
user	character(0/1). Users for whom to return logs. By default logs for all users are returned.
record	character(0/1). Record ID for which logs are to be returned. By default, logs are returned for all records.
dag	character(0/1). Data access group ID for which to return logs. By default, logs are returned for all data access groups.
beginTime	POSIXct(0/1). When given, only logs recorded after this time will be returned.
endTime	POSIXct(0/1). When given, only logs recorded before this time will be returned.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Value

Returns a data frame with columns

timestamp	The date/time of the logging record.
username	The user name of the user that performed the action being logged.
action	The classification of action being logged.
details	Details of the action being logged.
record	The record ID associated with the action being logged. When not related to a record, this will be NA

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export all of the logging events
exportLogging(rcon)

# Export all of the events for record '2'
exportLogging(rcon,
              record = "2")

# Export all of the events where a record was deleted
exportLoging(rcon,
             logtype = "record_delete")

## End(Not run)
```

 exportPdf

Export PDF file of Data Collection Instruments

Description

These methods allow the user to download PDF files of data collection instruments. The download may be with or without collected data; and may return a single record, multiple records, or all records.

Usage

```
exportPdf(
  rcon,
  dir,
  filename = "redcap_forms_download",
  record = NULL,
  events = NULL,
  instruments = NULL,
  all_records = FALSE,
  ...
)

## S3 method for class 'redcapApiConnection'
exportPdf(
  rcon,
  dir,
  filename = "redcap_forms_download",
  record = NULL,
```

```

    events = NULL,
    instruments = NULL,
    all_records = FALSE,
    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list(),
    api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
dir	character(1). The directory into which the file should be saved.
filename	character(1). The base of the file name. When record = NULL, it will be appended with "_blank.pdf". When record has a value, it will be appended with "_record_[record id].pdf"
record	character(1), integerish(1), or NULL. The record id for which forms should be downloaded.
events	character. The events for which forms should be downloaded
instruments	character. The instruments for which forms should be downloaded
all_records	logical(1). When TRUE forms for all records are downloaded. When TRUE, this overrides the records argument.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

These methods mimics the behavior of "Download PDF of Instruments" button on the REDCap user interface. They permit the user to export a PDF file for:

1. A single collection instrument (blank)
2. All instruments (blank)
3. A single instrument (with data from a single record)
4. All instruments (with data from a single record)
5. All instruments (with data from all records)

Value

exportPdf has no return. After saving the file to the local computer, a message is displayed providing the location of the file on the system.

See Also

```

exportMetaData(),
importMetaData(),
exportFieldNames(),
exportInstruments(),
exportMappings(),
importMappings()

```

exportVersion	<i>Export the REDCap Version Number</i>
---------------	---

Description

These methods enable the user to export the REDCap instance version number.

Usage

```

exportVersion(rcon, ...)

## S3 method for class 'redcapApiConnection'
exportVersion(
  rcon,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Value

Returns a character value giving the version number.

IF this function is used in a version of REDCap that does not support the method (prior to version 6.0.0), the value "5.12.2" will be returned. This is done solely for the convenience of always returning a value that can be compared against other versions.

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export the version number
exportVersion(rcon)

## End(Not run)
```

Extraction

Extraction and Assignment for redcapFactors

Description

Extract elements and make assignments to redcapFactors

Usage

```
## S3 method for class 'redcapFactor'
x[..., drop = FALSE]

## S3 method for class 'redcapFactor'
print(x, ...)
```

Arguments

x	an object of class redcapFactor
...	additional arguments to pass to other methods
drop	logical. If TRUE, unused levels are dropped.

fieldCastingFunctions *Functions for Casting Fields After Export (Post Processing)*

Description

The functions provided here allow for recasting fields after records have been exported. They generally have a similar interface to the casting strategy of [exportRecordsTyped\(\)](#), though they may not each offer all the same options.

Usage

```

recastRecords(data, rcon, fields, cast = list(), suffix = "")

castForImport(
  data,
  rcon,
  fields = NULL,
  na = list(),
  validation = list(),
  cast = list()
)

guessCast(
  data,
  rcon,
  na = isNAorBlank,
  validation,
  cast,
  quiet = FALSE,
  threshold = 0.8
)

guessDate(
  data,
  rcon,
  na = isNAorBlank,
  validation = valRx("^[0-9]{1,4}-(0?[1-9]|1[012])-(0?[1-9]|12)[0-9]|3[01])$"),
  cast = function(x, ...) as.POSIXct(x, format = "%Y-%m-%d"),
  quiet = FALSE,
  threshold = 0.8
)

mChoiceCast(data, rcon, style = "labelled", drop_fields = TRUE)

```

Arguments

<code>data</code>	data.frame with the data fields to be recoded.
<code>rcon</code>	A redcapConnection object.
<code>fields</code>	character/logical/integerish. A vector for identifying which fields to recode. When logical, the length must match the number of columns in data (i.e., recycling not permitted). A message is printed if any of the indicated fields are not a multiple choice field; no action will be taken on such fields. For this function, yes/no and true/false fields are considered multiple choice fields. Fields of class mChoice are quietly skipped.
<code>cast</code>	A named list of user specified class casting functions. The same named keys are supported as the na argument. The function will be provided the variables (x, field_name, coding). The function must return a vector of logical matching the input length. See fieldValidationAndCasting()

suffix	character(1). An optional suffix to provide if the recoded variables should be returned as new columns. For example, if recoding a field forklift_brand and suffix = "_labeled", the result will have one column with the coded values (forklift_brand) and one column with the labeled values (forklift_brand_labeled).
na	A named list of user specified functions to determine if the data is NA. This is useful when data is loaded that has coding for NA, e.g. -5 is NA. Keys must correspond to a truncated REDCap field type, i.e. date_, datetime_, date-time_seconds_, time_mm_ss, time_hh_mm_ss, time, float, number, calc, int, integer, select, radio, dropdown, yesno, truefalse, checkbox, form_complete, sql. The function will be provided the variables (x, field_name, coding). The function must return a vector of logicals matching the input. It defaults to isNAorBlank() for all entries.
validation	A named list of user specified validation functions. The same named keys are supported as the na argument. The function will be provided the variables (x, field_name, coding). The function must return a vector of logical matching the input length. Helper functions to construct these are valRx() and valChoice() . Only fields that are not identified as NA will be passed to validation functions.
quiet	Print no messages if triggered, Default=FALSE.
threshold	numeric(1). The threshold of non-NA data to trigger casting.
style	character. One of "labelled" or "coded". Default is "labelled"
drop_fields	character or NULL. A vector of field names to remove from the data.

Details

recastRecords is a post-processing function motivated initially by the need to switch between codes and labels in multiple choice fields. Field types for which no casting function is specified will be returned with no changes. It will not attempt to validate the content of fields; fields that cannot be successfully cast will be quietly returned as missing values.

castForImport is written with defaults that will return data in a format ready to be imported to a project via importRecords. All fields are returned as character vectors. If any values fail to validation check, are report is returned as an attribute named invalid. This attribute may be retrieved using [reviewInvalidRecords\(\)](#). These are then set to NA, which will be imported as blanks through the API.

guessCast is a helper function to make a guess at casting uncast columns. It will do a type cast if a validation is met above a threshold ratio of non-NA records. It modifies the existing invalid attribute to reflect the cast. This attribute may be retrieved using [reviewInvalidRecords\(\)](#). guessDate is a special cast of guessCast that has defaults set for casting a date field.

mChoiceCast is a helper function that adds the Hmisc::mChoice multiple choice class. It adds a column for a multiple choice checkbox that is cast to the Hmisc::mChoice class. Requires Hmisc to be loaded.

Zero-Coded Check Fields

A zero-coded check field is a field of the REDCap type checkbox that has a coding definition of 0, [label]. When exported, the field names for these fields is [field_name]__0. As in other checkbox fields, the raw data output returns binary values where 0 represent and unchecked box

and 1 represents a checked box. For zero-coded checkboxes, then, a value of 1 indicates that 0 was selected.

This coding rarely presents a problem when casting from raw values (as is done in `exportRecordsTyped`). However, casting from coded or labeled values can be problematic, as it In this case, it becomes indeterminate from context if the intent of 0 is 'false' or the coded value '0' ('true') ...

The situations in which casting may fail to produce the desired results are

Code	Label	Result
0	anything other than "0"	Likely to fail when casting from coded values
0	0	Likely to fail when casting from coded or labeled values

Because of the potential for miscast data, casting functions will issue a warning anytime a zero-coded check field is encountered. A separate warning is issued when a field is cast from coded or labeled values.

When casting from coded or labeled values, it is strongly recommended that the function `castCheckForImport()` be used. This function permits the user to state explicitly which values should be recognized as checked, avoiding the ambiguity resulting from the coding.

See Also

Exporting records:

`exportRecordsTyped()`,
`exportReportsTyped()`,
`fieldValidationAndCasting()`,
`reviewInvalidRecords()`

Other Post Processing Functions:

`splitForms()`,
`widerRepeated()`

Examples

```
## Not run:
# Using recastRecords after export
Recs <-
  exportRecordsTyped(rcon) |>
  recastRecords(rcon,
    fields = "dropdown_test",
    cast = list(dropdown = castCode))

# Using castForImport
castForImport(Records,
  rcon)

# Using castForImport to recast zero-coded checkbox values
castForImport(Records,
```



```

        rcon,
        cast = list(checkbox = castCheckForImport(c("0", "Unchecked"))))

# Using guessCast
exportRecordsTyped(rcon,
                    cast = raw_cast) |>
  guessCast(rcon,
            validation=valRx("^[0-9]{1,4}-(0?[1-9]|1[012])-(0?[1-9]|12)[0-9]|3[01])$"),
            cast=as.Date,
            threshold=0.6)

# Using mChoiceCast
exportRecordsTyped(rcon) |>
  mChoiceCast(rcon)

## End(Not run)

```

fieldChoiceMapping *Split a Field Choice Mapping Into a Two Column Matrix*

Description

Uses the string from the `select_choices_or_calculations` for the meta data to create a matrix of codes and their mapped labels.

Usage

```
fieldChoiceMapping(object, field_name, ...)
```

```
## S3 method for class 'character'
fieldChoiceMapping(object, field_name, ...)
```

```
## S3 method for class 'redcapApiConnection'
fieldChoiceMapping(object, field_name, ...)
```

Arguments

<code>object</code>	redcapConnection or character(1). When character, is matches the format of the meta data field choices (i.e. <code>rcon\$meta_data()\$select_choices_or_calculations</code>).
<code>field_name</code>	character(1) gives the field name for which to make the choice mapping.
<code>...</code>	Arguments to pass to other methods

Value

Returns a matrix with two columns, `choice_value` and `choice_label`

 fieldToVar

 Convert a REDCap Data Field to an R Vector

Description

Converts a field exported from REDCap into a valid R vector

Usage

```
fieldToVar(
  records,
  meta_data,
  factors = TRUE,
  dates = TRUE,
  checkboxLabels = FALSE,
  labels = TRUE,
  handlers = list(),
  mChoice = NULL,
  ...
)
```

Arguments

records	A data frame of records returned by exportRecords or exportReports
meta_data	A data frame giving the data dictionary, as returned by exportMetaData
factors	Logical, determines if checkbox, radio button, dropdown and yesno variables are converted to factors
dates	Logical, determines if date variables are converted to POSIXct format
checkboxLabels	Logical, determines if checkbox variables are labeled as "Checked" or using the checkbox label. Only applicable when factors = TRUE
labels	Logical. Determines if the variable labels are applied to the data frame.
handlers	List, Specify type conversion overrides for specific REDCap field types. E.g., handlers=list(date_ = as.Date). For datetime specifications the datetime ordering directive from the tail is dropped. The following field types are supported: date_, datetime_, datetime_seconds_, time_mm_ss, time, float, number, calc, int, integer, select, radio, dropdown, yesno, truefalse, checkbox, and form_complete.
mChoice	logical; defaults to TRUE. Convert checkboxes to mChoice if Hmisc is installed.
...,	additional arguments that are ignored.

Details

This function is called internally by exportRecords and exportReports. it is not available to the user.

`fieldValidationAndCasting`*Helper functions for exportRecordsTyped Validation and Casting*

Description

This set of functions assists in validating that the content of fields coming from REDCap match the MetaData, allowing for a validation report to be provided. The cast helpers allow for transforming the REDCap data into R data types and allowing the user to customize the end product.

Usage

```
isNAorBlank(x, ...)  
  
valRx(rx)  
  
valChoice(x, field_name, coding)  
  
valPhone(x, field_name, coding)  
  
na_values(FUN)  
  
castLabel(x, field_name, coding)  
  
castLabelCharacter(x, field_name, coding)  
  
castCode(x, field_name, coding)  
  
castCodeCharacter(x, field_name, coding)  
  
castRaw(x, field_name, coding)  
  
castChecked(x, field_name, coding)  
  
castCheckedCharacter(x, field_name, coding)  
  
castCheckLabel(x, field_name, coding)  
  
castCheckLabelCharacter(x, field_name, coding)  
  
castCheckCode(x, field_name, coding)  
  
castCheckCodeCharacter(x, field_name, coding)  
  
castCheckForImport(checked = c("Checked", "1"))  
  
castDpNumeric(dec_symbol = ",")
```

```
castDpCharacter(n_dec, dec_symbol = ",")
```

```
castTimeHHMM(x, field_name, coding)
```

```
castTimeMMSS(x, field_name, coding)
```

```
raw_cast
```

```
default_cast_no_factor
```

```
default_cast_character
```

Arguments

x	character. A vector to check.
...	Consumes anything else passed to function. I.e., field_name and coding.
rx	character. The regular expression pattern to check.
field_name	character(1). Name of the field(s)
coding	named character vector. The defined coding from the meta data.
FUN	function. A function that takes a character vector.
checked	character. Values to recognize as checked in a checkbox field.
dec_symbol	character(1). The symbol in the field used to denote a decimal.
n_dec	integerish(1). The number of decimal places permitted by the field validation.

Format

An object of class list of length 20.

An object of class list of length 24.

An object of class list of length 24.

Details

Functions passed to the na, validation, and cast parameter of `exportRecordsTyped()` all take the form of `function(x, coding, field_name)`. na and validation functions are expected to return a logical vector of the same length as the column processed. Helper routines are provided here for common cases to construct these functions.

Validation Functions:

`isNAorBlank` returns TRUE/FALSE if field is NA or blank. Helper function for constructing na overrides in `exportRecordsTyped()`.

`valRx` constructs a validation function from a regular expression pattern. The function returns a TRUE/FALSE if the value matches the pattern.

`valChoice` constructs a validation function from a set of choices defined in the MetaData. The functions returns a TRUE/FALSE if the value matches one of the choices.

`valPhone` constructs a validation function for (North American) phone numbers. It removes punctuation and spaces prior to validating with the regular expression.

`na_values` is a helper function to create a list of functions to test for NA based on field type. Useful for bulk override of NA detection for a project. The output can be directly passed to the `na` parameter of `exportRecordsTyped()`.

Casting Functions:

`castLabel` constructs a casting function for multiple choice variables. The field will be cast to return the choice label (generally more human readable). `castLabelCharacter` is an equivalent casting function that returns a character vector instead of a factor.

`castCode` constructs a casting function for multiple choice variables. Similar to `castLabel`, but the choice value is returned instead. The values are typically more compact and their meaning may not be obvious. `castCodeCharacter` is an equivalent casting function that returns a character vector instead of a factor.

`castRaw` constructs a casting function that returns the content from REDCap as it was received. It is functionally equivalent to `identity`. For multiple choice variables, the result will be coerced to numeric, if possible; otherwise, the result is character vector.

`castChecked` constructs a casting function for checkbox fields. It returns values in the form of Unchecked/Checked. `castCheckedCharacter` is an equivalent casting function that returns a character vector instead of a factor.

`castCheckLabel` and `castCheckCode` also construct casting functions for checkbox fields. For both, unchecked variables are cast to an empty string (""). Checked variables are cast to the option label and option code, respectively. `castCheckLabelCharacter` and `castCheckCodeCharacter` are equivalent casting functions that returns a character vector instead of a factor.

`castCheckForImport` is a special case function to allow the user to specify exactly which values are to be considered "Checked". Values that match are returned as 1 and all other values are returned as 0. This is motivated by the special case where the coding on a checkbox includes "0, Option". In the resulting field `checkbox__0`, a coded value of 0 actually implies the choice was selected. In order to perform an import on such data, it is necessary to cast it using `castCheckForImport(c("0"))`.

`castDpNumeric` is a casting function for fields that use the `number_ndp_comma` field type (where `n` is the number of decimal places). This function will convert the values to numeric values for use in analysis. This is a function that returns the appropriate casting function, thus the appropriate usage when using the defaults is `cast = list(number_1dp_comma = castDpNumeric())` (using the parentheses).

`castDpCharacter` is a casting function to return fields that use `number_ndp_comma` field types to character strings for import. This is a function that returns the appropriate casting function, thus the appropriate usage when casting for one decimal place is `cast = list(number_1dp_comma = castDpCharacter(1))`.

`castTimeHHMM` and `castTimeMMSS` are casting functions to facilitate importing data. They convert time data into a character format that will pass the API requirements.

Casting Lists:

`raw_cast` overrides all casting if passed as the `cast` parameter.

`default_cast_no_factor` is a list of casting functions that matches all of the default casts but with the exception that any fields that would have been cast to factors will instead be cast to characters. It is provided for the user that prefers to work absent factors. The list `default_cast_character`

is equivalent and is provided for those that prefer to describe their casting in terms of what the result is (and not what it is not).

Value

Validation and casting functions return the objects indicated in the following table:

Function Name	Object Type Returned
isNAOrBlank	logical
valRx	logical
valChoice	logical
valPhone	logical
castLabel	factor
castLabelCharacter	character
castCode	factor
castCodeCharacter	character
castRaw	character
castChecked	factor
castCheckedCharacter	character
castCheckLabel	factor
castCheckLabelCharacter	character
castCheckCode	factor
castCheckCodeCharacter	character
castCheckForImport	numeric
castDpNumeric	numeric
castDpCharacter	character
castTimeHHMM	character
castTimeMMSS	character

See Also

[fieldCastingFunctions\(\)](#),
[exportRecordsTyped\(\)](#),
[exportReportsTyped\(\)](#)

Examples

```
## Not run:
# Make a custom function to give special treatment to a field.
# In this function, the field "field_name_to_skip" will
# be cast using `castRaw`. All other fields will be cast
# using `castCode`
customCastCode <- function(x, field_name, coding){
  if (field_name == "field_name_to_skip"){
    castRaw(x, field_name, coding)
  } else {
    castCode(x, field_name, coding)
  }
}
```

```
## End(Not run)
```

fileMethods

Export, Import, or Delete Files to a Field in a REDCap Project

Description

These methods enable to the user to export a file stored in a project field, import a file, or delete an existing file.

Usage

```
exportFiles(rcon, record, field, event = NULL, dir, file_prefix = TRUE, ...)
```

```
importFiles(  
  rcon,  
  file,  
  record,  
  field,  
  event,  
  overwrite = TRUE,  
  repeat_instance = NULL,  
  ...  
)
```

```
deleteFiles(rcon, record, field, event, ...)
```

```
## S3 method for class 'redcapApiConnection'  
exportFiles(  
  rcon,  
  record,  
  field,  
  event = NULL,  
  dir,  
  file_prefix = TRUE,  
  repeat_instance = NULL,  
  ...,  
  error_handling = getOption("redcap_error_handling"),  
  config = list(),  
  api_param = list()  
)
```

```
## S3 method for class 'redcapApiConnection'  
importFiles(  
  rcon,
```

```

    file,
    record,
    field,
    event = NULL,
    overwrite = TRUE,
    repeat_instance = NULL,
    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list(),
    api_param = list()
)

## S3 method for class 'redcapApiConnection'
deleteFiles(
  rcon,
  record = NULL,
  field = NULL,
  event = NULL,
  repeat_instance = NULL,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
record	character(1) or integerish(1). The record ID in which the desired file is stored.
field	character(1). The field name in which the file is stored.
event	character(1) or NULL. The event name for the file. This applies only to longitudinal projects. If the event is not supplied for a longitudinal project, the API will return an error message
repeat_instance	integerish(1) or NULL. The repeat instance number of the repeating event or the repeating instrument. When available in your instance of REDCap, and passed as NULL, the API will assume a value of 1.
file	character(1). The file path to the file to be imported.
overwrite	logical(1). When FALSE, the function checks if a file already exists for that record. If a file exists, the function terminates to prevent overwriting. When TRUE, no additional check is performed.
dir	character(1). A directory/folder to which the file will be saved. By default, the working directory is used.
file_prefix	logical(1). Determines if a prefix is appended to the file name. The prefix takes the form [record_id]-[event_name]-[file_name]. The file name is always the same name of the file as it exists in REDCap.

...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in <code>rcon\$config</code> .
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by <code>redcapAPI</code> .

Details

These functions only export, import, or delete a single file.

When exporting, the file cannot be changed; whatever name exists in REDCap is the name that will be used. The record ID and event name may be appended as a prefix.

Value

`exportFiles` has no return and displays a message with file path to which the exported file was saved.

`importFiles` has no return and displays a message indicating whether the import was successful.

`deleteFiles` has no return and displays a message indicating whether the file was successfully deleted from the project.

Functions

- `exportFiles()`: Export a file from a REDCap project.
- `importFiles()`: Import a file to a REDCap project.
- `deleteFiles()`: Delete a file from a REDCap project.

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

save_to_dir <- tempdir()

# Export a file
exportFiles(rcon,
            record = 1,
            field = "file_upload_test",
            dir = save_to_dir)

# Export a file for a specific event
exportFiles(rcon,
            record = 1,
```

```

        field = "file_upload_test",
        event = "event_1_arm_1",
        dir = save_to_dir)

# Import a file
importFiles(rcon,
            file = "file_to_upload.txt"
            record = 1,
            field = "file_upload_test")

# Delete a file
deleteFiles(rcon,
            record = 1,
            field = "file_upload_test")

## End(Not run)

```

fileRepositoryMethods *Export, Import, or Delete Multiple Files from the File Repository*

Description

These methods enable the user to export, import, or delete entire folders of files from the file repository. These actions may be done recursively to include subfolders as well.

Usage

```

exportFileRepository(
  rcon,
  folder_id,
  dir = getwd(),
  dir_create = FALSE,
  recursive = FALSE,
  ...
)

importFileRepository(rcon, dir, folder_id = numeric(0), ...)

deleteFileRepository(rcon, folder_id, recursive = FALSE, ...)

## S3 method for class 'redcapApiConnection'
exportFileRepository(
  rcon,
  folder_id = numeric(0),
  dir = getwd(),
  dir_create = FALSE,
  recursive = FALSE,

```

```

    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list(),
    api_param = list()
)

## S3 method for class 'redcapApiConnection'
importFileRepository(
  rcon,
  dir,
  folder_id = numeric(0),
  dag_id = numeric(0),
  role_id = numeric(0),
  recursive = FALSE,
  ...,
  refresh = TRUE,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
deleteFileRepository(
  rcon,
  folder_id,
  recursive = FALSE,
  refresh = TRUE,
  ...,
  confirm = c("ask", "no", "yes"),
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
folder_id	integerish(0/1) The folder ID with the files to download. If length 0, defaults to the top-level directory.
dir	character(1). A directory on the local system to which the files are to be saved. Defaults to the working directory.
dir_create	logical(1). When TRUE create the directory dir if it does not already exist. Defaults to FALSE. If dir does not exist and dir_create = FALSE, an error is thrown.
dag_id	integerish(0/1) The ID of a data access group. When provided, access to the folder will be restricted to the DAG.
role_id	integerish(0/1) The ID of a role. When provided, access to the folder will be restricted to users with that role.

recursive	logical(1). When TRUE, export all subfolders and their files as well.
refresh	logical(1). When TRUE (default), the cached File Repository data on rcon will be refreshed.
confirm	character. One of c("ask", "no", "yes"). When "ask", user will be prompted to confirm the deletion. When "no", the function will terminate with no action. When "yes", the function will proceed without confirmation (useful for automated processes).
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

`deleteFileRepository` will only delete files and cannot delete folders.

Deleted files will remain in the recycling bin for up to 30 days.

Value

`exportFileRepository` and `importFileRepository` display messages giving the directory to which files were saved to the local machine and File Repository, respectively. They also return a data frame with the columns:

directory	The directory in which the file is saved.
filename	The name of the saved file.

`deleteFileRepository` displays a message giving the files that were deleted from the File Repository. It also returns a data frame with the columns:

folder_id	The REDCap assigned ID number for the folder. This will be NA for files.
doc_id	The REDCap assigned ID number for the file.
name	The filename of the deleted files.
parent_folder	The folder ID of parent folder.

Functions

- `exportFileRepository()`: Export multiple files from the File Repository.
- `importFileRepository()`: Import multiple files to the File Repository.

- `deleteFileRepository()`: Delete multiple files from the File Repository.

See Also

```
exportFromFileRepository(),  
importToFileRepository(),  
deleteFromFileRepository(),  
exportFileRepositoryListing(),  
createFileRepositoryFolder()
```

Examples

```
## Not run:  
unlockREDCap(connections = c(rcon = "project_alias"),  
              url = "your_redcap_url",  
              keyring = "API_KEYS",  
              envir = globalenv())  
  
save_location <- tempdir()  
  
# Export the top-level file repository folder  
exportFileRepository(rcon,  
                    folder_id = numeric(0),  
                    dir = save_location)  
  
# Export the entire repository  
exportFileRepository(rcon,  
                    folder_id = numeric(0),  
                    dir = save_location,  
                    recursive = TRUE)  
  
# Export a file repository folder below the top-level  
exportFileRepository(rcon,  
                    folder_id = 12345,  
                    dir = save_location)  
  
# Import the files from a folder to the top-level file repository  
importFileRepository(rcon,  
                    dir = "path/to/folder")  
  
# Import the files from a folder to sub folder of the file repository  
importFileRepository(rcon,  
                    dir = "path/to/folder",  
                    folder_id = 12345)  
  
# Import the files from a folder and assign to a specific  
# Data Access Group  
importFileRepository(rcon,  
                    dir = "path/to/folder",  
                    dag_id = 789)  
  
# Delete files from the top-level folder of the file repository
```

```

deleteFileRepository(rcon,
                    folder_id = numeric(0))

# Delete all the files from the file repository
deleteFileRepository(rcon,
                    folder_id = numeric(0),
                    recursive = TRUE)

## End(Not run)

```

fileRepositoryPath *Reconstruct the file repository path*

Description

Reconstruct the file repository path

Usage

```
fileRepositoryPath(doc_id = numeric(0), folder_id = numeric(0), fileRepo)
```

Arguments

doc_id	integerish(0/1). The document ID for which the file path should be returned. Only one of doc_id or folder_id should be specified.
folder_id	integerish(0/1). The folder ID for which the file path should be returned. Only one of doc_id or folder_id should be specified.
fileRepo	data.frame with the file repository listing. Typically provided by rcon\$fileRepository()

filterEmptyRow *Remove Rows Containing Only Missing Values*

Description

Evaluates each row of a data frame for missingness. If all fields (excluding the identifying fields) are missing, the row is removed from the data. For the purpose of this function, redcap_data_access_group is considered an identifying field.

Usage

```
filterEmptyRow(data, rcon)
```

Arguments

data	A data.frame to be filtered.
rcon	A redcapConnection object.

See Also

[exportRecordsTyped\(\)](#),
[exportReportsTyped\(\)](#)

fromFileRepositoryMethods

Export, Import, and Delete Individual Files from the File Repository

Description

These methods enable the user to export, import, or delete individual files from a REDCap project's file repository.

Usage

```
exportFromFileRepository(rcon, doc_id, dir = getwd(), dir_create = FALSE, ...)
```

```
importToFileRepository(rcon, file, folder_id = numeric(0), ...)
```

```
deleteFromFileRepository(rcon, doc_id, ...)
```

```
## S3 method for class 'redcapApiConnection'
exportFromFileRepository(
  rcon,
  doc_id,
  dir = getwd(),
  dir_create = FALSE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)
```

```
## S3 method for class 'redcapApiConnection'
importToFileRepository(
  rcon,
  file,
  folder_id = numeric(0),
  ...,
  refresh = TRUE,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)
```

```
## S3 method for class 'redcapApiConnection'
```

```

deleteFromFileRepository(
  rcon,
  doc_id,
  ...,
  refresh = TRUE,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
doc_id	integerish(1). The document ID to be downloaded.
folder_id	integerish(0/1). The ID of the folder into which the file is to be imported. If length is zero, it is imported to the top-level folder.
file	character(1). A file on the local system to be imported to the File Repository.
dir	character(1). A directory on the local system to which the file is to be saved. Defaults to the working directory.
dir_create	logical(1). Create the directory dir if it does not already exist. Defaults to FALSE. If dir does not exist and create = FALSE, an error is thrown.
refresh	logical(1) When TRUE, the cached File Repository data on rcon will be refreshed.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

When a file is deleted, the file will remain in the Recycle Bin folder for up to 30 days.

Value

`exportFromFileRepository`, `importToFileRepository`, and `deleteFromFileRepository` each return a data frame with the columns:

directory	The directory in which the file is saved.
filename	The name of the saved file.

Additionally, `exportFromFileRepository` displays a message with the file path to which the file was saved on the local computer.

`importToFileRepository` displays a message with the path in the file repository to which the file is imported.

`deleteFromFileRepository` displays a message with the path on the file repository from which the file was deleted.

Functions

- `exportFromFileRepository()`: Export a file from the file repository.
- `importToFileRepository()`: Import a file to the file repository.
- `deleteFromFileRepository()`: Delete a file from the file repository.

See Also

[exportFileRepository\(\)](#),
[importFileRepository\(\)](#),
[deleteFileRepository\(\)](#),
[exportFileRepositoryListing\(\)](#),
[createFileRepositoryFolder\(\)](#)

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

write_to_path <- tempdir()

# Export a file from the repository
exportFromFileRepository(rcon,
                        doc_id = 12345,
                        dir = write_to_path)

# Export a file and create the target directory if it does not exist
exportFromFileRepository(rcon,
                        doc_id = 12345,
                        dir = write_to_path,
                        dir_create = TRUE)

# Import a file to the top-level directory of the file repository
importFileToRepository(rcon,
                      file = "file_to_import.txt")

# Import a file to a specific directory of the file repository
importFileToRepository(rcon,
                      file = "file_to_import.txt",
```

```
        folder_id = 678)

# Delete a file from the file repository
deleteFileFromRepository(rcon,
                        doc_id = 12345)

## End(Not run)
```

getProjectIdFields *Return a vector of the Project ID Fields*

Description

Returns a character vector listing the project ID fields. This will be at most a vector of length two. The first element will be the first field in the meta data. The second, if provided, will be the name of the secondary unique field specified in the project.

Usage

```
getProjectIdFields(rcon)
```

Arguments

rcon A redcapConnection object.

Value

Returns a character vector with the field names that uniquely identify an experimental unit.

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

getProjectIdFields(rcon)

## End(Not run)
```

importRecords	<i>Import Records to a Project</i>
---------------	------------------------------------

Description

These methods enable the user to import new records or update existing records to a project.

Usage

```
importRecords(
  rcon,
  data,
  overwriteBehavior = c("normal", "overwrite"),
  returnContent = c("count", "ids", "nothing", "auto_ids"),
  returnData = FALSE,
  logfile = "",
  ...
)

## S3 method for class 'redcapApiConnection'
importRecords(
  rcon,
  data,
  overwriteBehavior = c("normal", "overwrite"),
  returnContent = c("count", "ids", "nothing", "auto_ids"),
  returnData = FALSE,
  logfile = "",
  force_auto_number = FALSE,
  ...,
  batch.size = -1,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)
```

Arguments

rcon	A redcapConnection object.
data	A data.frame to be imported to the project.
overwriteBehavior	character(1). One of c("normal", "overwrite"). "normal" prevents blank fields from overwriting populated fields. "overwrite" causes blanks to overwrite data in the database.
returnContent	character(1). One of c("count", "ids", "nothing", "auto_ids"). 'count' returns the number of records imported; 'ids' returns the record ids that are imported; 'nothing' returns no message; 'auto_ids' returns a list of pairs of all

	record IDs that were imported. If used when <code>force_auto_number = FALSE</code> , the value will be changed to <code>'ids'</code> .
<code>returnData</code>	<code>logical(1)</code> . When <code>TRUE</code> , prevents the REDCap import and instead returns the data frame that would have been given for import. This is sometimes helpful if the API import fails without providing an informative message. The data frame can be written to a csv and uploaded using the interactive tools to troubleshoot the problem.
<code>logfile</code>	<code>character(1)</code> . An optional filepath (preferably <code>.txt</code>) in which to print the log of errors and warnings about the data. When <code>""</code> , the log is printed to the console.
<code>...</code>	Arguments to pass to other methods
<code>force_auto_number</code>	<code>logical(1)</code> . If record auto-numbering has been enabled in the project, it may be desirable to import records where each record's record name is automatically determined by REDCap (just as it does in the user interface). When <code>TRUE</code> , the record names provided in the request will not be used (although they are still required in order to associate multiple rows of data to an individual record in the request); instead those records in the request will receive new record names during the import process. It is recommended that the user use <code>returnContent = "auto_ids"</code> when <code>force_auto_number = TRUE</code>
<code>batch.size</code>	<code>integerish(1)</code> . Specifies the number of subjects to be included in each batch of a batched export or import. Non-positive numbers export/import the entire operation in a single batch. Batching may be beneficial to prevent tying up smaller servers. See Details.
<code>error_handling</code>	<code>character(1)</code> . One of <code>c("error", "null")</code> . An option for how to handle errors returned by the API. see <code>redcapError()</code> .
<code>config</code>	A named list. Additional configuration parameters to pass to <code>httr::POST()</code> . These are appended to any parameters in <code>rcon\$config</code> .
<code>api_param</code>	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by <code>redcapAPI</code> .

Details

`importRecords` prevents the most common import errors by testing the data before attempting the import. Namely

1. Check that all variables in data exist in the REDCap data dictionary.
2. Check that the record id variable exists
3. Force the record id variable to the first position in the data frame (with a warning)
4. Remove calculated fields (with a warning)
5. Verify that REDCap date fields are represented in the data frame as either `character`, `POSIXct`, or `Date` class objects.
6. Determine if values are within their specified validation limits.

See the documentation for [validateImport\(\)](#) for detailed explanations of the validation.

A 'batched' import is one where the export is performed over a series of API calls rather than one large call. For large projects on small servers, this may prevent a single user from tying up the server and forcing others to wait on a larger job.

Value

`importRecords`, when `returnData = FALSE`, returns the content from the API response designated by the `returnContent` argument.

`importRecords`, when `returnData = TRUE`, returns the data frame that was internally prepared for import. This data frame has values transformed from R objects to character values the API will accept.

See Also

[exportRecords\(\)](#),
[deleteRecords\(\)](#),
[exportRecordsTyped\(\)](#)

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Import records
NewData <- data.frame(record_id = c(1, 2, 3),
                     age = c(27, 43, 32),
                     date_of_visit = rep(Sys.Date(), 3))
importRecords(rcon,
              data = NewData)

# Import records and save validation info to a file
NewData <- data.frame(record_id = c(1, 2, 3),
                     age = c(27, 43, 32),
                     date_of_visit = rep(Sys.Date(), 3))
importRecords(rcon,
              data = NewData,
              logfile = "import-validation-notes.txt")

## End(Not run)
```

invalidSummary	<i>Helper functions for formatting validation failure report</i>
----------------	--

Description

`exportRecordsTyped()` may have an `invalid` attribute if validations fail. This data has some routines which help locate the failing records.

Usage

```
## S3 method for class 'invalid'
format(x, ...)

## S3 method for class 'invalid'
print(x, ...)

## S3 method for class 'invalid'
summary(object, ...)
```

Arguments

<code>x</code>	The <code>invalid</code> class object.
<code>...</code>	additional arguments to print
<code>object</code>	The <code>invalid</code> class object.

Examples

```
## Not run:
rcon <- redcapConnection(url=[YOUR_REDCAP_URL], token=[API_TOKEN])

rec <- exportRecordsTyped(rcon)

attr(rec, "invalid")

## End(Not run)
```

isZeroCodedCheckField	<i>Identify Check Fields with a Zero Coded Option</i>
-----------------------	---

Description

Check fields that have 0 as a coding option can confuse certain data processing steps because it can be difficult to differentiate if a 0 value represents an unchecked or checked option. Identifying these fields is important to handling them correctly.

Usage

```
isZeroCodedCheckField(field_name)

warnOfZeroCodedCheckCasting(field_name, x)

warnZeroCodedFieldPresent(field_names)
```

Arguments

```
field_name    character(1) The name of a field to be tested.
x             atomic object.
field_names   character vector of field names.
```

Value

isZeroCodedCheckField returns a logical(1)

warnOfZeroCodedCheckCasting has no return and issues a warning if the field name appears to be zero-coded.

warnZeroCodedFieldPresent has no return and issues a warning if any of the fields passed appear to be zero-coded.

Zero-Coded Check Fields

A zero-coded check field is a field of the REDCap type checkbox that has a coding definition of 0, [label]. When exported, the field names for these fields is [field_name]__0. As in other checkbox fields, the raw data output returns binary values where 0 represent an unchecked box and 1 represents a checked box. For zero-coded checkboxes, then, a value of 1 indicates that 0 was selected.

This coding rarely presents a problem when casting from raw values (as is done in exportRecordsTyped). However, casting from coded or labeled values can be problematic, as it In this case, it becomes indeterminate from context if the intent of 0 is 'false' or the coded value '0' ('true') ...

The situations in which casting may fail to produce the desired results are

Code	Label	Result
0	anything other than "0"	Likely to fail when casting from coded values
0	0	Likely to fail when casting from coded or labeled values

Because of the potential for miscast data, casting functions will issue a warning anytime a zero-coded check field is encountered. A separate warning is issued when a field is cast from coded or labeled values.

When casting from coded or labeled values, it is strongly recommended that the function `castCheckForImport()` be used. This function permits the user to state explicitly which values should be recognized as checked, avoiding the ambiguity resulting from the coding.

Examples

```
## Not run:
isZeroCodedCheckField("check_field___x")

isZeroCodedCheckField("check_field___0")

x <- factor(c(1, 0, 1, 0, 0),
            levels = 0:1)
warnOfZeroCodedCheckCasting(field_name = "check_field___0",
                             x = x)

warnZeroCodedFieldPresent(c("check_field___x", "check_field___0"))

## End(Not run)
```

makeApiCall

Make REDCap API Calls

Description

Constructs and executes API calls to the REDCap API. These are left deliberately abstract in order to be flexible enough to support the redcapAPI functions, but also allow users to execute calls for new REDCap features that are not yet implemented.

Usage

```
makeApiCall(rcon, body = list(), config = list())
```

Arguments

rcon	A redcapConnection object.
body	list List of parameters to be passed to <code>httr::POST()</code> 's body argument
config	list A list of options to be passed to <code>httr::POST()</code> . These will be appended to the config options included in the rcon object.

Details

The intent of this function is to provide an approach to execute calls to the REDCap API that is both consistent and flexible. Importantly, this provides a framework for making calls to the API using features that the R package does not yet support (redcapAPI will always lag behind when REDCap adds new features).

The API call consists of two components: the "body" and the "config." The body of the call contains all of the arguments being passed to the API. When building body components, be sure to review the documentation. options to the API that require an array need to be built using `vectorToApiBodyList`; options that are not an array can be entered directly (see examples).

The config list is a list of parameters to pass to `httpr::POST()`. Refer to documentation there for details.

Using the settings stored in the `redcapConnection` object, a response code of 408 (Request Timeout), 500 (Internal Server Error), 502 (Bad Gateway), 503 (Service Unavailable), or 504 (Gateway Timeout) will prompt reattempts at calling the API. See `redcapConnection()` for details. If the API reaches its attempt limit without resolving to any other code, the last response is returned. If any other response code is returned at any point in the retry loop, the loop breaks and returns that response.

Examples

```
## Not run:
url <- "Enter your API URL here"
token <- "Enter your API token here"

rcon <- redcapConnection(url = url,
                        token = token)

MetaData <-
  makeApiCall(rcon = rcon,
             body = list(content = "metadata",
                        format = "csv",
                        returnFormat = "csv"))
MetaData <- utils::read.csv(text = as.character(MetaData),
                          stringsAsFactors = FALSE,
                          na.strings = "")

# Call to export Meta Data (Data Dictionary) for specific fields

fields <- vectorToApiBodyList(vector = c("row_purpose",
                                       "prereq_radio"),
                             parameter_name = "fields")

MetaData <-
  makeApiCall(rcon = rcon,
             body = c(list(content = "metadata",
                        format = "csv",
                        returnFormat = "csv"),
                    fields))
MetaData <- read.csv(text = as.character(MetaData),
                   stringsAsFactors = FALSE,
                   na.strings = "")

# Basic call to export records

Records <- makeApiCall(rcon = rcon,
                    body = list(content = "record",
                              format = "csv",
                              returnFormat = "csv",
```

```

                                type = "flat"))

Records <- read.csv(text = as.character(Records),
                   stringsAsFactors = FALSE,
                   na.strings = "")

# Call to export records for a single form.
# Note that even though we are interested in a single form, the
# API requires an array, so we use vectorToApiBodyList

export_form <- vectorToApiBodyList("branching_logic",
                                  parameter_name = "forms")
Records <- makeApiCall(rcon = rcon,
                     body = c(list(content = "record",
                                   format = "csv",
                                   returnFormat = "csv",
                                   type = "flat"),
                              export_form))
Records <- read.csv(text = as.character(Records),
                   stringsAsFactors = FALSE,
                   na.strings = "")

# Call to export records with a pipe delimiter.

Records <- makeApiCall(rcon = rcon,
                     body = list(content = "record",
                                 format = "csv",
                                 returnFormat = "csv",
                                 type = "flat",
                                 csvDelimiter = "|"))
Records <- read.csv(text = as.character(Records),
                   stringsAsFactors = FALSE,
                   na.strings = "",
                   sep = "|")

# Call to export records created/modified after 25 Dec 2022 14:00.

Records <- makeApiCall(rcon = rcon,
                     body = list(content = "record",
                                 format = "csv",
                                 returnFormat = "csv",
                                 type = "flat",
                                 dateRangeBegin = "2022-12-25 14:00:00"))

Records <- read.csv(text = as.character(Records),
                   stringsAsFactors = FALSE,
                   na.strings = "")

```

```
## End(Not run)
```

```
mappingMethods
```

```
Export and Import Instrument-Event Mappings
```

Description

These methods enable the user to export and add/modify the mappings between instruments and events. The information provided with the methods corresponds to what is provided in the 'Designate Instruments for My Events' page in the user interface.

Usage

```
exportMappings(rcon, arms, ...)
```

```
importMappings(rcon, data, refresh = TRUE, ...)
```

```
## S3 method for class 'redcapApiConnection'
exportMappings(
  rcon,
  arms = NULL,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)
```

```
## S3 method for class 'redcapApiConnection'
importMappings(
  rcon,
  data,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)
```

Arguments

rcon	A redcapConnection object.
arms	integerish or character. A vector of arm numbers. When given, mappings are only exported for the given arms.
data	data.frame with columns arm_num, unique_event_name, and form. See Details

refresh	logical(1). When TRUE, cached mappings in the rcon object are refreshed after the import.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see <code>redcapError()</code> .
config	A named list. Additional configuration parameters to pass to <code>httr::POST()</code> . These are appended to any parameters in <code>rcon\$config</code> .
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by <code>redcapAPI</code> .

Details

These methods are only applicable to longitudinal projects. If the project information reports that the project is not longitudinal, a data frame with 0 rows is returned without calling the API.

Value

`exportMappings` returns a data frame with the columns:

arm_num	The arm number for the unique event mapped to the instrument.
unique_event_name	The unique event name to which the instrument is assigned.
form	The REDCap assigned instrument name mapped to the event.

Functions

- `exportMappings()`: Export instrument-event mappings.
- `importMappings()`: Import instrument-event mappings to the project.

See Also

`exportFieldNames()`,
`exportInstruments()`,
`exportMetaData()`,
`importMetaData()`,
`exportPdf()`

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export all mappings
exportMappings(rcon)
```

```

# Export mappings for a specific arm
exportMappings(rcon,
              arms = 1)

# Import mappings
NewMapping <-
  data.frame(arm_num = c(1, 1, 2),
            unique_event_name = c("event_1_arm_1",
                                  "event_2_arm_1",
                                  "event_1_arm_2"),
            form = c("registration",
                    "follow_up",
                    "registration"))

importMapping(rcon,
             data = NewMapping)

## End(Not run)

```

massert

Conduct Multiple Assertions

Description

This documentation attempts to describe arguments to make assertions on arguments. In order to prevent confusion, it is imperative to develop some terminology up front. We will use *function argument* to refer to an argument of the function for which we are conducting assertions. We will use *assertion argument* to refer to arguments to pass to the assertion function being applied to a function argument. Lastly, we will use *massert argument* to refer to arguments to massert

Usage

```
massert(formula, fun, ..., fixed = list())
```

Arguments

formula	A one sided formula naming the arguments on which the assertion will be performed.
fun	An assertion function to perform.
...	Additional lists. Each argument provided is a named list of assertion arguments. The name of each element in a list should match the name of a function argument. <code>lower = list(var1 = 0, var2 = 10)</code> sets the <i>assertion argument</i> lower = 0 for <i>function argument</i> var1; and sets the <i>assertion argument</i> lower = 10 for function argument var2. The <i>massert arguments</i> in ... may themselves be named or unnamed.
fixed	A named list of arguments that are fixed across all assertions.

Details

Only one assert function may be utilized in each call to `massert`. This allows for all numeric variables to be checked in one call, all logical variables to be checked in a subsequent call, etc.

metaDataMethods	<i>Export and Import the Project Meta Data (Data Dictionary)</i>
-----------------	--

Description

These methods provide the user access to a REDCap project's data dictionary. The data dictionary may be exported or altered via the import.

Usage

```
exportMetaData(rcon, ...)

importMetaData(rcon, data, ...)

## S3 method for class 'redcapApiConnection'
exportMetaData(
  rcon,
  fields = character(),
  forms = character(),
  ...,
  drop_utf8 = FALSE,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
importMetaData(
  rcon,
  data,
  refresh = TRUE,
  ...,
  field_types = REDCAP_METADATA_FIELDTYPE,
  validation_types = REDCAP_METADATA_VALIDATION_TYPE,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)
```

Arguments

`rcon` A `redcapConnection` object.

fields	character vector of field names for which the metadata is to be retrieved.
forms	character vector of forms for which the metadata is to be retrieved. If a form name is given, all of the fields on that form will be returned, regardless of whether it is included in fields or not. Form names should match those in the second column of the data dictionary, and not the display names shown on the web interface.
data	data.frame with the Meta Data to import.
refresh	logical(1). When TRUE, the cached metadata and instruments will be refreshed after the import.
drop_utf8	logical(1). When TRUE, non-ASCII characters will be replaced with empty characters.
...	Arguments to pass to other methods
field_types	character giving the acceptable field types when validating the field_type column. This
validation_types	character giving the acceptable values for the text_validation_or_show_slider_number column.
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

When importing meta data, the following conditions apply:

Field names may start with a letter, have any number of letters, numbers, or underscores, and end in either a letter or a number. All letters must be lowercase (the function will coerce them to lower before checking for duplicate field names).

Form names may start with a letter, have any number of letters, numbers, or underscores, and end in either a letter or a number. All letters must be lowercase (the function will coerce them to lower before checking for duplicate field names).

Field types may be one of REDCAP_METADATA_FIELDTYPE. In the event that a new field type is added to REDCap and redcapAPI is not yet updated, the user may add additional values via c(REDCAP_METADATA_FIELDTYPE, "new_type").

Validation types may be one of REDCAP_METADATA_VALIDATION_TYPE or NA. As with field types, additional values can be appended if necessary. Only fields that have a field type of "text" or "slider" should have a validation type. "slider" fields should be either NA (do not display the selected number) or "number".

For multiple choice fields, the selection choices take the format of "code1, label1 | ... | coden, labeln". For slider fields, the format is "left_value | mid_value | right_value". Any of those values may be an empty character, but the two pipes are required, nonetheless.

For calculated fields, the values in "select_choices_or_calculations" are currently unvalidated.

All of the values between brackets in the branching logic must be either a field name or an existing unique event name (such as "event_1_arm_1")

Value

exportMetaData returns a data frame. Not all 18 (or more) columns are documented here, but the most commonly used within redcapAPI are (these may appear in a different order in the data frame):

field_name	The name of a field in the project.
filed_label	The human-readable form of the field name.
form_name	The name of the form on which the field is found.
field_type	One of two fields used to determine how a field is transformed into an R object.
select_choices_or_calculations	The second field used to determine how a field is translated into an R object.
text_validation_type_or_show_slider_number	Describes how fields are validated. For slider fields, it gives the limits and number of ticks.
field_annotation	Contains annotations such as units of measures. Also contains action text for some fields.

importMetaData has no return and displays a message indicating the number of fields that were imported.

Functions

- exportMetaData(): Export the Meta Data (Data Dictionary) of a REDCap Project
- importMetaData(): Import New Meta Data (Data Dictionary) Definitions

See Also

[exportFieldNames\(\)](#),
[exportInstruments\(\)](#),
[exportMappings\(\)](#),
[importMappings\(\)](#),
[exportPdf\(\)](#)

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export the MetaData from REDCap
exportMetaData(rcon)

# Export MetaData for select fields only (returns two rows)
```



```

exportMetaData(rcon,
               fields = c("dropdown_test", "radio_test"))

# Export MetaData for select forms
exportMetaData(rcon,
               forms = c("first_form", "second_form"))

# MetaData my be exported for a combination of fields and forms
exportMetaData(rcon,
               fields = c("dropdown_test", "radio_test"),
               forms = c("first_form", "second_form"))

# Alter and import new MetaData (change the record ID label)
Meta <- exportMetaData(rcon)

Meta$field_label[1] <- "A better description of the Record ID"
importMetaData(rcon,
               data = Meta)

## End(Not run)

```

missingSummary

Report of Missing Values

Description

Returns a data frame of subject events with missing values.

Usage

```

missingSummary(
  rcon,
  excludeMissingForms = TRUE,
  ...,
  fixed_fields = REDCAP_SYSTEM_FIELDS
)

## S3 method for class 'redcapApiConnection'
missingSummary(
  rcon,
  excludeMissingForms = TRUE,
  ...,
  fixed_fields = REDCAP_SYSTEM_FIELDS,
  exportRecordsArgs = list(),
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

```
missingSummary_offline(
  records,
  meta_data,
  excludeMissingForms = TRUE,
  fixed_fields = REDCAP_SYSTEM_FIELDS
)
```

Arguments

<code>rcon</code>	A redcapConnection object.
<code>excludeMissingForms</code>	logical(1) When TRUE, forms where all fields are missing are assumed to be deliberately missing data and are excluded from the count of missing values. An example when this is desirable is if a patient did not experience an adverse event; the adverse event form would contain no data and the empty fields should not be considered missing data.
<code>...</code>	Arguments to pass to other methods
<code>fixed_fields</code>	character A vector of field names that will be used as the identifying fields in the output summary. This always includes the record identifier (ie, the first field in the data dictionary). By default it also includes any fields identified in REDCAP_SYSTEM_FIELDS, which are fields that REDCap adds to exports to identify arms, events, etc..
<code>exportRecordsArgs</code>	named list. Arguments to pass to exportRecords. This allows for testing specific forms, events, and/or records. Internally, any setting passed for factors, labels, dates, survey, or dag arguments will be ignored.
<code>error_handling</code>	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
<code>config</code>	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in <code>rcon\$config</code> .
<code>api_param</code>	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.
<code>records</code>	character(1) A filename pointing to the raw records download from REDCap.
<code>meta_data</code>	character(1) A filename pointing to the data dictionary download from REDCap.

Details

The intention of this function is to generate a list of subject events that are missing and could potentially be values that should have been entered.

The branching logic from the data dictionary is parsed and translated into an R expression. When a field with branching logic passes the logical statement, it is evaluated with `is.na`, otherwise, it is set to FALSE (non-missing, because there was never an opportunity to provide a value). The utility of this function is limited to simple logic where all of the data exist within the same row. Any complex statements using events will result in a failure.

Optionally, forms that are entirely missing can be determined to be non-missing. This is applicable when, for instance, a patient did not have an adverse event. In this case, a form dedicated to adverse events would contain meaningless missing values and could be excluded from the report.

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Generate a summary of missing values for the entire project
missingSummary(rcon)

# Generate a summary of missing values for a single form
missingSummary(rcon,
              exportRecordsArgs = list(forms = "target_form"))

## End(Not run)
```

parseBranchingLogic *Parse Branching Logic*

Description

Branching logic from the REDCap Data Dictionary is parsed into R Code and returned as expressions. These can be evaluated if desired and allow the user to determine if missing values are truly missing or not required because the branching logic prevented the variable from being presented.

Usage

```
parseBranchingLogic(l)
```

Arguments

1 A vector of REDCap branching logic statements. These are usually passed as the vector `meta_data$branching_logic`.

Details

For a study, I was asked to identify which subjects had missing values so that remaining data could be collected. The initial pass of `is.na` produced a lot of subjects missing values where there was no need to collect data because they did not qualify for some variables in the branching logic. Parsing the logic allowed me to determine which values we expected to be missing and narrow the search to just those subjects with legitimately missing values.

The utility of this function is limited to simple logic where all of the data exist within the same row. Any complex statements using events will result in a failure.

Value

Returns a list of unevaluated expressions.

See Also

[missingSummary\(\)](#)

Examples

```
## Not run:
parseBranchingLogic("[age] > 30")
parseBranchingLogic("[dropdown_test] = 'd'")
parseBranchingLogic(c("[age] > 30",
                      "[dropdown_test] = 'd'"))

## End(Not run)
```

```
prepUserImportData      Prepare User Data for Import
```

Description

Prepares a data frame for import via the API. Allows for data to be passed in either the raw format or the labeled data received from exportUsers.

Usage

```
prepUserImportData(data, rcon, consolidate = TRUE, user_role = FALSE)
```

Arguments

data	data.frame with the structure of redcapAPI:::REDCAP_USER_STRUCTURE. It may also have additional columns for the form and export access of each of the instruments.
rcon	A redcapConnection object.
consolidate	logical(1) If TRUE, the form and data export access values will be read from the expanded columns. Otherwise, the consolidated values (as provided by the API export) are utilized.
user_role	logical(1) If TRUE, the code will treat the data as if it is being prepared for importing User Roles.

Value

Returns a data.frame with user settings that will be accepted by the API for import.

See Also

```
importUsers(),  
importUserRoles()
```

Examples

```
## Not run:  
unlockREDCap(connections = c(rcon = "project_alias"),  
              url = "your_redcap_url",  
              keyring = "API_KEYS",  
              envir = globalenv())  
  
# Prep user data  
NewData <- data.frame(username = "target_user",  
                      design = 1,  
                      api_export = "Access",  
                      api_import = "No Access",  
                      surveys_enabled = 0)  
prepUserImportData(data = NewData,  
                  rcon = rcon)  
  
# Prep user role data  
NewData <- data.frame(unique_role_name = "target_user",  
                      design = 1,  
                      api_export = "Access",  
                      api_import = "No Access",  
                      surveys_enabled = 0)  
prepUserImportData(data = NewData,  
                  rcon = rcon)  
  
## End(Not run)
```

projectInformationMethods

Export and Import Project Settings

Description

These methods enable the user to export or update project level settings, such as the project title, if it is longitudinal, if surveys are enabled, etc.

Usage

```
exportProjectInformation(rcon, ...)  
  
importProjectInformation(rcon, data, ...)
```

```

## S3 method for class 'redcapApiConnection'
exportProjectInformation(
  rcon,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
importProjectInformation(
  rcon,
  data,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
data	data.frame with only one row and any subset of allowable fields to be updated. See Details.
refresh	logical(1). If TRUE, the cached project information will be updated after the import.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

When importing, fields that are not editable will be quietly removed prior to import. This allows the user to use the result of `exportProjectInformation` as a template for the import.

For any values that are boolean, they should be represented as either a '0' (no/false) or '1' (yes/true).

It is not required for data to have all of the fields, but only the fields the user wishes to update (see examples).

The following project attributes can be updated:

- project_title

- project_language
- purpose
- purpose_other
- project_notes
- custom_record_label
- secondary_unique_field
- is_longitudinal
- surveys_enabled
- scheduling_enabled
- record_autonumbering_enabled
- randomization_enabled
- project_irb_number
- project_grant_number
- project_pi_firstname
- project_pi_lastname
- display_today_now_button
- bypass_branching_erase_field_prompt

Value

exportProjectInformation returns a data frame with the columns

project_id	The internal ID number assigned to the project.
project_title	The project title given to the project.
creation_time	The date/time the project was created.
production_time	The date/time the project was moved into production status.
in_production	Boolean value indicating if the project is in production status.
project_language	The language associated with the project.
purpose	An integerish value identifying the purpose of the project. 0 = "Practice/Just for
purpose_other	The user supplied character value given when the project purpose is 'Other'.
project_notes	The user supplied notes about the project.
custom_record_label	The user provided custom label for the record identifier field.
secondary_unique_field	The name of the secondary unique field, if this has been configured.
is_longitudinal	Boolean value indicating if the project is a longitudinal project.
has_repeating_instruments_or_events	Boolean value indicating if the repeating instruments or events module has been
surveys_enabled	Boolean value indicating if the surveys module has been enabled.
scheduling_enabled	Boolean value indicating if the scheduling module has been enabled.
record_autonumbering_enabled	Boolean value indicating if the record autonumbering feature has been enabled.
randomization_enabled	Boolean value indicating if the randomization module has been enabled.
ddp_enabled	Boolean value indicating if dynamic data pull has been enabled for a project (m
project_irb_number	The user provided IRB number for the project.
project_grant_number	The user provided grant number for the project.
project_pi_firstname	The first name of the principal investigator.

purgeRestoreProject *Purge and Restore Project Data*

Description

These functions are primarily intended to assist with testing features of redcapAPI. Purging and restoring project data permits us to perform tests on different project structures without having to manage multiple projects or API tokens.

When purging project data, many of these actions may only be performed with a project in development status, as they are potentially destructive and may result in data loss. It is a good practice to back up your data and project structure before purging a project.

Usage

```
preserveProject(object, ...)  
  
## S3 method for class 'redcapApiConnection'  
preserveProject(  
  object,  
  ...,  
  error_handling = getOption("redcap_error_handling"),  
  config = list()  
)  
  
purgeProject(object, ...)  
  
## S3 method for class 'redcapApiConnection'  
purgeProject(  
  object,  
  arms = FALSE,  
  events = FALSE,  
  users = FALSE,  
  user_roles = FALSE,  
  dags = FALSE,  
  records = FALSE,  
  purge_all = FALSE,  
  flush = TRUE,  
  ...,  
  error_handling = getOption("redcap_error_handling"),  
  config = list()  
)  
  
restoreProject(object, ...)  
  
## S3 method for class 'redcapApiConnection'  
restoreProject(  

```

```

    object,
    project_information = NULL,
    arms = NULL,
    events = NULL,
    meta_data = NULL,
    mappings = NULL,
    repeating_instruments = NULL,
    users = NULL,
    user_roles = NULL,
    user_role_assignments = NULL,
    dags = NULL,
    dag_assignments = NULL,
    records = NULL,
    flush = TRUE,
    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list()
)

## S3 method for class 'list'
restoreProject(
  object,
  rcon,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list()
)

```

Arguments

<code>object</code> , <code>rcon</code>	A <code>redcapConnection</code> object. Except in <code>restoreProject.list</code> , where <code>object</code> is a list of data frames to use in restoring the project.
<code>...</code>	Arguments to pass to other methods
<code>error_handling</code>	<code>character(1)</code> . One of <code>c("error", "null")</code> . An option for how to handle errors returned by the API. see redcapError() .
<code>config</code>	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in <code>rcon\$config</code> .
<code>arms</code>	Either <code>logical(1)</code> indicating if arms data should be purged from the project; or a <code>data.frame</code> for restoring arms data via <code>importArms</code> .
<code>events</code>	Either <code>logical(1)</code> indicating if events data should be purged from the project; or a <code>data.frame</code> for restoring events data via <code>importEvents</code>
<code>users</code>	Either <code>logical(1)</code> indicating if users data should be purged from the project; or a <code>data.frame</code> for restoring users data via <code>importUsers</code> . NOT YET IMPLEMENTED
<code>user_roles</code>	Either <code>logical(1)</code> indicating if user roles data should be purged from the project; or a <code>data.frame</code> for restoring user roles data via <code>importUserRoles</code> . NOT YET IMPLEMENTED

dags	Either <code>logical(1)</code> indicating if DAG data should be purged from the project; or a <code>data.frame</code> for restoring DAGs data via <code>importDags</code> . NOT YET IMPLEMENTED
records	Either <code>logical(1)</code> indicating if records data should be purged from the project; or a <code>data.frame</code> for restoring records data via <code>importRecords</code>
purge_all	<code>logical(1)</code> . A shortcut option to purge all data elements from a project.
flush	<code>logical(1)</code> . When TRUE, all caches in the connection object will be flushed after completing the operation. This is highly recommended.
project_information	<code>data.frame</code> for restoring data. Provides the project settings to load via <code>importProjectInformation</code> .
meta_data	A <code>data.frame</code> for restoring metadata data via <code>importMetaData</code> . The API does not support deleting metadata, but an import replaces the existing metadata.
mappings	A <code>data.frame</code> for restoring instrument-event mappings via <code>importMappings</code> . The API does not support deleting mappings, but an import replaces the existing mappings.
repeating_instruments	A <code>data.frame</code> for restoring repeating instruments configuration via importRepeatingInstrumentsEven . The API does not support deleting repeating instruments, but an import replaces the existing instruments. NOT YET IMPLEMENTED
user_role_assignments	A <code>data.frame</code> for restoring user-role assignments via <code>importUserRoleAssignments</code> . The API does not support deleting assignments, but an import replaces the existing assignments. NOT YET IMPLEMENTED.
dag_assignments	A <code>data.frame</code> for restoring DAG assignments via <code>importDagAssignments</code> . The API does not support deleting assignments, but an import replaces the existing assignments. NOT YET IMPLEMENTED.

Details

When restoring a project, all arguments are optional. Any argument that is NULL will result in no import being made. The order of reconstructing the project is (purging data occurs in the reverse order):

1. Update project information
2. Import Arms Data
3. Import Events Data
4. Import Meta Data
5. Import Mappings
6. Import Repeating Instruments
7. Import Users
8. Import User Roles
9. Import User-Role Assignments
10. Import Data Access Groups
11. Import Data Access Group Assignments
12. Import Records

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Preserve a project
preserveProject(rcon)

# Purge a project
purgeProject(rcon,
             purge_all = TRUE)

# Restore a project
restoreProject(rcon)

## End(Not run)
```

recodeCheck

Change labeling of checkbox variables

Description

Rewrites the labeling of checkbox variables from Checked/Unchecked to Yes/No (or some other user specified labeling).

Usage

```
recodeCheck(
  df,
  vars,
  old = c("Unchecked", "Checked"),
  new = c("No", "Yes"),
  reverse = FALSE
)
```

Arguments

df	A data frame, presumably retrieved from REDCap, though not a strict requirement.
vars	Optional character vector of variables to convert. If left missing, all of the variables in df that are identified as checkbox variables are relabeled. See 'Details' for more about identifying checkbox variables.
old	A character vector to be passed to factor. This indicates the levels to be replaced and their order.

new	A character vector of labels to replace the values in levels. The first value becomes the reference value.
reverse	For convenience, if the user would prefer to reverse the order of the elements in levels and labels, simply set this to TRUE.

Details

checkbox variables are not identified using the metadata from the REDCap database. Instead, variables are scanned, and those variables in which every value is in levels are assumed to be checkbox variables.

Realistically, this could be used to relabel any set of factors with identical labels, regardless of the data source. The number of labels is not limited, but levels and labels should have the same length.

The actual code to perform this is not particularly difficult (`df[checkbox] <- lapply(df[checkbox], factor, levels=levels, labels=labels)`), but checkbox variables are common enough in REDCap (and the Checked/Unchecked scheme so unpalatable) that a quick way to replace the labels was highly desirable

reconstituteFileFromExport

Save a File to a Local Directory from a Response

Description

Converts the file from a response object and saves it to the local file directory.

Usage

```
reconstituteFileFromExport(
  response,
  dir,
  dir_create = FALSE,
  file_prefix = "",
  filename = character(0)
)
```

Arguments

response	An object of class response.
dir	character(1) A directory on the local file system into which the file will be saved.
dir_create	logical(1) If TRUE and the directory does not exist, it will be created. Defaults to FALSE. If dir does not exist and create = FALSE, an error is thrown.
file_prefix	character(1) An optional prefix to prepend to the file name. This may be desirable to explicitly associate files with a record and/or event.

filename character(0/1) An optional filename. This is used in the case where a filename is being provided. If this has length 0, the filename will be extracted from the API response.

See Also

```
exportFiles(),
exportFromFileRepository(),
exportFileRepository(),
exportPdf()
```

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

response <- makeApiCall(rcon,
                      body = list(content = 'file',
                                  action = 'export',
                                  record = '1',
                                  field = 'file_upload_test',
                                  event = 'event_1_arm_1'))
reconstituteFileFromExport(response,
                          dir = tempdir())

## End(Not run)
```

recordsManagementMethods

Export Next Record Name or Rename a Record

Description

These methods enable the user to get the next record name (when auto numbering is enabled) or rename an existing record.

Usage

```
exportNextRecordName(rcon, ...)

renameRecord(rcon, record_name, new_record_name, arm = NULL, ...)

## S3 method for class 'redcapApiConnection'
exportNextRecordName(
  rcon,
```

```

    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list(),
    api_param = list()
)

## S3 method for class 'redcapApiConnection'
renameRecord(
  rcon,
  record_name,
  new_record_name,
  arm = NULL,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
record_name	character(1) or integerish(1). The name of an existing record in the project.
new_record_name	character(1) or integerish(1). The new name to give to the record.
arm	character(1) or NULL, an optional arm number. If NULL, then all records with same name across all arms on which it exists (if longitudinal with multiple arms) will be renamed to new record name, otherwise it will rename the record only in the specified arm.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Value

exportNextRecordName returns an integerish value. The value is determined by looking up the highest record ID number in the project and incrementing it by 1.

renameRecord return a logical value that indicates if the operation was successful.

Functions

- [exportNextRecordName\(\)](#): Get the ID number for the next record to be created.
- [renameRecord\(\)](#): Rename an existing record.

See Also

```
exportRecords(),  
exportReports(),  
importRecords(),  
deleteRecords(),  
exportRecordsTyped(),  
exportReportsTyped()
```

Examples

```
## Not run:  
unlockREDCap(connections = c(rcon = "project_alias"),  
              url = "your_redcap_url",  
              keyring = "API_KEYS",  
              envir = globalenv())  
  
# Get the next record name  
exportNextRecordName(rcon)  
  
# Rename an existing record  
renameRecord(rcon,  
            record_name = "1",  
            new_record_name = "42")  
  
## End(Not run)
```

recordsMethods

Export Records and Reports

Description

These methods enable the user to export records and reports from a project.

Usage

```
exportRecords(  
  rcon,  
  factors = TRUE,  
  fields = NULL,  
  forms = NULL,  
  records = NULL,  
  events = NULL,  
  labels = TRUE,  
  dates = TRUE,  
  drop = NULL,  
  survey = TRUE,  
  dag = TRUE,
```



```
checkboxLabels = FALSE,
colClasses = character(0),
...
)

exportRecords_offline(
  dataFile,
  metaDataFile,
  factors = TRUE,
  fields = NULL,
  forms = NULL,
  labels = TRUE,
  dates = TRUE,
  checkboxLabels = FALSE,
  colClasses = NA,
  ...,
  meta_data
)

exportReports(
  rcon,
  report_id,
  factors = TRUE,
  labels = TRUE,
  dates = TRUE,
  drop = NULL,
  checkboxLabels = FALSE,
  ...
)

## S3 method for class 'redcapApiConnection'
exportRecords(
  rcon,
  factors = TRUE,
  fields = NULL,
  forms = NULL,
  records = NULL,
  events = NULL,
  labels = TRUE,
  dates = TRUE,
  drop = NULL,
  survey = TRUE,
  dag = TRUE,
  checkboxLabels = FALSE,
  colClasses = character(0),
  ...,
  batch.size = -1,
  error_handling = getOption("redcap_error_handling"),
```

```

    config = list(),
    api_param = list(),
    form_complete_auto = TRUE
)

## S3 method for class 'redcapApiConnection'
exportReports(
  rcon,
  report_id,
  factors = TRUE,
  labels = TRUE,
  dates = TRUE,
  drop = NULL,
  checkboxLabels = FALSE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
report_id	integerish(1). Gives the report id of the desired report. This is located on the Report Builder page of the user interface.
factors	logical(1). When TRUE, multiple choice fields will be returned as factors. Otherwise, they are returned as character values. See 'Exporting Records' for more on how this interacts with the checkboxLabels argument.
fields	character. Fields to be returned. When NULL, all fields are returned.
forms	character. Forms to be returned. When NULL, all forms are returned.
records	character or integerish. Record ID's to be returned. When NULL, all records are returned.
events	character. Events to be returned from a longitudinal database. When NULL, all events are returned.
labels	logical(1). When TRUE, field labels are attached to each column as an attribute.
dates	logical(1). When TRUE, date variables are converted to POSIXct objects.
drop	character. An optional vector of REDCap field names to remove from the dataset. Ignored when NULL. Any fields in this argument that do not exist in the project will be ignored.
survey	logical(1). specifies whether or not to export the survey identifier field (redcap_survey_identifier) or survey timestamp fields ([form_name]_timestamp) when surveys are utilized in the project.
dag	logical(1). When TRUE, the system field redcap_data_access_group is included in the export. This option is only viable if the user whose token is being

	used to make the API request is not in a data access group. If the user is in a group, then this flag will revert to FALSE.
checkboxLabels	logical(1). When FALSE labels are applied as "Unchecked"/"Checked". When TRUE, they are applied as ""/[field_label] where [field_label] is the label assigned to the level in the data dictionary.
form_complete_auto	logical(1). When TRUE (default), the [form]_complete fields for any form from which at least one variable is requested will automatically be retrieved. When FALSE, these fields must be explicitly requested.
colClasses	Named character vector. Column classes passed to <code>utils::read.csv()</code> calls. Useful to force the interpretation of a column in a specific type and avoid an unexpected recast.
batch.size	integerish(1). Specifies the number of subjects to be included in each batch of a batched export or import. Non-positive numbers export/import the entire operation in a single batch. Batching may be beneficial to prevent tying up smaller servers. See Details.
dataFile	character(1). Gives the location of the dataset downloaded from REDCap. This should be the raw (unlabeled) data set.
metaDataFile	character(1). Gives the location of the data dictionary downloaded from REDCap.
...	Arguments to pass to other methods
error_handling	character(1). One of <code>c("error", "null")</code> . An option for how to handle errors returned by the API. see <code>redcapError()</code> .
config	A named list. Additional configuration parameters to pass to <code>httr::POST()</code> . These are appended to any parameters in <code>rcon\$config</code> .
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by <code>redcapAPI</code> .
meta_data	Deprecated version of <code>metaDataFile</code> .

Details

It is unnecessary to include "redcap_event_name" in the fields argument. This field is automatically exported for any longitudinal database. If the user does include it in the fields argument, it is removed quietly in the parameter checks.

There are four ways the data from checkbox variables may be represented depending on the values of `factors` and `checkboxLabels`. The most common are the first and third rows of the table below. When `checkboxLabels = TRUE`, either the coded value or the labeled value is returned if the box is checked, or an empty string if it is not.

factors	checkboxLabels	Output
FALSE	FALSE	0 / 1
FALSE	TRUE	"" / code
TRUE	FALSE	Unchecked / Checked
TRUE	TRUE	"" / label

The 'offline' version of `exportReports` operates on the raw (unlabeled) data file downloaded from REDCap along with the data dictionary. This is made available for instances where the API cannot be accessed for some reason (such as waiting for API approval from the REDCap administrator).

A 'batched' export (or import) is one where the export is performed over a series of API calls rather than one large call. For large projects on small servers, this may prevent a single user from tying up the server and forcing others to wait on a larger job. The batched export is performed by first calling the API to export the record identifier field (the first field in the meta data). The unique ID's are then assigned a batch number with no more than `batch.size` ID's in any single batch. The batches are exported from the API and stacked together.

In longitudinal projects, `batch.size` may not necessarily be the number of records exported in each batch. If `batch.size` is ten and there are four records per patient, each batch will consist of 40 records. Thus, if the user is concerned about tying up the server with a large, longitudinal project, it would be prudent to use a smaller batch size.

Value

`exportRecords` returns a data frame with the project data. The data will be formatted consistent with the meta data and the arguments provided by the user.

`exportReports` returns a data frame with the data from the requested report. The data will be formatted consistent with the meta data and the arguments provided by the user.

Functions

- `exportRecords()`: Export records from a project.
- `exportRecords_offline()`: Format records from REDCap data file exports.
- `exportReports()`: Export data via a report.

See Also

`exportRecordsTyped()`,
`exportReportsTyped()`,
`importRecords()`,
`deleteRecords()`,
`exportNextRecordName()`,
`renameRecord()`

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export records
exportRecords(rcon)

# Export records in batches of one hundred IDs
exportRecords(rcon,
```

```
        batch.size = 100)

# Export records without factors
exportRecords(rcon,
             factors = FALSE)

# Export a report
exportReports(rcon,
             report_id = 12345)

## End(Not run)
```

recordsTypedMethods *Export Records or Reports From a Project*

Description

These methods enable the user to export records from a database or from a report. These methods have more control for casting fields to R objects than `exportRecords`.

Usage

```
exportRecordsTyped(
  rcon,
  fields = NULL,
  drop_fields = NULL,
  forms = NULL,
  records = NULL,
  events = NULL,
  ...
)

exportReportsTyped(rcon, report_id, ...)

## S3 method for class 'redcapApiConnection'
exportRecordsTyped(
  rcon,
  fields = NULL,
  drop_fields = NULL,
  forms = NULL,
  records = NULL,
  events = NULL,
  survey = TRUE,
  dag = TRUE,
```

```

    date_begin = NULL,
    date_end = NULL,
    na = list(),
    validation = list(),
    cast = list(),
    assignment = list(label = stripHTMLandUnicode, units = unitsFieldAnnotation),
    filter_empty_rows = TRUE,
    ...,
    config = list(),
    api_param = list(),
    csv_delimiter = ",",
    batch_size = NULL,
    error_handling = getOption("redcap_error_handling")
)

## S3 method for class 'redcapOfflineConnection'
exportRecordsTyped(
  rcon,
  fields = NULL,
  drop_fields = NULL,
  forms = NULL,
  records = NULL,
  events = NULL,
  na = list(),
  validation = list(),
  cast = list(),
  assignment = list(label = stripHTMLandUnicode, units = unitsFieldAnnotation),
  ...
)

## S3 method for class 'redcapApiConnection'
exportReportsTyped(
  rcon,
  report_id,
  drop_fields = NULL,
  na = list(),
  validation = list(),
  cast = list(),
  assignment = list(label = stripHTMLandUnicode, units = unitsFieldAnnotation),
  ...,
  config = list(),
  api_param = list(),
  csv_delimiter = ",",
)

```

Arguments

`rcon` A redcapConnection object.

report_id	integerish(1). The ID number of the report to be exported.
fields	character or NULL. Vector of fields to be returned. If NULL, all fields are returned (unless forms is specified).
drop_fields	character or NULL. A vector of field names to remove from the export.
forms	character or NULL. Vector of forms to be returned. If NULL, all forms are returned (unless fields is specified).
records	character or integerish. A vector of study ID's to be returned. If NULL, all subjects are returned.
events	A character vector of events to be returned from a longitudinal database. If NULL, all events are returned. When using a redcapOfflineConnection object, this argument is unvalidated, and only rows that match one of the values given are returned; misspellings may result in unexpected results.
survey	logical(1). When TRUE, the survey identifier field (e.g., redcap_survey_identifier) and survey timestamp fields (e.g., [form_name]_timestamp) will be exported (relevant only when surveys are utilized in the project).
dag	logical(1). When TRUE the redcap_data_access_group field will be included in the export \ when data access groups are utilized in the project. This flag is only viable if the user whose token is being used to make the API request is not in a data access group. If the user is in a group, then this flag will revert to its default value.
date_begin	POSIXct(1) or NULL. Ignored if NULL (default). Otherwise, records created or modified after this date will be returned.
date_end	POSIXct(1) or NULL. Ignored if NULL (default). Otherwise, records created or modified before this date will be returned.
na	A named list of user specified functions to determine if the data is NA. This is useful when data is loaded that has coding for NA, e.g. -5 is NA. Keys must correspond to a truncated REDCap field type, i.e. date_, datetime_, date-time_seconds_, time_mm_ss, time_hh_mm_ss, time, float, number, calc, int, integer, select, radio, dropdown, yesno, truefalse, checkbox, form_complete, sql. The function will be provided the variables (x, field_name, coding). The function must return a vector of logicals matching the input. It defaults to isNAorBlank() for all entries.
validation	A named list of user specified validation functions. The same named keys are supported as the na argument. The function will be provided the variables (x, field_name, coding). The function must return a vector of logical matching the input length. Helper functions to construct these are valRx() and valChoice() . Only fields that are not identified as NA will be passed to validation functions.
cast	A named list of user specified class casting functions. The same named keys are supported as the na argument. The function will be provided the variables (x, field_name, coding). The function must return a vector of logical matching the input length. See fieldValidationAndCasting()
assignment	A named list of functions. These functions are provided, field_name, label, description and field_type and return a list of attributes to assign to the column. Defaults to creating a label attribute from the stripped HTML and UNICODE raw label and scanning for units="UNITS" in description

filter_empty_rows	logical(1). Filter out empty rows post retrieval. Defaults to TRUE.
csv_delimiter	character. One of c(", ", "\t", ";", " ", "^"). Designates the delimiter for the CSV file received from the API.
batch_size	integerish(1) or NULL. When NULL, all records are pulled. Otherwise, the records all pulled in batches of this size.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httptr::POST() . These are appended to any parameters in <code>rcon\$config</code> .
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by <code>redcapAPI</code> .

Details

The 'offline' method operates on the raw (unlabeled) data file downloaded from REDCap along with the data dictionary. This is made available for instances where the API cannot be accessed for some reason (such as waiting for API approval from the REDCap administrator).

Record Identifier Fields:

In all calls, the project's ID fields will be included—there is no option provided to prevent this. Additionally, if the project has a secondary unique field specified, it will also be included. Inclusion of these fields is necessary to support some post-processing functions.

By default, the system fields `redcap_event_name`, `redcap_repeat_instrument`, and `redcap_repeat_instance` are exported (when they are appropriate to the project). These are automatically included by the API. However, if the user omits any of these in `fields` or designates one in `drop_fields`, the final result will honor those conditions. Excluding any of these identifiers may cause problems with some post-processing functions that operate on repeating instrument data.

The combination of the project ID field, secondary unique field, and the system fields are what uniquely identify an experimental unit. In nearly all cases, it is desirable to have them all included.

Record Batching:

A 'batched' export is one where the export is performed over a series of API calls rather than one large call. For large projects on small servers, this may prevent a single user from tying up the server and forcing others to wait on a larger job. The batched export is performed by first calling the API to export the subject identifier field (the first field in the meta data). The unique ID's are then assigned a batch number with no more than `batch_size` ID's in any single batch. The batches are exported from the API and stacked together.

In longitudinal projects, `batch_size` may not necessarily be the number of records exported in each batch. If `batch_size` is ten and there are four records per patient, each batch will consist of 40 records. Thus, if the user is concerned about tying up the server with a large, longitudinal project, it would be prudent to use a smaller batch size.

Inversion of Control:

The final product of calling this is a `data.frame` with columns that have been type cast to most commonly used analysis class (e.g. `factor`). This version allows the user to override any step of this process by specifying a different function for each of the stages of the type casting. The algorithm is as follows:

1. Detect NAs in returned data (`na` argument).
2. Run `validate` functions for the `field_types`.
3. On the fields that are not NA and pass `validate` do the specified cast.

It is expected that the `na` and `validate` overrides should rarely be used. Their exposure via the function parameters is to future proof against possible bugs in the defaults, and allows for things that higher versions of REDCap add as possible field types. I.e., the overrides are for use to continue using the library when errors or changes to REDCap occur.

The cast override is one where users can specify things that were controlled by an ever increasing set of flags before. E.g., `dates=as.Date` was an addition to allow dates in the previous version to be overridden if the user wanted to use the `Date` class. In this version, it would appear called as `cast=list(_date=as.Date)`. See [fieldValidationAndCasting\(\)](#) for a full listing of package provided cast functions.

Value

`exportRecordsTyped` returns a data frame with the formatted data.

`exportReportsTyped` returns a data frame with the formatted data.

Functions

- `exportRecordsTyped()`: Export records with type casting.
- `exportReportsTyped()`: Export reports with type casting.
- `exportRecordsTyped(redcapOfflineConnection)`: Export records without API access.

Zero-Coded Check Fields

A zero-coded check field is a field of the REDCap type checkbox that has a coding definition of `0, [label]`. When exported, the field names for these fields is `[field_name]__0`. As in other checkbox fields, the raw data output returns binary values where 0 represent an unchecked box and 1 represents a checked box. For zero-coded checkboxes, then, a value of 1 indicates that 0 was selected.

This coding rarely presents a problem when casting from raw values (as is done in `exportRecordsTyped`). However, casting from coded or labeled values can be problematic, as in this case, it becomes indeterminate from context if the intent of 0 is 'false' or the coded value '0' ('true') ...

The situations in which casting may fail to produce the desired results are

Code	Label	Result
0	anything other than "0"	Likely to fail when casting from coded values
0	0	Likely to fail when casting from coded or labeled values

Because of the potential for miscast data, casting functions will issue a warning anytime a zero-

coded check field is encountered. A separate warning is issued when a field is cast from coded or labeled values.

When casting from coded or labeled values, it is strongly recommended that the function `castCheckForImport()` be used. This function permits the user to state explicitly which values should be recognized as checked, avoiding the ambiguity resulting from the coding.

See Also

Other records exporting functions:

`exportRecords()`,
`exportReports()`,
`exportBulkRecords()`

Field validations and casting:

`fieldValidationAndCasting()`,
`reviewInvalidRecords()`

Post-processing functionality:

`recastRecords()`,
`guessCast()`,
`guessDate()`,
`castForImport()`,
`mChoiceCast()`,
`splitForms()`,
`widerRepeated()`

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export records with default settings
exportRecordsTyped(rcon)

# Export records with no factors
exportRecordsTyped(rcon,
                  cast = default_cast_character)

# Export records for specific records
exportRecordsTyped(rcon,
                  records = 1:3)

# Export records for specific instruments
exportRecordsTyped(rcon,
                  forms = c("registration", "visit_1", "medications"))

# Export records using filterLogic, an API parameter not provided
```

```

# in the exportRecordsTyped function signature
exportRecordsTyped(
  rcon,
  records = 1:3,
  api_param = list(filterLogic = "[age_at_enrollment] > 25")
)

# Export a report
exportReports(rcon,
              report_id = 12345)

# Export records using files downloaded from the user interface
rcon_off <-
  offlineConnection(
    meta_data =
      system.file(file.path("extdata/offlineConnectionFiles",
                            "TestRedcapAPI_DataDictionary.csv"),
                  package = "redcapAPI"),
    records =
      system.file(file.path("extdata/offlineConnectionFiles",
                            "TestRedcapAPI_Records.csv"),
                  package = "redcapAPI"))

exportRecordsTyped(rcon_off)

## End(Not run)

```

redcapConnection	<i>Connect to a REDCap Database</i>
------------------	-------------------------------------

Description

These methods enable the user to create a connection object used to access the database.

Usage

```

redcapConnection(
  url = getOption("redcap_api_url"),
  token,
  config = httr::config(),
  retries = 5,
  retry_interval = 2^(seq_len(retries)),
  retry_quietly = TRUE
)

```

```

## S3 method for class 'redcapApiConnection'
print(x, ...)

offlineConnection(
  meta_data = NULL,
  arms = NULL,
  events = NULL,
  instruments = NULL,
  field_names = NULL,
  mapping = NULL,
  repeat_instrument = NULL,
  users = NULL,
  user_roles = NULL,
  user_role_assignment = NULL,
  dags = NULL,
  dag_assignment = NULL,
  project_info = NULL,
  version = NULL,
  file_repo = NULL,
  records = NULL
)

## S3 method for class 'redcapOfflineConnection'
print(x, ...)

```

Arguments

url	character(1). URL for the user's REDCap database API.
token	character(1) REDCap API token
config	A list to be passed to <code>httr::POST()</code> . This allows the user to set additional configurations for the API calls, such as certificates, SSL version, etc. For the majority of users, this does not need to be altered.
retries	integerish(1). Sets the number of attempts to make to the API if a timeout error is encountered. Must be a positive value.
retry_interval	numeric. Sets the intervals (in seconds) at which retries are attempted. By default, set at a 2^r where r is the r th retry (ie, 2, 4, 8, 16, ...). For fixed intervals, provide a single value. Values will be recycled to match the number of retries.
retry_quietly	logical(1). When FALSE, messages will be shown giving the status of the API calls. Defaults to TRUE.
x	redcapConnection object to be printed
...	arguments to pass to other methods
meta_data	Either a character giving the file from which the metadata can be read, or a <code>data.frame</code> .
arms	Either a character giving the file from which the arms can be read, or a <code>data.frame</code> .

events	Either a character giving the file from which the events can be read, or a <code>data.frame</code> .
instruments	Either a character giving the file from which the instruments can be read, or a <code>data.frame</code> .
field_names	Either a character giving the file from which the field names can be read, or a <code>data.frame</code> .
mapping	Either a character giving the file from which the Event Instrument mappings can be read, or a <code>data.frame</code> .
repeat_instrument	Either a character giving the file from which the Repeating Instruments and Events settings can be read, or a <code>data.frame</code> . Note: The REDCap GUI does not offer a download file of these settings (at the time of this writing).
users	Either a character giving the file from which the User settings can be read, or a <code>data.frame</code> .
user_roles	Either a character giving the file from which the User Roles can be read, or a <code>data.frame</code> .
user_role_assignment	Either a character giving the file from which the User-Role Assignments can be read, or a <code>data.frame</code> .
dags	Either a character giving the file from which the Data Access Groups can be read, or a <code>data.frame</code> .
dag_assignment	Either a character giving the file from which the Data Access Group Assignments can be read, or a <code>data.frame</code> .
project_info	Either a character giving the file from which the Project Information can be read, or a <code>data.frame</code> .
version	Either a character giving the file from which the version can be read, or a <code>data.frame</code> .
file_repo	Either a character giving the file from which the File Repository Listing can be read, or a <code>data.frame</code> .
records	Either a character giving the file from which the Records can be read, or a <code>data.frame</code> . This should be the raw data as downloaded from the API, for instance. Using labeled or formatted data is likely to result in errors when passed to other functions.

Details

`redcapConnection` objects will retrieve and cache various forms of project information. This can make metadata, arms, dags, events, instruments, fieldnames, arm-event mappings, users, version, project information, fileRepository, and repeating instruments available directly from the `redcapConnection` object. The retrieval of these objects uses the default values of the respective export functions (excepting the file repository, which uses `recursive = TRUE`).

For each of these objects, there are four methods that can be called from the `redcapConnection` object:

Function type	Purpose	Example
---------------	---------	---------

<code>[info_type]</code>	Returns the information from the connection object	<code>rcon\$metadata()</code>
<code>has_[info_type]</code>	Returns a boolean indicating if the information is cached	<code>rcon\$has_metadata()</code>
<code>flush_[info_type]</code>	Purges the information from the connection object	<code>rcon\$flush_metadata()</code>
<code>refresh_[info_type]</code>	Replaces the information with a new call to the API	<code>rcon\$refresh_metadata()</code>

Information is cached for

- metadata
- arms
- events
- instruments
- fieldnames
- mapping (field-event mappings)
- repeatInstrumentEvent
- users
- user_roles
- user_role_assignment
- dags
- dag_assignment
- projectInformation
- version
- fileRepository

There is also a `flush_all` and `refresh_all` method that will purge the entire cache and refresh the entire cache, respectively.

The `redcapConnection` object also stores the user preferences for handling repeated attempts to call the API. In the event of a timeout error or server unavailability, these settings allow a system pause before attempting another API call. In the event all of the retries fail, the error message of the last attempt will be returned. These settings may be altered at any time using the methods `rcon$set_retries(r)`, `rcon$set_retry_interval(ri)`, and `rcon$set_retry_quietly(rq)`. The argument to these functions have the same requirements as the corresponding arguments to `redcapConnection`.

Tokens are specific to a project, and a token must be created for each project for which the user wishes to use the API.

Additional Curl option can be set in the `config` argument. See the documentation for [httr::config\(\)](#) and [httr:httr_options\(\)](#) for more Curl options.

Examples

```
## Not run:
rcon <- redcapConnection(url=[YOUR_REDCAP_URL], token=[API_TOKEN])

options(redcap_api_url=[YOUR_REDCAP_URL])
```

```
rcon <- redcapConnection(token=[API_TOKEN])  
exportRecords(rcon)  
  
# Get the complete metadata for the project  
rcon$metadata()  
  
# Get the fieldnames for a project  
rcon$fieldnames()  
  
# remove a cached value for fieldnames  
rcon$flush_fieldnames()  
rcon$has_fieldnames()  
  
## End(Not run)
```

redcapDataStructures *REDCap Data Structures*

Description

Utilities for recognizing and validating data structures for use with the REDCap API

Usage

```
validateRedcapData(data, redcap_data)
```

```
REDCAP_SYSTEM_FIELDS
```

```
REDCAP_METADATA_FIELDTYPE
```

```
REDCAP_METADATA_VALIDATION_TYPE
```

```
REDCAP_REPEAT_INSTRUMENT_STRUCTURE
```

Arguments

`data` `data.frame` User provided data to be compared against the established REDCap data structure.

`redcap_data` `data.frame` A data set from the redcapAPI package to use a reference for comparing to expected data structure.

Format

An object of class `character` of length 4.

An object of class `character` of length 11.

An object of class `character` of length 23.

An object of class `data.frame` with 0 rows and 3 columns.

`redcapError`*Handle Errors from the REDCap API*

Description

Determine the proper way to handle errors returned from the API. Not all errors should be fatal. See Details for more

Usage

```
redcapError(x, error_handling)
```

Arguments

`x` Object returned by `httr::POST()`.

`error_handling` character(1). One of `c("error", "null")`. An option for how to handle errors returned by the API. see `redcapError()`.

Details

Maintaining consistent functionality for all types of REDCap projects requires that errors be handled delicately. It is not always desirable for an error from the API to terminate the program. One example of such a case is when a user executes the `exportEvents` function for a classic project; doing so returns an error from the API that events cannot be exported for classic projects. In REDCap versions earlier than 6.5.0, there is no way to determine if a project is classic or longitudinal without attempting to export the events.

For this reason, it is often preferable to have these kinds of errors return `NULL` so that the program does not crash if it does not need to (one such instance where it does not need to crash is when `exportEvents` is called within `exportRecords`; the `events` argument is irrelevant to a classic project and the error can safely be ignored.

The other common type of error that does not need to be fatal is when a `redcapAPI` method is sent to a REDCap instance that does not support the method. For example, the `exportVersion` method is not supported in REDCap instances earlier than 6.0.0. In these cases, we may prefer not to cast a hard error.

These two types of errors may be handled in one of two ways. When the error handler is set to `"null"`, a `NULL` is returned. When the error handler is set to `"error"`, the error is returned. The option is set globally using `options(redcap_error_handler = "null")` and is set to `"null"` by default.

redcapFactorFlip *Convert REDCap factors between labeled and coded*

Description

Factors exported from REDCap can be toggled between the coded and labeled values with the use of the attributes assigned to the factors during export.

Usage

```
redcapFactorFlip(v)
```

Arguments

v A factor exported from REDCap. The REDCap type may be radio, dropdown, check, yesno, etc.

Details

Each factor type variable in REDCap is given the attributes `redcapLabels` and `redcapLevels`. With these attached to the vector, switching between the coded and labeled values can be done with ease. This may be helpful when the coded value has importance, such as 0/1 for death, or if a yes is worth six points (instead of one).

repeatingInstrumentMethods
Export or Import Repeating Instrument and Events Settings

Description

These methods enable the user to export the existing repeating instrument and event settings, or import new settings to the project.

Usage

```
exportRepeatingInstrumentsEvents(rcon, ...)

importRepeatingInstrumentsEvents(rcon, data, ...)

## S3 method for class 'redcapApiConnection'
exportRepeatingInstrumentsEvents(
  rcon,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
```

```

    api_param = list()
  )

## S3 method for class 'redcapApiConnection'
importRepeatingInstrumentsEvents(
  rcon,
  data,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
data	data.frame. For classical projects, it must have the columns form_name and custom_form_label. Longitudinal projects also require a column for event_name.
refresh	logical(1). When TRUE, the cached value of repeating instruments and events on rcon will be refreshed.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

Repeating events (as opposed to repeating instruments) are provided as a row of data where the form_name column is NA.

It is not possible to update the has_repeating_instruments_or_events property of the project through importProjectInformation. Enabling of repeating instruments and events must be done through the GUI.

Although the API does not provide a delete method, it is possible to remove settings by doing an import that excludes the settings that are to be deleted. All settings can be cleared by executing importRepeatingInstrumentsEvents(rcon, REDCAP_REPEAT_INSTRUMENT_STRUCTURE).

Value

exportRepeatingInstrumentsEvents returns a data frame with the columns:

event_name	The unique event name.
------------	------------------------

form_name	The form name, as given in the second column of the Meta Data
custom_form_label	A custom display string for the repeating instrument/event

importRepeatingInstrumentsEvents has no return and displays a message describing the number of rows imported.

Functions

- exportRepeatingInstrumentsEvents(): Export repeating instruments and events.
- importRepeatingInstrumentsEvents(): Import repeating instruments and events.

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export repeating instruments and events
exportRepeatingInstrumentsEvents(rcon)

# Import repeating instruments and events
NewData <- data.frame(event_name = c("event_1_arm_1",
                                   "event_2_arm_1"),
                     form_name = c("field_observation",
                                   "self_assessment"),
                     custom_form_label = c("Instructor led field observation",
                                           "Trainee self assessment"))

importRepeatingInstrumentsEvents(rcon,
                                data = NewData)

## End(Not run)
```

reviewInvalidRecords *Review Invalid Records Following Field Validation*

Description

This function retrieves a summary of data elements that failed validation during field validation and casting.

Usage

```
reviewInvalidRecords(data, quiet = TRUE)
```

Arguments

data	data.frame. The result of a function that performed field validation.
quiet	logical(1). When TRUE, a message will be printed if the <code>invalid</code> attribute is not found on data. Otherwise, the message is suppressed.

Details

When discussing field validation and invalid data, it is helpful to establish the following terminology:

A *Records data frame* is a data frame returned by a function where the fields (columns) in the data frame have been cast for subsequent analysis.

Some casting function also perform field validation and return an *Invalid data frame*, which is a listing of data elements that have failed validation. The Invalid data frame is attached as an attribute to the Records data frame. If no data elements fail the validation, the Invalid data frame will have zero rows. If at least one data element fails validation, a warning is printed to notify the user so that the user may review the Invalid data frame and mitigate the failed validations.

The Invalid data frame has an additional class (`c("invalid", "data.frame")`) and comes with a print method. The `print.invalid` method displays the content of the Invalid data frame neatly in both the console and within reports utilizing markdown.

Value

If data has the "invalid" attribute, an object with class `c("invalid", "data.frame")` is returned. (NULL will be returned if data does not have the attribute).

The columns in the Invalid data frame are

row	The row number from the Records data frame for which validation failed.
record_id	The record ID for the failed validation.
field_name	The field name (column) of the failed validation.
field_type	The field type of the failed validation.
value	The original value that failed validation. It will be replaced with NA in the Records data.

The Invalid data frame has additional attributes

- `time` - The date/time at which the validation was performed.
- `version` - The REDCap version number (as retrieved by `exportVersion`).
- `project` - The title of the REDCap project (as retrieved by `exportProjectInformation`).

See Also

[exportRecordsTyped\(\)](#),
[exportReportsTyped\(\)](#),
[castForImport\(\)](#),
[guessCast\(\)](#)

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Review the Invalid data frame after export
Records <- exportRecordsTyped(rcon)
reviewInvalidRecords(Records)

# Review Invalid data frame before import
RecordsForIMport <- castForImport(rcon)
reviewInvalidRecords(Records)

# Access the Invalid data frame the attributes
Records <- exportRecordsTyped(rcon)
attr(Records, "invalid")
attributes(Records)$invalid

## End(Not run)
```

splitForms

Split a Data Frame into its Forms

Description

Separates a data frame from REDCap into a list of data frames where each form constitutes an element in the list.

Usage

```
splitForms(Records, rcon, envir = NULL, base = NULL, post = NULL)
```

Arguments

Records	data.frame such as one generated by exportRecords or exportRecordsTyped
rcon	A redcapConnection object.
envir	environment. The target environment for the resulting list of data.frames. Defaults to NULL which returns the a list. Use globalenv to assign the global environment. Will accept a number of the environment.

base	character(1) giving the start of the naming scheme for the elements of the list. By default, the names of the list will be the form names. If this value is provided, it will follow the format <code>base.form_name</code> .
post	function to apply to each element of form data after separating them, must be of signature <code>function(data, rcon)</code> .

See Also

Other post-processing functions:

[recastRecords\(\)](#),
[guessCast\(\)](#),
[guessDate\(\)](#),
[castForImport\(\)](#),
[mChoiceCast\(\)](#),
[widerRepeated\(\)](#)

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

Records <- exportRecordsTyped(rcon)

splitForms(Records, rcon)

## End(Not run)
```

stringCleanup

Remove Undesired Characters From Strings

Description

These functions are utilities to clear undesired characters from REDCap output.

Usage

```
stripHTMLTags(
  x,
  tags = c("p", "br", "div", "span", "b", "font", "sup", "sub"),
  ignore.case = TRUE
)

stripUnicode(x)
```

Arguments

x	character, vector of content to be cleaned.
tags	character, vector of HTML tags to remove from x
ignore.case	logical(1), should cases be ignored when matching patterns? Defaults to TRUE.

Value

stripHTMLTags returns a character vector.

stripUnicode returns a character vector.

Examples

```
stripHTMLTags("<p>Text in a paragraph <b>tag</b> with bold formatting </p>")
```

```
stripUnicode("\U00B5 = 0")
```

stripHTMLandUnicode *Helper Functions for exportRecordsType Attributes*

Description

These functions assist in setting attributes for columns of the resulting type cast data.frame.

Usage

```
stripHTMLandUnicode(field_name, field_label, field_annotation)
```

```
unitsFieldAnnotation(field_name, field_label, field_annotation)
```

Arguments

field_name	character. Name of the fields.
field_label	character. Labels from meta data.
field_annotation	character. Annotations from meta_data.

Details

Functions passed into the assignment argument list of `exportRecordsTyped()` construct attributes on a column. They are expected to have a signature of `function(field_name, field_label, field_annotation)` and return the attribute to assign or NA. They must be vectorized.

Useful utilities are provided in `stringCleanup()`

`stripHTMLandUnicode` strips both HTML and UNICODE from the `field_label`.

`unitsFieldAnnotation` pulls a units string from the `field_annotation`. An example of the form searched for is `units=\{"meters"\}`

Value

stripHTMLandUnicode returns a character vector.

unitsFieldAnnotation returns a character vector.

See Also

[exportRecordsTyped\(\)](#),
[exportReportsTyped\(\)](#),
[stripHTMLTags\(\)](#),
[stripUnicode\(\)](#)

Examples

```
## Not run:
stripHTMLandUnicode("field_name", "<b>Field label</b>", "field annotation")

unitsFieldAnnotation("field", "label", "units={\"meters\"}")

## End(Not run)
```

surveyMethods

Export Survey Participant Information

Description

These methods enable the user to export information relating to survey participants.

Usage

```
exportSurveyParticipants(rcon, instrument, event, ...)

exportSurveyLink(rcon, record, instrument, event, repeat_instance = 1, ...)

exportSurveyQueueLink(rcon, record, ...)

exportSurveyReturnCode(
  rcon,
  record,
  instrument,
  event,
  repeat_instance = 1,
  ...
)

## S3 method for class 'redcapApiConnection'
exportSurveyParticipants(
```



```
    rcon,
    instrument = NULL,
    event = NULL,
    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list(),
    api_param = list()
)

## S3 method for class 'redcapApiConnection'
exportSurveyLink(
  rcon,
  record,
  instrument,
  event = NULL,
  repeat_instance = 1,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
exportSurveyQueueLink(
  rcon,
  record,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
exportSurveyReturnCode(
  rcon,
  record,
  instrument,
  event = NULL,
  repeat_instance = 1,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)
```

Arguments

rcon A redcapConnection object.

record	character(1) or integerish(1). The record ID of a survey participant.
instrument	character(1). The name of a survey instrument.
event	character(1) The event name of the event for which participant information should be exported.
repeat_instance	integerish(1). The repeat instance if the instrument is designated as a repeating instrument. Default value is 1.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in <code>rcon\$config</code> .
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by <code>redcapAPI</code> .

Value

`exportSurveyParticipants` returns a data frame with the columns:

email	The e-mail address of the participant.
email_occurrence	The number of times the invitation has been sent (after the next invite).
identifier	Participant identifier (if it exists) to match the survey response to a participant.
record	Record ID of the participant.
invitation_sent_status	Boolean value indicating if a survey invitation has been sent.
invitation_send_time	Date/time the survey invitation was sent.
response_status	Boolean value indicating if the participant has responded.
survey_access_code	The participant's survey access code.
survey_link	The participant's survey link.
survey_queue_link	The participants' survey queue link.

`exportSurveyLink` returns a character(1) giving the link for the user to access the survey form.

`exportSurveyQueueLink` returns a character(1) giving the survey queue link for the user.

`exportSurveyReturnCode` returns a character(1) giving the survey return code for the user.

Functions

- `exportSurveyParticipants()`: Export survey participants for a survey instrument.
- `exportSurveyLink()`: Export a survey participant's survey instrument link.
- `exportSurveyQueueLink()`: Export a survey participant's survey queue link.
- `exportSurveyReturnCode()`: Export a survey participant's instrument return code.

Examples

```

## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export survey participants
exportSurveyParticipants(rcon,
                       instrument = "survey_form")

# Export survey participants for an event
exportSurveyParticipants(rcon,
                       instrument = "survey_form",
                       event = "event_1_arm_1")

# Export survey link
exportSurveyLink(rcon,
                record = 1,
                instrument = "survey_form")

# Export survey queue link
exportSurveyQueueLink(rcon,
                    record = 1)

# Export survey return code
exportSurveyReturnCode(rcon,
                     user = 1,
                     instrument = "survey_form")

## End(Not run)

```

switchDag

Switch Data Access Group Assignment for the Current User

Description

This method enables the current API user to switch (assign/reassign/unassign) their current Data Access Group assignment if they have been assigned to multiple DAGs via the DAG Switcher page in the project.

Usage

```

switchDag(rcon, dag, ...)

## S3 method for class 'redcapApiConnection'
switchDag(
  rcon,

```

```

    dag,
    refresh = TRUE,
    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list(),
    api_param = list()
  )

```

Arguments

rcon	A redcapConnection object.
dag	character(1) A unique data access group to which to assign the current user. Use NA to leave the user unassigned.
refresh	logical(1) If TRUE, the cached data access group assignments will be refreshed.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to http::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Value

Returns TRUE when the call is completed successfully.

See Also

```

exportDags(),
importDags(),
deleteDags(),
exportUserDagAssignments(),
importUserDagAssignments()

```

Examples

```

## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Switch the current user to the DAG "Facility Two"
switchDag(rcon,
          dag = "facility_two")

## End(Not run)

```

syncUnderscoreCodings *Synchronize coding of checkbox variables between meta data and records field names.*

Description

Due to a bug in the REDCap export module, underscores in checkbox codings are not retained in the suffixes of the field names in the exported records. For example, if variable `chk` is a checkbox with a coding 'a_b, A and B', the field name in the data export becomes `chk___ab`. The loss of the underscore causes `fieldToVar` to fail as it cannot match variable names to the meta data. `syncUnderscoreCodings` rectifies this problem by searching the suffixes and meta data for underscores. If a discrepancy is found, the underscores are removed from the metadata codings, restoring harmony to the universe. This bug was fixed in REDCap version 5.5.21 and this function does not apply to that and later versions.

Usage

```
syncUnderscoreCodings(records, meta_data, export = TRUE)
```

Arguments

<code>records</code>	The data frame object returned from the API export prior to applying factors, labels, and dates via the <code>fieldToVar</code> function.
<code>meta_data</code>	Metadata export from <code>exportMetaData</code>
<code>export</code>	Logical. Specifies if data are being synchronized for import or export

Details

`syncUnderscoreCodings` performs a series of evaluations. First, it determines if any underscores are found in the checkbox codings. If none are found, the function terminates without changing anything.

If the checkbox codings have underscores, the next evaluation is to determine if the variable names suffixes have matching underscores. If they do, then the function terminates with no changes to the meta data.

For data exports, if the prior two checks find underscores in the meta data and no underscores in the suffixes, the underscores are removed from the meta data and the new meta data returned.

For data imports, the meta data are not altered and the `checkbox_field_name_map` attribute is used to synchronize field names to the meta data and the expectations of REDCap (for import, REDCap expects the underscore codings to be used).

Backward Compatibility

In retrospect, we realize that the way `syncUnderscoreCodings` is written is backward. We should have altered the field names in the records data frame. Any scripts that make use of `syncUnderscoreCodings` and were written prior to version 5.5.21 will fail because the underscores in the codings will now be present where they were not before.

For backward compatibility of redcapAPI, we continue to alter the codings in the meta data. We do not anticipate many problems, as most people do not use underscores in the checkbox codings

If your scripts were written under REDCap 5.5.21 or higher, there will be no backward compatibility problems related to this issue.

unlockREDCap	<i>Open REDCap connections using cryptolocker for storage of API_KEYS.</i>
--------------	--

Description

Opens a set of connections to REDcap from API_KEYs stored in an encrypted keyring. If the keyring does not exist, it will ask for password to this keyring to use on later requests. Next it will ask for the API_KEYs specified in connections. If an API_KEY does not work, it will request again. On later executions it will use an open keyring to retrieve all API_KEYs or for a password if the keyring is currently locked.

Usage

```
unlockREDCap(
  connections,
  url,
  keyring,
  envir = NULL,
  passwordFUN = .default_pass(),
  ...
)
```

Arguments

connections	character vector. A list of strings that define the connections with associated API_KEYs to load into environment. Each name should correspond to a REDCap project for traceability, but it can be named anything one desires. The name in the returned list is this name.
url	character. The url of one's institutional REDCap server api.
keyring	character. Potential keyring, not used by default.
envir	environment. The target environment for the connections. Defaults to NULL which returns the keys as a list. Use <code>globalenv()</code> to assign in the global environment. Will accept a number such a '1' for global as well.
passwordFUN	function. Function to get the password for the keyring. Usually defaults <code>getPass::getPass</code> . On MacOS it will use <code>rstudioapi::askForPassword</code> if available.
...	Additional arguments passed to <code>redcapConnection()</code> .

Details

If one forgets the password to this keyring, or wishes to start over: `keyring::keyring_delete("<NAME_OF_KEY_RING_HERE")`

Consistent behavior requires `options(keyring_backend=keyring::backend_file)` to be set. It is recommended to place this in `~/.Rprofile`.

For production servers where the password must be stored in a readable plain text file, it will search for `./<basename>.yaml`. DO NOT USE this unless one is a sysadmin, as this defeats the security and purpose of a local encrypted file. The expected structure of this yaml file is as follows:

```
other-config-stuff1: blah blah
redcapAPI:
  keys:
    intake: THIS_IS_THE_INTAKE_DATABASE_APIKEY
    details: THIS_IS_THE_DETAILS_DATABASE_APIKEY
other-config-stuff2: blah blah
other-config-stuff3: blah blah
```

IMPORTANT: Make sure that R is set to NEVER save workspace to .RData as this *is* writing the API_KEY to a local file in clear text because connection objects contain the unlocked key in memory. Tips are provided in vignette("redcapAPI-best-practices").

Value

If `envir` is NULL returns a list of opened connections. Otherwise connections are assigned into the specified `envir`.

Examples

```
## Not run:
options(keyring_backend=keyring::backend_file) # Put in .Rprofile

unlockREDCap(c(test_conn = 'TestRedcapAPI',
               sandbox_conn = 'SandboxAPI'),
             keyring = '<NAME_OF_KEY_RING_HERE>',
             envir = globalenv(),
             url = 'https://<INSTITUTIONS_REDCAP_DOMAIN>/api/')

## End(Not run)
```

Description

These methods enable the user to add and remove users from a project. They also enable the user to modify the permissions granted to each user within the project.

Usage

```

exportUsers(rcon, ...)

importUsers(rcon, data, ...)

deleteUsers(rcon, users, ...)

## S3 method for class 'redcapApiConnection'
exportUsers(
  rcon,
  dates = TRUE,
  labels = TRUE,
  form_rights = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
importUsers(
  rcon,
  data,
  consolidate = TRUE,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
deleteUsers(
  rcon,
  users,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
dates	logical(1). When TRUE, expiration dates are converted to a POSIXct object.
labels	logical(1). When TRUE the data export and form access rights are converted to factor objects.

form_rights	logical(1). When TRUE, the form rights will be transformed to one column per form. The API-provided character string is always returned with the format [form_name]:[access_code] and a comma separating each form.
users	character. Vector of unique user names to be deleted.
data	data.frame. Provides the user data for import. It must have a column titled username. All other columns are optional.
consolidate	logical(1). When TRUE, the form and data export access values will be read from the expanded columns. Otherwise, the consolidated values (as provided by the API export) are utilized.
refresh	logical(1). When TRUE, the cached data will be refreshed after the API action is complete.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httr::POST() . These are appended to any parameters in <code>rcon\$config</code> .
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

User project access fields (those not related to forms or exports) are mapped between coded and labeled values as:

Code	Label
0	No Access
1	Access

Form access fields are mapped as:

Code	Label
0	No Access
1	View records/responses and edit records (survey responses are read-only)
2	Read Only
3	Edit survey responses

Form export permission fields are mapped as:

Code	Label
0	No Access
1	Full Data Set
2	De-Identified
3	Remove Identifier Fields

Importing Users/User Roles:

It is not required that the user provide a data frame with all of the fields available for modification. Only fields that are provided will be modified. The only required field for imports is the username field.

When setting permissions for a user project access fields, form access, and form export permissions, the user may provided any of the coded or labeled values above. The user data is passed through `prepUserImportData()` before sending it to the API; text values will be converted to the numeric value.

It is also permissible to use a column for each form individually, as can be exported via `exportUsers()`. With `consolidate = TRUE`, these settings will be consolidated into the text string expected by the API.

The REDCap API does not natively allow for modifying the rights of a user that is part of a User Role. When an attempt to modify the rights of a user in a User Role is made with this package, the user will be removed from the User Role, the rights modified, and then the User Role restored. This is done silently: be aware that modifications to a user's rights may not have an impact while the User Role is assigned.

Limitations:

When importing via CSV, (as `redcapAPI` does by default) it appears that the form access rights are imported but may not always be reflected in the exported values. The form export rights do not appear to be imported when using the CSV format. We may be able to resolve this in the future using a JSON format.

Value

`exportUsers` returns a data frame with the columns:

<code>username</code>	The unique username for a user that can access the project.
<code>email</code>	The e-mail address associated with the user in the REDCap system.
<code>firstname</code>	The user's first name.
<code>lastname</code>	The user's last name.
<code>expiration</code>	The date at which the user's access to the project will expire.
<code>data_access_group</code>	The text name of the Data Access Group to which the user is assigned.
<code>data_access_group_id</code>	The REDCap assigned unique identifier of the Data Access Group.
<code>design</code>	Boolean flag indicating if the user has permissions to utilize the project design modules.
<code>alerts</code>	Boolean flag indicating if the user has permissions to utilize the alerts tools.
<code>user_right</code>	Boolean flag indicating if the user has permissions to modify user rights.
<code>data_access_groups</code>	Boolean flag indicating if the user has user has permission to assign user to Data Access G
<code>reports</code>	Boolean flag indicating if the user has permissions to design reports.
<code>stats_and_charts</code>	Boolean flag indicating if the user has permissions to view the Statistics and Charts module
<code>manage_survey_participants</code>	Boolean flag indicating if the user has permissions to manage survey participants.
<code>calendar</code>	Boolean flag indicating if the user has permissions to utilize the project calendar module.
<code>data_import_tool</code>	Boolean flag indicating if the user has permissions to use the data import tool.
<code>data_comparison_tool</code>	Boolean flag indicating if the user has permissions to use the data comparison tool.
<code>logging</code>	Boolean flag indicating if the user has permissions to view the project logs (audit trail).
<code>file_repository</code>	Boolean flag indicating if the user has permissions to access the project file repository.

data_quality_create	Boolean flag indicating if the user has permission create new data quality rules.
data_quality_execute	Boolean flag indicating if the user has permission to execute data quality rules.
api_export	Boolean flag indicating if the user has API export privileges.
api_import	Boolean flag indicating if the user has API import privileges.
mobile_app	Boolean flag indicating if the user has permissions to use the mobile app.
mobile_app_download_data	Boolean flag indicating if the user has permissions to download data on the mobile app.
record_create	Boolean flag indicating if the user has permission to create new records.
record_rename	Boolean flag indicating if the user has permission to rename existing records.
record_delete	Boolean flag indicating if the user has permission to delete records.
lock_records_all_forms	Boolean flag indicating if the user has permission to lock records across all forms.
lock_records	Boolean flag indicating if the user has permission to lock a records on individual forms.
lock_records_customization	Boolean flag indicating if the user has permission to customize record locking.
random_setup	Boolean flag indicating if the user has permission to set up randomization rules.
random_dashboard	Boolean flag indicating if the user has permission to view the randomization dashboard.
random_perform	Boolean flag indicating if the user has permission to perform record randomization.
forms	Character string listing form access rights for each form.
forms_export	Character string listing the form export rights for each form.

When `form_rights = TRUE`, additional columns are created that give the form access and form export rights in an individual column for each form. Form access rights columns have the naming pattern `[form_name]_access` and the form export rights columns have the naming pattern `[form_name]_export_access`.

`importUsers` has no return value and displays a message indicating how many users were added or modified.

`deleteUsers` has no return value and displays a message indicating how many users were deleted.

Functions

- `exportUsers()`: Export users affiliated with a project.
- `importUsers()`: Add users or modify user permissions in a project.
- `deleteUsers()`: Remove users from a project.

See Also

```
exportUserRoles(),
importUserRoles(),
deleteUserRoles(),
exportUserRoleAssignments(),
importUserRoleAssignments()
```

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())
```

```

# Export users
exportUsers(rcon)

# Export users without additional form access variables
exportUsers(rcon,
             form_rights = FALSE)

# Export users as raw data
exportUsers(rcon,
             labels = FALSE)

# Import new permissions
NewData <- data.frame(username = "target_user",
                      design = 0,
                      api_export = 1,
                      api_import = "No Access")

importUsers(rcon,
            data = NewData)

# Remove a user from a project
deleteUsers(rcon,
            users = "target_user")

## End(Not run)

```

userRoleAssignmentMethods

Export or Import User-Role Assignments

Description

These methods enable the user to export the user-role assignments, add assignments, or modify existing assignments.

Usage

```

exportUserRoleAssignments(rcon, ...)

importUserRoleAssignments(rcon, data, ...)

## S3 method for class 'redcapApiConnection'
exportUserRoleAssignments(
  rcon,
  ...,
  error_handling = getOption("redcap_error_handling"),

```

```

    config = list(),
    api_param = list()
  )

## S3 method for class 'redcapApiConnection'
importUserRoleAssignments(
  rcon,
  data,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
data	data.frame with columns username and unique_role_name. Each username must be unique. Users without a unique_role_name will not be assigned to a user role.
refresh	logical(1). When TRUE, the cached value in rcon will be refreshed after the import.
...	Arguments to pass to other methods
error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in rcon\$config.
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Value

exportUserRoleAssignments returns a data frame with the columns:

username	Username of a user in the project.
unique_role_name	The unique role name to which the user is assigned.
data_access_group	The Data Access Group to which the user is assigned.

Functions

- `exportUserRoleAssignments()`: Export user-role assignments from a project.
- `importUserRoleAssignments()`: Import user-role assignments to a project.

See Also

```
exportUsers(),  
importUsers(),  
deleteUsers(),  
exportUserRoles(),  
importUserRoles(),  
deleteUserRoles()
```

Examples

```
## Not run:  
unlockREDCap(connections = c(rcon = "project_alias"),  
              url = "your_redcap_url",  
              keyring = "API_KEYS",  
              envir = globalenv())  
  
# Export user-role assignments  
exportUserRoleAssignments(rcon)  
  
# Import/modify a user-role assignment  
NewData <- data.frame(username = "desired_user_name",  
                      unique_role_name = "KN3430U")  
importUserRolesAssignments(rcon,  
                           data = NewData)  
  
## End(Not run)
```

userRoleMethods

Export, Import, or Delete User Roles in a Project

Description

These methods enable the user to export user roles, add user roles, or remove user roles from a project. They also enable the user to modify the permissions granted to a user.

Usage

```
exportUserRoles(rcon, ...)  
  
importUserRoles(rcon, data, ...)  
  
deleteUserRoles(rcon, user_roles, ...)  
  
## S3 method for class 'redcapApiConnection'  
exportUserRoles(  
  rcon,  
  labels = TRUE,
```

```

    form_rights = TRUE,
    ...,
    error_handling = getOption("redcap_error_handling"),
    config = list(),
    api_param = list()
)

## S3 method for class 'redcapApiConnection'
importUserRoles(
  rcon,
  data,
  consolidate = TRUE,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

## S3 method for class 'redcapApiConnection'
deleteUserRoles(
  rcon,
  user_roles,
  refresh = TRUE,
  ...,
  error_handling = getOption("redcap_error_handling"),
  config = list(),
  api_param = list()
)

```

Arguments

rcon	A redcapConnection object.
labels	logical(1). When TRUE the data export and form access rights are converted to factor objects.
form_rights	logical(1). When TRUE, the form rights will be transformed to one column per form. The API-provided character string is always returned with the format [form_name]:[access_code] and a comma separating each form.
user_roles	character. Unique role names to be deleted from the project.
data	data.frame. Provides the user data for import. It must have a column titled unique_role_name. All other columns are optional.
consolidate	logical(1). When TRUE, the form and data export access values will be read from the expanded columns. Otherwise, the consolidated values (as provided by the API export) are utilized.
refresh	logical(1). When TRUE, the cached data will be refreshed after the API action is complete.
...	Arguments to pass to other methods

error_handling	character(1). One of c("error", "null"). An option for how to handle errors returned by the API. see redcapError() .
config	A named list. Additional configuration parameters to pass to httpr::POST() . These are appended to any parameters in <code>rcon\$config</code> .
api_param	A named list. Additional API parameters to pass into the body of the API call. This provides users to execute calls with options that may not otherwise be supported by redcapAPI.

Details

User project access fields (those not related to forms or exports) are mapped between coded and labeled values as:

Code	Label
0	No Access
1	Access

Form access fields are mapped as:

Code	Label
0	No Access
1	View records/responses and edit records (survey responses are read-only)
2	Read Only
3	Edit survey responses

Form export permission fields are mapped as:

Code	Label
0	No Access
1	Full Data Set
2	De-Identified
3	Remove Identifier Fields

Importing Users/User Roles:

It is not required that the user provide a data frame with all of the fields available for modification. Only fields that are provided will be modified. The only required field for imports is the username field.

When setting permissions for a user project access fields, form access, and form export permissions, the user may provided any of the coded or labeled values above. The user data is passed through [prepUserImportData\(\)](#) before sending it to the API; text values will be converted to the numeric value.

It is also permissible to use a column for each form individually, as can be exported via [exportUsers\(\)](#). With `consolidate = TRUE`, these settings will be consolidated into the text string expected by the API.

The REDCap API does not natively allow for modifying the rights of a user that is part of a User Role. When an attempt to modify the rights of a user in a User Role is made with this package, the user will be removed from the User Role, the rights modified, and then the User Role restored. This is done silently: be aware that modifications to a user's rights may not have an impact while the User Role is assigned.

Limitations:

When importing via CSV, (as redcapAPI does by default) it appears that the form access rights are imported but may not always be reflected in the exported values. The form export rights do not appear to be imported when using the CSV format. We may be able to resolve this in the future using a JSON format.

Value

exportUserRoles returns a data frame with the columns:

unique_role_name	The REDCap assigned unique role name.
role_label	The user provided label describing the role.
design	Boolean flag indicating if the user has permissions to utilize the project design modules.
alerts	Boolean flag indicating if the user has permissions to utilize the alerts tools.
user_right	Boolean flag indicating if the user has permissions to modify user rights.
data_access_groups	Boolean flag indicating if the user has user has permission to assign user to Data Access G
reports	Boolean flag indicating if the user has permissions to design reports.
stats_and_charts	Boolean flag indicating if the user has permissions to view the Statistics and Charts module
manage_survey_participants	Boolean flag indicating if the user has permissions to manage survey participants.
calendar	Boolean flag indicating if the user has permissions to utilize the project calendar module.
data_import_tool	Boolean flag indicating if the user has permissions to use the data import tool.
data_comparison_tool	Boolean flag indicating if the user has permissions to use the data comparison tool.
logging	Boolean flag indicating if the user has permissions to view the project logs (audit trail).
file_repository	Boolean flag indicating if the user has permissions to access the project file repository.
data_quality_create	Boolean flag indicating if the user has permission create new data quality rules.
data_quality_execute	Boolean flag indicating if the user has permission to execute data quality rules.
api_export	Boolean flag indicating if the user has API export privileges.
api_import	Boolean flag indicating if the user has API import privileges.
mobile_app	Boolean flag indicating if the user has permissions to use the mobile app.
mobile_app_download_data	Boolean flag indicating if the user has permissions to download data on the mobile app.
record_create	Boolean flag indicating if the user has permission to create new records.
record_rename	Boolean flag indicating if the user has permission to rename existing records.
record_delete	Boolean flag indicating if the user has permission to delete records.
lock_records_all_forms	Boolean flag indicating if the user has permission to lock records across all forms.
lock_records	Boolean flag indicating if the user has permission to lock a records on individual forms.
lock_records_customization	Boolean flag indicating if the user has permission to customize record locking.
random_setup	Boolean flag indicating if the user has permission to set up randomization rules.
random_dashboard	Boolean flag indicating if the user has permission to view the randomization dashboard.
random_perform	Boolean flag indicating if the user has permission to perform record randomization.
forms	Character string listing form access rights for each form.
forms_export	Character string listing the form export rights for each form.

When `form_rights = TRUE`, additional columns are created that give the form access and form export rights in an individual column for each form. Form access rights columns have the naming pattern `[form_name]_access` and the form export rights columns have the naming pattern `[form_name]_export_access`.

`importUserRoles` has no return value and displays a message indicating how many users were added or modified.

`deleteUserRoles` has no return value and displays a message indicating how many users were deleted.

Functions

- `exportUserRoles()`: Export user roles from a project.
- `importUserRoles()`: Import user roles to a project.
- `deleteUserRoles()`: Delete user roles from a project.

See Also

[exportUsers\(\)](#),
[importUsers\(\)](#),
[deleteUsers\(\)](#),
[exportUserRoleAssignments\(\)](#),
[importUserRoleAssignments\(\)](#)

Examples

```
## Not run:
unlockREDCap(connections = c(rcon = "project_alias"),
              url = "your_redcap_url",
              keyring = "API_KEYS",
              envir = globalenv())

# Export users-roles
exportUserRoles(rcon)

# Export user-roles without additional form access variables
exportUsersRoles(rcon,
                 form_rights = FALSE)

# Export users as raw data
exportUserRoles(rcon,
                 labels = FALSE)

# Import new permissions
NewData <- data.frame(unique_role_name = "KN439U",
                     design = 0,
                     api_export = 1,
                     api_import = "No Access")
importUserRoles(rcon,
                data = NewData)
```

```
# Remove a user from a project
deleteUserRoles(rcon,
                user_roles = "KN439U")

## End(Not run)
```

validateImport *Validate Data Frames for Import*

Description

Validates the variables in a data frame prior to attempting an import to REDCap

Usage

```
validateImport(data, meta_data, logfile = "")
```

Arguments

data	data.frame being prepared for import to REDCap.
meta_data	REDCap database meta data.
logfile	A character string giving the filepath to which the results of the validation are printed. If "", the results are printed in the console.

Details

validateImport is called internally by importRecords and is not available to the user.

Each variable is validated by matching the type of variable with the type listed in the REDCap database.

Although the log messages will indicate a preference for dates to be in mm/dd/yyyy format, the function will accept mm/dd/yy, yyyy-mm-dd, yyyy/mm/dd, and yyyymmdd formats as well. When possible, pass dates as Date objects or POSIXct objects to avoid confusion. Dates are also compared to minimum and maximum values listed in the data dictionary. Records where a date is found out of range are allowed to import and a message is printed in the log.

For continuous/numeric variables, the values are checked against the minimum and maximum allowed in the data dictionary. Records where a value is found out of range are allowed to import and a message is printed in the log.

ZIP codes are tested to see if they fit either the five digit or five digit + four format. When these conditions are not met, the data point is deleted and a message printed in the log.

YesNo fields permit any of the values 'yes', 'no', '0', '1' to be imported to REDCap with 0=No, and 1=Yes. The values are converted to lower case for validation, so any combination of lower and upper case values will pass (ie, the data frame is not case-sensitive).

TrueFalse fields will accept 'TRUE', 'FALSE', 0, 1, and logical values and are also not case-sensitive.

Radio and dropdown fields may have either the coding in the data dictionary or the labels in the data dictionary. The validation will use the meta data to convert any matching values to the appropriate coding before importing to REDCap. Values that cannot be reconciled are deleted with a message printed in the log. These variables are not case-sensitive.

Checkbox fields require a value of "Checked", "Unchecked", "0", or "1". These are currently case-sensitive. Values that do not match these are deleted with a warning printed in the log.

Phone numbers are required to be ten digit numbers. The phone number is broken into three parts: 1) a three digit area code, 2) a three digit exchange code, and 3) a four digit station code. The exchange code must start with a number from 2-9, followed by 0-8, and then any third digit. The exchange code starts with a number from 2-9, followed by any two digits. The station code is four digits with no restrictions.

E-mail addresses are considered valid when they have three parts. The first part comes before the @ symbol, and may be number of characters from a-z, A-Z, a period, underscore, percent, plus, or minus. The second part comes after the @, but before the period, and may consist of any number of letters, numbers, periods, or dashes. Finally, the string ends with a period then anywhere from two to six letters.

vectorToApiBodyList *Convert R Vector To List for the API Call Body*

Description

Converts an R vector to a list that will be suitable for makeApiCall.

Usage

```
vectorToApiBodyList(vector, parameter_name)
```

Arguments

vector An atomic vector.
parameter_name character(1). The REDCap API parameter name.

Examples

```
## Not run:
vectorToApiBodyList(1:3, "records")

## End(Not run)
```

widerRepeated	<i>Transform Data Into Wide Format</i>
---------------	--

Description

Converts a dataframe into wide format given a single REDCap form. This function assumes that the `Records` argument is the result of `exportRecordsTyped`, and that all empty values have been previously dropped. This will only widen data frames that have a unique identification variable (e.g. `'record_id'`), `"redcap_event_name"` and `"redcap_repeat_instrument"` in the fields. Otherwise, the data passed in will be returned unchanged.

Usage

```
widerRepeated(Records, rcon)
```

Arguments

<code>Records</code>	data.frame containing the records from <code>exportRecordsTyped()</code>
<code>rcon</code>	A <code>redcapConnection</code> object.

See Also

Other post-processing functions:

```
recastRecords(),  
guessCast(),  
guessDate(),  
castForImport(),  
mChoiceCast(),  
splitForms()
```

Examples

```
## Not run:  
unlockREDCap(connections = c(rcon = "project_alias"),  
              url = "your_redcap_url",  
              keyring = "API_KEYS",  
              envir = globalenv())  
  
Records <- exportRecordsTyped(rcon)  
  
widerRepeated(Records, rcon)  
  
## End(Not run)
```

`writeDataForImport` *Prepare a Data Frame for Import Through the API*

Description

Converts a dataframe into a character value in the format of a CSV for import through the API.

Usage

```
writeDataForImport(data)
```

Arguments

`data` `data.frame` to be imported to the API

Index

- * **datasets**
 - fieldValidationAndCasting, [43](#)
 - redcapDataStructures, [103](#)
 - [.redcapFactor (Extraction), [37](#)
- allocationTable, [3](#)
- allocationTable_offline
 - (allocationTable), [3](#)
- armsMethods, [6](#)
- castCheckCode
 - (fieldValidationAndCasting), [43](#)
- castCheckCodeCharacter
 - (fieldValidationAndCasting), [43](#)
- castChecked
 - (fieldValidationAndCasting), [43](#)
- castCheckedCharacter
 - (fieldValidationAndCasting), [43](#)
- castCheckForImport
 - (fieldValidationAndCasting), [43](#)
- castCheckForImport(), [40](#), [63](#), [98](#)
- castCheckLabel
 - (fieldValidationAndCasting), [43](#)
- castCheckLabelCharacter
 - (fieldValidationAndCasting), [43](#)
- castCode (fieldValidationAndCasting), [43](#)
- castCodeCharacter
 - (fieldValidationAndCasting), [43](#)
- castDpCharacter
 - (fieldValidationAndCasting), [43](#)
- castDpNumeric
 - (fieldValidationAndCasting), [43](#)
- castForImport (fieldCastingFunctions), [37](#)
- castForImport(), [98](#), [108](#), [110](#), [133](#)
- castLabel (fieldValidationAndCasting), [43](#)
- castLabelCharacter
 - (fieldValidationAndCasting), [43](#)
- castRaw (fieldValidationAndCasting), [43](#)
- castTimeHHMM
 - (fieldValidationAndCasting), [43](#)
- castTimeMMSS
 - (fieldValidationAndCasting), [43](#)
- checkbox_suffixes, [9](#)
- cleanseMetaData, [10](#)
- createFileRepositoryFolder, [10](#)
- createFileRepositoryFolder(), [30](#), [53](#), [57](#)
- dagAssignmentMethods, [12](#)
- dagMethods, [15](#)
- default_cast_character
 - (fieldValidationAndCasting), [43](#)
- default_cast_no_factor
 - (fieldValidationAndCasting), [43](#)
- deleteArms (armsMethods), [6](#)
- deleteDags (dagMethods), [15](#)
- deleteDags(), [14](#), [116](#)
- deleteEvents (eventsMethods), [21](#)
- deleteFileRepository
 - (fileRepositoryMethods), [50](#)
- deleteFileRepository(), [12](#), [30](#), [57](#)
- deleteFiles (fileMethods), [47](#)
- deleteFromFileRepository
 - (fromFileRepositoryMethods), [55](#)
- deleteFromFileRepository(), [12](#), [30](#), [53](#)
- deleteRecords, [17](#)
- deleteRecords(), [61](#), [88](#), [92](#)
- deleteUserRoles (userRoleMethods), [126](#)
- deleteUserRoles(), [123](#), [126](#)
- deleteUsers (userMethods), [119](#)
- deleteUsers(), [126](#), [130](#)
- deprecated_redcapProjectInfo, [19](#)
- dropRepeatingNA, [20](#)
- eventsMethods, [21](#)
- exportArms (armsMethods), [6](#)
- exportBulkRecords, [24](#)
- exportBulkRecords(), [98](#)
- exportBundle, [26](#)

- exportBundle(), [19](#)
- exportDags (dagMethods), [15](#)
- exportDags(), [14](#), [116](#)
- exportEvents (eventsMethods), [21](#)
- exportFieldNames, [27](#)
- exportFieldNames(), [36](#), [68](#), [72](#)
- exportFieldNamesArgs
(exportFieldNames), [27](#)
- exportFileRepository
(fileRepositoryMethods), [50](#)
- exportFileRepository(), [12](#), [30](#), [57](#), [86](#)
- exportFileRepositoryListing, [29](#)
- exportFileRepositoryListing(), [12](#), [53](#),
[57](#)
- exportFiles (fileMethods), [47](#)
- exportFiles(), [86](#)
- exportFromFileRepository
(fromFileRepositoryMethods), [55](#)
- exportFromFileRepository(), [12](#), [30](#), [53](#),
[86](#)
- exportInstruments, [31](#)
- exportInstruments(), [28](#), [32](#), [36](#), [68](#), [72](#)
- exportLogging, [32](#)
- exportMappings (mappingMethods), [67](#)
- exportMappings(), [23](#), [28](#), [32](#), [36](#), [72](#)
- exportMetaData (metaDataMethods), [70](#)
- exportMetaData(), [28](#), [32](#), [36](#), [68](#)
- exportNextRecordName
(recordsManagementMethods), [86](#)
- exportNextRecordName(), [92](#)
- exportPdf, [34](#)
- exportPdf(), [28](#), [32](#), [68](#), [72](#), [86](#)
- exportProjectInformation
(projectInformationMethods), [77](#)
- exportRecords (recordsMethods), [88](#)
- exportRecords(), [18](#), [61](#), [88](#), [98](#)
- exportRecords_offline (recordsMethods),
[88](#)
- exportRecordsTyped
(recordsTypedMethods), [93](#)
- exportRecordsTyped(), [18](#), [20](#), [24](#), [25](#), [37](#),
[40](#), [44–46](#), [55](#), [61](#), [62](#), [88](#), [92](#), [108](#),
[111](#), [112](#), [133](#)
- exportRepeatingInstrumentsEvents
(repeatingInstrumentMethods),
[105](#)
- exportReports (recordsMethods), [88](#)
- exportReports(), [88](#), [98](#)
- exportReportsTyped
(recordsTypedMethods), [93](#)
- exportReportsTyped(), [20](#), [40](#), [46](#), [55](#), [88](#),
[92](#), [108](#), [112](#)
- exportSurveyLink (surveyMethods), [112](#)
- exportSurveyParticipants
(surveyMethods), [112](#)
- exportSurveyQueueLink (surveyMethods),
[112](#)
- exportSurveyReturnCode (surveyMethods),
[112](#)
- exportUserDagAssignments
(dagAssignmentMethods), [12](#)
- exportUserDagAssignments(), [17](#), [116](#)
- exportUserRoleAssignments
(userRoleAssignmentMethods),
[124](#)
- exportUserRoleAssignments(), [123](#), [130](#)
- exportUserRoles (userRoleMethods), [126](#)
- exportUserRoles(), [123](#), [126](#)
- exportUsers (userMethods), [119](#)
- exportUsers(), [122](#), [126](#), [128](#), [130](#)
- exportVersion, [36](#)
- Extraction, [37](#)
- fieldCastingFunctions, [37](#)
- fieldCastingFunctions(), [46](#)
- fieldChoiceMapping, [41](#)
- fieldToVar, [42](#)
- fieldValidationAndCasting, [43](#)
- fieldValidationAndCasting(), [38](#), [40](#), [95](#),
[97](#), [98](#)
- fileMethods, [47](#)
- fileRepositoryMethods, [50](#)
- fileRepositoryPath, [54](#)
- filterEmptyRow, [54](#)
- format.invalid (invalidSummary), [62](#)
- fromFileRepositoryMethods, [55](#)
- getProjectIdFields, [58](#)
- globalenv(), [118](#)
- guessCast (fieldCastingFunctions), [37](#)
- guessCast(), [98](#), [108](#), [110](#), [133](#)
- guessDate (fieldCastingFunctions), [37](#)
- guessDate(), [98](#), [110](#), [133](#)
- httr::config(), [102](#)
- httr::httr_options(), [102](#)

- httr::POST(), [8](#), [11](#), [13](#), [16](#), [18](#), [22](#), [28](#), [30](#), [31](#), [33](#), [35](#), [36](#), [49](#), [52](#), [56](#), [60](#), [64](#), [65](#), [68](#), [71](#), [74](#), [78](#), [82](#), [87](#), [91](#), [96](#), [100](#), [104](#), [106](#), [114](#), [116](#), [121](#), [125](#), [128](#)
- importArms (armsMethods), [6](#)
- importDags (dagMethods), [15](#)
- importDags(), [14](#), [116](#)
- importEvents (eventsMethods), [21](#)
- importFileRepository
 - (fileRepositoryMethods), [50](#)
- importFileRepository(), [12](#), [30](#), [57](#)
- importFiles (fileMethods), [47](#)
- importMappings (mappingMethods), [67](#)
- importMappings(), [23](#), [28](#), [32](#), [36](#), [72](#)
- importMetaData (metaDataMethods), [70](#)
- importMetaData(), [28](#), [32](#), [36](#), [68](#)
- importProjectInformation
 - (projectInformationMethods), [77](#)
- importRecords, [59](#)
- importRecords(), [18](#), [88](#), [92](#)
- importRepeatingInstrumentsEvents
 - (repeatingInstrumentMethods), [105](#)
- importRepeatingInstrumentsEvents(), [83](#)
- importToFileRepository
 - (fromFileRepositoryMethods), [55](#)
- importToFileRepository(), [12](#), [30](#), [53](#)
- importUserDagAssignments
 - (dagAssignmentMethods), [12](#)
- importUserDagAssignments(), [17](#), [116](#)
- importUserRoleAssignments
 - (userRoleAssignmentMethods), [124](#)
- importUserRoleAssignments(), [123](#), [130](#)
- importUserRoles (userRoleMethods), [126](#)
- importUserRoles(), [77](#), [123](#), [126](#)
- importUsers (userMethods), [119](#)
- importUsers(), [77](#), [126](#), [130](#)
- invalidSummary, [62](#)
- isNAorBlank
 - (fieldValidationAndCasting), [43](#)
- isNAorBlank(), [39](#), [95](#)
- isZeroCodedCheckField, [62](#)
- makeApiCall, [64](#)
- mappingMethods, [67](#)
- massert, [69](#)
- mChoiceCast (fieldCastingFunctions), [37](#)
- mChoiceCast(), [98](#), [110](#), [133](#)
- metaDataMethods, [70](#)
- metaDataMethodsArgs (metaDataMethods), [70](#)
- missingSummary, [73](#)
- missingSummary(), [76](#)
- missingSummary_offline
 - (missingSummary), [73](#)
- na_values (fieldValidationAndCasting), [43](#)
- offlineConnection (redcapConnection), [99](#)
- parseBranchingLogic, [75](#)
- prepUserImportData, [76](#)
- prepUserImportData(), [122](#), [128](#)
- preserveProject (purgeRestoreProject), [81](#)
- print.invalid (invalidSummary), [62](#)
- print.redcapApiConnection
 - (redcapConnection), [99](#)
- print.redcapFactor (Extraction), [37](#)
- print.redcapOfflineConnection
 - (redcapConnection), [99](#)
- projectInformationMethods, [77](#)
- purgeProject (purgeRestoreProject), [81](#)
- purgeRestoreProject, [81](#)
- raw_cast (fieldValidationAndCasting), [43](#)
- recastRecords (fieldCastingFunctions), [37](#)
- recastRecords(), [98](#), [110](#), [133](#)
- recodeCheck, [84](#)
- reconstituteFileFromExport, [85](#)
- recordsManagementMethods, [86](#)
- recordsMethods, [88](#)
- recordsTypedMethods, [93](#)
- REDCAP_METADATA_FIELDTYPE
 - (redcapDataStructures), [103](#)
- REDCAP_METADATA_VALIDATION_TYPE
 - (redcapDataStructures), [103](#)
- REDCAP_REPEAT_INSTRUMENT_STRUCTURE
 - (redcapDataStructures), [103](#)
- REDCAP_SYSTEM_FIELDS
 - (redcapDataStructures), [103](#)
- redcapConnection, [99](#)
- redcapConnection(), [65](#), [118](#)
- redcapDataStructures, [103](#)

- redcapError, [104](#)
- redcapError(), [7](#), [11](#), [13](#), [16](#), [18](#), [22](#), [28](#), [30](#),
[31](#), [33](#), [35](#), [36](#), [49](#), [52](#), [56](#), [60](#), [68](#), [71](#),
[74](#), [78](#), [82](#), [87](#), [91](#), [96](#), [104](#), [106](#), [114](#),
[116](#), [121](#), [125](#), [128](#)
- redcapFactorFlip, [105](#)
- redcapProjectInfo
(deprecated_redcapProjectInfo),
[19](#)
- renameRecord
(recordsManagementMethods), [86](#)
- renameRecord(), [92](#)
- repeatingInstrumentEventMethods
(repeatingInstrumentMethods),
[105](#)
- repeatingInstrumentMethods, [105](#)
- restoreProject (purgeRestoreProject), [81](#)
- reviewInvalidRecords, [107](#)
- reviewInvalidRecords(), [39](#), [40](#), [98](#)

- splitForms, [109](#)
- splitForms(), [40](#), [98](#), [133](#)
- stringCleanup, [110](#)
- stringCleanup(), [111](#)
- stripHTMLandUnicode, [111](#)
- stripHTMLTags (stringCleanup), [110](#)
- stripHTMLTags(), [112](#)
- stripUnicode (stringCleanup), [110](#)
- stripUnicode(), [112](#)
- summary.invalid (invalidSummary), [62](#)
- surveyMethods, [112](#)
- switchDag, [115](#)
- switchDag(), [14](#), [17](#)
- switchDagArgs (switchDag), [115](#)
- syncUnderscoreCodings, [117](#)

- unitsFieldAnnotation
(stripHTMLandUnicode), [111](#)
- unlockREDCap, [118](#)
- userMethods, [119](#)
- userRoleAssignmentMethods, [124](#)
- userRoleMethods, [126](#)
- utils::read.csv(), [91](#)

- valChoice (fieldValidationAndCasting),
[43](#)
- valChoice(), [39](#), [95](#)
- validateImport, [131](#)
- validateImport(), [61](#)

- validateRedcapData
(redcapDataStructures), [103](#)
- valPhone (fieldValidationAndCasting), [43](#)
- valRx (fieldValidationAndCasting), [43](#)
- valRx(), [39](#), [95](#)
- vectorToApiBodyList, [132](#)

- warnOfZeroCodedCheckCasting
(isZeroCodedCheckField), [62](#)
- warnZeroCodedFieldPresent
(isZeroCodedCheckField), [62](#)
- widerRepeated, [133](#)
- widerRepeated(), [40](#), [98](#), [110](#)
- writeDataForImport, [134](#)