

Package ‘archeoViz’

June 8, 2023

Type Package

Title Visualisation, Exploration, and Web Communication of Archaeological Spatial Data

Version 1.2.0

Date 2023-06-07

Author Sebastien Plutniak [aut, cre] (<<https://orcid.org/0000-0002-6674-3806>>),
Renata Araujo [ctb] (<<https://orcid.org/0000-0001-8874-2858>>),
Sara Giardino [ctb] (<<https://orcid.org/0000-0001-5634-7060>>)

Maintainer Sebastien Plutniak <sebastien.plutniak@posteo.net>

Description An R 'Shiny' application for the visualisation, interactive exploration, and web communication of archaeological spatial data. It includes interactive 3D and 2D visualisations, generation of cross sections and maps of the remains, basic spatial analysis methods (convex hull, regression surfaces, 2D kernel density estimation), and excavation timeline visualisation. 'archeoViz' can be used locally or deployed on a server, either with interactive input of data or with a static data set.

License GPL-3

Repository CRAN

Encoding UTF-8

Imports ggplot2, plotly, mgcv, cxhull, reshape2, svglite, htmlwidgets, shiny, shinythemes, knitr,

Suggests covr, SEAHORS, rmarkdown, markdown, testthat (>= 3.0.0)

Config/testthat.edition 3

VignetteBuilder knitr

URL <https://github.com/sebastien-plutniak/archeoviz>

BugReports <https://github.com/sebastien-plutniak/archeoviz/issues>

NeedsCompilation no

Date/Publication 2023-06-07 23:32:54 UTC

R topics documented:

archeoViz	2
demo_objects_data	5
demo_refits_data	5
demo_timeline_data	6

Index

7

archeoViz

archeoViz

Description

Launch the archeoViz application to visualise, interactive explore, and expose on the web archaeological data from excavation

Usage

```
archeoViz(objects.df=NULL, refits.df=NULL, timeline.df=NULL,
          title=NULL, home.text=NULL, lang="en", set.theme="cosmo",
          square.size = 100,
          reverse.axis.values = NULL, reverse.square.names = NULL,
          add.x.square.labels = NULL, add.y.square.labels = NULL,
          class.variable = NULL, class.values = NULL,
          default.group = "by.layer", location.mode = NULL,
          map.z.val = NULL, map.density = "no", map.refits = NULL,
          plot3d.ratio = 1, plot3d.hulls = NULL, plot3d.surfaces = NULL,
          plot3d.refits = NULL,
          sectionX.x.val = NULL, sectionX.y.val = NULL, sectionX.refits = NULL,
          sectionY.x.val = NULL, sectionY.y.val = NULL, sectionY.refits = NULL,
          camera.center = c(0, 0, 0), camera.eye = c(1.25, 1.25, 1.25),
          run.plots = FALSE, html.export = TRUE
        )
```

Arguments

objects.df	data frame, with data documenting the location and type of archaeological remains.
refits.df	data frame, with two columns containin the ids of refitting objects.
timeline.df	data frame, with data documenting the year of excavation of the site's squares.
title	character. Title to display on the application.
home.text	character. Html contents to display on the home page of the application.
lang	character. Language of the interface, one of 'en' (English), 'fr' (French), 'it' (Italian), 'pt' (Portuguese).
set.theme	character. Name of the shinytheme to use.

square.size integer. Size (width and height) in centimeter of the squares in the grid system.
 Default value is 100 cm.

reverse.axis.values
 character. Name of the axis or axes to be reversed (any combination of 'x', 'y', 'z').

reverse.square.names
 character. Name of the axis or axes for which to reverse the order of the square labels (any combination of 'x', 'y', 'z').

add.x.square.labels
 character. Additional square labels for the 'x' axis.

add.y.square.labels
 character. Additional square labels for the 'y' axis.

class.variable character. At the launch of the app, name of the variable to preselect.

class.values character. At the launch of the app, names of the values to preselect.

default.group character. At the launch of the app, preselection of the variable used to group data (one of 'by.layer' or 'by.variable').

location.mode character. At the launch of the app, preselection of the location method (one of 'exact', 'fuzzy', 'show.uncertainty').

map.z.val double. Minimal and maximal Z depth coordinates values to display in the map plot, e.g. c(0, 30).

map.density character. At the launch of the app, whether to compute and show density contours in the map plot (one of 'no', 'overall', 'by.variable').

map.refits logical. Whether to show refits in the map plot.

plot3d.ratio double. At the launch of the app, ratio of the vertical axis in the 3D plot.

plot3d.hulls logical. At the launch of the app, whether to compute and show convex hulls in the 3D plot.

plot3d.surfaces
 logical. At the launch of the app, whether to compute and show regression in the 3D plot.

plot3d.refits logical. At the launch of the app, whether to show refits on the 3D section plot.

sectionX.x.val double. At the launch of the app, minimal and maximal X coordinates values to display in the X section plot, e.g. c(10, 20).

sectionX.y.val double. At the launch of the app, minimal and maximal Y coordinates values to display in the X section plot, e.g. c(10, 20).

sectionX.refits
 logical. At the launch of the app, whether to show refits in the X section plot.

sectionY.x.val double. At the launch of the app, minimal and maximal X coordinates values to display in the Y section plot, e.g. c(10, 20).

sectionY.y.val double. At the launch of the app, minimal and maximal Y coordinates values to display in the Y section plot, e.g. c(10, 20).

sectionY.refits
 logical. At the launch of the app, whether to show refits in the Y section plot.

<code>camera.center</code>	double. In 3D plot, x,y,z coordinates of the point to which the camera is oriented, to pass to the ‘plotly::layout()‘ function. Default value: c(x=0, y=0, z=0).
<code>camera.eye</code>	double. In 3D plot, x,y,z coordinates of the camera’s view point, to pass to the ‘plotly::layout()‘ function. Default value: c(x=1.25, y=1.25, z=1.25).
<code>run.plots</code>	logical. Whether to immediately compute and show plots (without requiring the user to click on the buttons in the interface).
<code>html.export</code>	logical. Whether or not to allow figures to be exported as html widgets.

Details

This function launches the ‘archeoViz‘ application. It can be used without parameter, allowing the user to input data through the "Input data" tab. Alternatively, the ‘objects.df‘ parameter, and the optional ‘refits.df‘ and ‘timeline.df‘ parameters, can be used to input data.frames about the archaeological objects, the refitting relationships between these objects, and the chronology of the excavation, respectively.

The aspect of the application can be modified using the ‘title‘, ‘home.text‘, and ‘set.theme‘ parameters. Possible values for the ‘set.theme‘ parameter includes the allowed values for the ‘shinytheme()‘ function (i.e., “cerulean”, “cosmo”, “cyborg”, “darkly”, “flatly”, “journal”, “lumen”, “paper”, “readable”, “sandstone”, “simplex”, “slate”, “spacelab”, “superhero”, “united”, “yeti”).

Note that the ‘SEAHORS‘ package includes interactive features to format a dataset in ‘archeoViz‘ format, export it or send it to an online ‘archeoViz‘ instance.

Value

Launch the ‘archeoViz‘ Shiny application.

Author(s)

Sebastien Plutniak <sebastien.plutniak at posteo.net>

See Also

`shiny shinytheme plotly layout ggplot2 gam cxhull hullMesh SEAHORS`

Examples

```
## Not run:
# running the app with no particular data and settings:
archeoViz()

# running the app with a particular data set:
objects <- demo_objects_data(1000)
refits <- demo_refits_data(1000)
archeoViz(objects.df=objects, refits.df=refits, title="My data set")

## End(Not run)
```

demo_objects_data *Generates an "objects" data set populated with random values.*

Description

A convenient function to generate a data set to be used for the objects.df parameter of the [archeoViz](#) function.

Usage

```
demo_objects_data(n.objects)
```

Arguments

n.objects numerical, number of objects to include in the data set.

Value

A data.frame with 12 columns ("id", "square_x", "square_y", "xmin", "xmax", "ymin", "ymax", "zmin", "zmax", "layer", "object_type", "object_class_size").

Author(s)

Sebastien Plutniak <sebastien.plutniak at posteo.net>

Examples

```
## Not run: demo_objects_data(n.objects=df=100)
```

demo_refits_data *Generates a "refits" data set populated with random values.*

Description

A convenient function to generate a data set to be used for the refits.df parameter of the [archeoViz](#) function.

Usage

```
demo_refits_data(n.objects)
```

Arguments

n.objects numerical, number of objects between which refitting relationships must be created.

Value

A matrix with 2 columns containing random pairs of numerical values (corresponding to the unique identifiers of the objects generated with the `demo_objects_data` function).

Author(s)

Sebastien Plutniak <sebastien.plutniak at posteo.net>

Examples

```
## Not run: demo_refits_data(n.objects.df=100)
```

`demo_timeline_data` *Generates a "timeline" data set populated with random values.*

Description

A convenient function to generate a data set to be used for the `timeline.df` parameter of the `archeoViz` function.

Usage

```
demo_timeline_data()
```

Details

Note that there is no correspondence between the data generated with `demo_timeline_data` and the data generated with `demo_objects_data` and `demo_refits_data`.

Value

A data frame with 3 columns containing random data ("year", "square_x", "square_y").

Author(s)

Sebastien Plutniak <sebastien.plutniak at posteo.net>

Examples

```
## Not run: demo_timeline_data()
```

Index

archeoViz, 2, 5, 6
cxhull, 4
demo_objects_data, 5, 6
demo_refits_data, 5
demo_timeline_data, 6
gam, 4
hullMesh, 4
layout, 4
shinytheme, 4