

Package ‘clinPK’

October 12, 2022

Type Package

Title Clinical Pharmacokinetics Toolkit

Version 0.11.1

Date 2022-05-06

Description Calculates equations commonly used in clinical pharmacokinetics and clinical pharmacology, such as equations for dose individualization, compartmental pharmacokinetics, drug exposure, anthropomorphic calculations, clinical chemistry, and conversion of common clinical parameters. Where possible and relevant, it provides multiple published and peer-reviewed equations within the respective R function.

URL <https://github.com/InsightRX/clinPK>

License MIT + file LICENSE

RoxygenNote 7.1.2

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Ron Keizer [aut],
Jasmine Hughes [aut],
Dominic Tong [aut],
Kara Woo [aut, cre],
InsightRX [cph, fnd]

Maintainer Kara Woo <kara@insight-rx.com>

Repository CRAN

Date/Publication 2022-05-09 08:10:05 UTC

R topics documented:

clinPK-package	4
absolute2relative_bsa	4
accumulation_ratio	5

add_ruv	5
as.num	6
auc2dose	6
calc_abw	7
calc_aki_stage	7
calc_amts_for_conc	9
calc_baseline_scr	10
calc_bmi	11
calc_bsa	11
calc_creat	12
calc_creat_neo	13
calc_dosing_weight	13
calc_egfr	14
calc_egfr_cystatin	18
calc_ffm	18
calc_ibw	20
calc_kel_double_tdm	21
calc_kel_single_tdm	22
calc_kgfr	23
calc_lbw	24
calc_t12	25
check_covs_available	26
cm2inch	26
conc2mol	27
convert_creat_assay	27
convert_creat_unit	28
convert_flow_unit	28
dose2auc	29
egfr_cov_reqs	30
find_factor	30
find_nearest_dose	31
find_nearest_interval	31
fraction_of_ss	32
ibw_devine	32
ibw_standard	33
inch2cm	33
is.nil	34
kdigo_stage	34
kg2lbs	35
kg2oz	35
lbs2kg	36
mol2conc	36
nca	37
nca_trapezoid	38
oz2kg	39
pct_bmi_for_age	39
pct_for_age_generic	40
pct_height_for_age	40

pct_weight_for_age	41
pk_1cmt_bolus	42
pk_1cmt_bolus_cmax_ss	42
pk_1cmt_bolus_cmin_ss	43
pk_1cmt_bolus_dose_from_cmax	44
pk_1cmt_bolus_dose_from_cmin	44
pk_1cmt_bolus_ss	45
pk_1cmt_inf	46
pk_1cmt_inf_cmax_ss	47
pk_1cmt_inf_cmin_ss	47
pk_1cmt_inf_dose_for_range	48
pk_1cmt_inf_dose_from_cmax	49
pk_1cmt_inf_dose_from_cmin	49
pk_1cmt_inf_ss	50
pk_1cmt_oral	51
pk_1cmt_t12	52
pk_2cmt_bolus	52
pk_2cmt_bolus_cmax_ss	53
pk_2cmt_bolus_cmin_ss	54
pk_2cmt_bolus_dose_from_cmax	55
pk_2cmt_bolus_dose_from_cmin	56
pk_2cmt_bolus_ss	57
pk_2cmt_inf	58
pk_2cmt_inf_cmax_ss	58
pk_2cmt_inf_cmin_ss	59
pk_2cmt_inf_dose_from_cmax	60
pk_2cmt_inf_dose_from_cmin	61
pk_2cmt_inf_ss	62
pk_2cmt_t12	63
pk_2cmt_t12_interval	63
print.nca_output	64
read_who_table	64
relative2absolute_bsa	65
remove_lt_gt	66
time_to_ss	66
valid_units	67
weight2kg	67
%>=%	68
%<=%	68

clinPK-package

clinPK

Description

Equations and tool for clinical pharmacokinetics

Author(s)

Ron Keizer <ronkeizer@gmail.com>

absolute2relative_bsa *Convert quantity expressed in absolute units relative to normalized BSA*

Description

Often used for eGFR estimates

Usage

```
absolute2relative_bsa(quantity, bsa = NULL, ...)
```

Arguments

quantity	quantity expressed in absolute units
bsa	ideal body weight in kg
...	arguments passed on to 'calc_bsa', if bsa is NULL

Value

quantity expressed relative to /1.73m²

Examples

```
absolute2relative_bsa(quantity = 60, bsa = 1.6)  
absolute2relative_bsa(quantity = 60, weight = 14, height = 90, method = "dubois")
```

accumulation_ratio	<i>Calculate accumulation ratio This is the ratio of drug concentration or AUC at steady state over concentrations after single dose</i>
--------------------	------------------------------------------------------------------------------------------------------------------------------------------

Description

Calculate accumulation ratio This is the ratio of drug concentration or AUC at steady state over concentrations after single dose

Usage

```
accumulation_ratio(kel = NULL, halflife = NULL, tau = 24)
```

Arguments

kel	drug elimination rate
halflife	halflife. Either 'kel' or 'halflife' is required.
tau	dosing interval

Examples

```
accumulation_ratio(halflife = 24, tau = 24)  
accumulation_ratio(kel = 0.08, tau = 12)
```

add_ruv	<i>Add residual variability to data</i>
---------	-----------------------------------------

Description

Add residual variability to data

Usage

```
add_ruv(x, ruv = list())
```

Arguments

x	data
ruv	list with arguments prop, add, exp

Examples

```
y <- pk_1cmt_inf()$y  
y + add_ruv(y, list(prop = 0.1, add = 0.05))
```

as.num	<i>factors or characters to numeric</i>
--------	-----------------------------------------

Description

factors or characters to numeric

Usage

```
as.num(x)
```

Arguments

x	value
---	-------

auc2dose	<i>Convert AUCtau or AUCt to dose (for 1-compartment linear PK model)</i>
----------	---------------------------------------------------------------------------

Description

Convert AUCtau or AUCt to dose (for 1-compartment linear PK model)

Usage

```
auc2dose(auc, CL, V, t_auc = NA)
```

Arguments

auc	AUCtau
CL	Clearance
V	Volume of distribution
t_auc	if AUCtau is not known but only AUCt, 't_auc' specifies time until which AUC_t is calculated to be able to calculate dose

Examples

```
auc2dose(450, CL = 5, V = 50)
```

calc_abw	<i>Calculate adjusted body weight (ABW)</i>
----------	---------------------------------------------

Description

Often used for chemotherapy calculations when actual weight > 120 Adjusted body weight is returned in units of kg.

Usage

```
calc_abw(weight = NULL, ibw = NULL, factor = 0.4, verbose = TRUE, ...)
```

Arguments

weight	actual body weight in kg
ibw	ideal body weight in kg
factor	weighting factor, commonly 0.4 or 0.3
verbose	show output?
...	parameters passed to ibw function (if 'ibw' not specified)

Value

adjusted body weight in kg

Examples

```
calc_abw(weight = 80, ibw = 60)
calc_abw(weight = 80, height = 160, sex = "male", age = 60)
```

calc_aki_stage	<i>Calculate AKI stage</i>
----------------	----------------------------

Description

Calculate AKI class based on serum creatinine values over time, using various methods for children (pRIFLE) and adults (RIFLE, KDIGO)

Usage

```

calc_aki_stage(
  scr = NULL,
  times = NULL,
  method = "kdigo",
  baseline_scr = "median",
  baseline_egfr = NULL,
  first_dose_time = NULL,
  age = NULL,
  egfr = NULL,
  egfr_method = NULL,
  force_numeric = FALSE,
  override_prifle_baseline = FALSE,
  verbose = TRUE,
  return_object = TRUE,
  ...
)

```

Arguments

scr	serum creatinine in mg/dL. Use 'convert_creat()' to convert from mmol/L. Values below the detection limit (" <0.2 ") will be converted to numeric (0.2)
times	creatinine sample times in hours
method	classification method, one of 'KDIGO', 'RIFLE', 'pRIFLE' (case insensitive)
baseline_scr	baseline serum creatinine, required for 'RIFLE' classification. Will use value if numeric. If 'character', can be either 'median', 'median_before_treatment', 'lowest', or 'first'.
baseline_egfr	baseline eGFR, required for 'RIFLE' classifications. Will take median of 'egfr' values if 'NULL'.
first_dose_time	time in hours of first dose relative to sCr value, used for calculate baseline serum creatinine in 'median_before_treatment' approach.
age	age in years, needed when eGFR is used in the classification method
egfr	eGFR in ml/min/1.73m ² . Optional, can also be calculated if 'age', 'weight', 'height', 'sex', 'egfr_method' are specified as arguments.
egfr_method	eGFR calculation method, used by 'calc_egfr()'. If NULL, will pick default based on classification system ('cockroft_gault' for RIFLE / KDIGO, 'revised_schwartz' for pRIFLE).
force_numeric	keep stage numeric (1, 2, or 3), instead of e.g. "R", "I", "F" as in RIFLE. Default 'FALSE'.
override_prifle_baseline	by default, 'pRIFLE' compares eGFR to 120 ml/min. Override by setting to TRUE.
verbose	verbose ('TRUE' or 'FALSE')
return_object	return object with detailed data (default 'TRUE'). If 'FALSE', will just return maximum stage.

... arguments passed on to 'calc_egfr()'

References

- **pRIFLE**: Ackan-Arikan et al. "Modified RIFLE criteria in critically ill children with acute kidney injury." *Kidney Int.* (2007)
- **RIFLE**: Bellomo et al. "Acute renal failure - definition, outcome measures, animal models, fluid therapy and information technology needs: the Second International Consensus Conference of the Acute Dialysis Quality Initiative (ADQI) Group." *Critical Care.* (2004)
- **KDIGO**: Khwaja. "KDIGO clinical practice guidelines for acute kidney injury." *Nephron Clinical Practice.* (2012)
- **pRIFLE baseline eGFR**: Soler et al. "pRIFLE (Pediatric Risk, Injury, Failure, Loss, End Stage Renal Disease) score identifies Acute Kidney Injury and predicts mortality in critically ill children : a prospective study." *Pediatric Critical Care Medicine.* (2014)

Examples

```
calc_aki_stage(
  scr = c(0.7, 0.9, 1.8, 1.5),
  t = c(0, 40, 100, 130),
  age = 50, weight = 60,
  height = 170, sex = "female")
```

calc_amts_for_conc	<i>Calculate the amounts in all compartments in a compartmental PK system based on a given concentration in the central compartment, and assuming steady state.</i>
--------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------

Description

Calculate the amounts in all compartments in a compartmental PK system based on a given concentration in the central compartment, and assuming steady state.

Usage

```
calc_amts_for_conc(conc = 10, parameters = NULL, n_cmt = 1)
```

Arguments

conc	concentration in central compartment
parameters	for PK model
n_cmt	number of compartments

Examples

```

calc_amts_for_conc(conc = 10, parameters = list(CL = 5, V = 50), n_cmt = 1)
calc_amts_for_conc(
  conc = 10,
  parameters = list(CL = 5, V = 50, Q = 20, V2 = 100),
  n_cmt = 2)
calc_amts_for_conc(
  conc = 10,
  parameters = list(CL = 5, V = 50, Q = 20, V2 = 100, Q2 = 30, V3 = 200),
  n_cmt = 3)

```

calc_baseline_scr	<i>Calculate baseline sCr</i>
-------------------	-------------------------------

Description

Calculate baseline sCr

Usage

```

calc_baseline_scr(
  baseline_scr,
  scr,
  times,
  method,
  first_dose_time = NULL,
  verbose
)

```

Arguments

baseline_scr	baseline serum creatinine method (character). See calc_aki_stage() for available options.
scr	serum creatinine in mg/dL. Use 'convert_creat()' to convert from mmol/L. Values below the detection limit (" <0.2 ") will be converted to numeric (0.2)
times	creatinine sample times in hours
method	classification method, one of 'KDIGO', 'RIFLE', 'pRIFLE' (case insensitive)
first_dose_time	time in hours of first dose relative to sCr value, used for calculate baseline serum creatinine in 'median_before_treatment' approach.
verbose	verbose ('TRUE' or 'FALSE')

calc_bmi	<i>Calculate BMI</i>
----------	----------------------

Description

Calculate BMI

Usage

```
calc_bmi(weight, height)
```

Arguments

weight	weight in kg
height	height in cm

Value

value of BMI in kg/m²

Examples

```
calc_bmi(weight = 70, height = 160)
```

calc_bsa	<i>Calculate body surface area</i>
----------	------------------------------------

Description

Get an estimate of body-surface area (in m²) based on weight and height

Usage

```
calc_bsa(  
  weight = NULL,  
  height = NULL,  
  method = c("dubois", "mosteller", "haycock", "gehan_george", "boyd")  
)
```

Arguments

weight	weight
height	height
method	estimation method, choose from 'dubois', 'mosteller', 'haycock', 'gehan_george', 'boyd'

Value

Returns a list of the following elements:

value	Body Surface Area (BSA) in units of m2
unit	Unit describing BSA, (m2)

Examples

```
calc_bsa(weight = 70, height = 170)
calc_bsa(weight = 70, height = 170, method = "gehan_george")
```

calc_creat	<i>Estimate serum creatinine</i>
------------	----------------------------------

Description

Calculate an estimated serum creatinine. Function takes vectorized input as well.

Usage

```
calc_creat(sex = NULL, age = NULL, digits = 1)
```

Arguments

sex	sex, either 'male' or 'female'
age	age in years
digits	number of digits to round to

Details

Uses equations described in Ceriotti et al. Clin Chem. 2008, and Junge W et al. Clin Chim Acta. 2004. For age 15-18, a linear interpolation is used between equations for <15 and >18 years as described in Johanssen A et al. Ther Drug Monit 2011.

Examples

```
calc_creat(sex = "male", age = 40)
calc_creat(sex = "male", age = c(10, 17, 60))
```

calc_creat_neo *Estimate serum creatinine in neonates*

Description

Calculate an estimated serum creatinine. Function takes vectorized input as well.

Usage

```
calc_creat_neo(pma = NULL, digits = 1)
```

Arguments

pma	post-natal age in weeks
digits	number of digits to round to

Details

Uses equations described in Germovsek E et al. (<http://www.ncbi.nlm.nih.gov/pubmed/27270281>) based on data from Cuzzolin et al. (<http://www.ncbi.nlm.nih.gov/pubmed/16773403>) and Rudd et al. (<http://www.ncbi.nlm.nih.gov/pubmed/6838252>)

Examples

```
calc_creat_neo(pma = 36)
convert_creat_unit(calc_creat_neo(pma = 36))
```

calc_dosing_weight *Calculate commonly used "dosing weight"*

Description

Dosing weight is determined based on total (TBW), ideal (IBW), or adjusted (ABW) body weight in kg.

Usage

```
calc_dosing_weight(weight, height, age, sex, verbose = TRUE, ...)
```

Arguments

weight	weight
height	height
age	age
sex	sex
verbose	verbosity ('TRUE' or 'FALSE')
...	passed to 'calc_abw()' function

Details

This is derived using following: - In principle, use IBW - If total body weight (TBW) > 1.2*IBW, then use ABW - If TBW < IBW, use TBW

Value

Returns a list of the following elements:

value	Dosing weight, in units of kg
unit	Units of dosing weight (kg)
type	Type of dosing weight selected, e.g., total body weight, ideal body weight.

Examples

```
calc_dosing_weight(weight = 50, height = 170, sex = "female", age = 50)
```

calc_egfr	<i>Calculate eGFR</i>
-----------	-----------------------

Description

Calculate the estimated glomerular filtration rate (an indicator of renal function) based on measured serum creatinine using one of the following approaches:

- Cockcroft-Gault (using weight, ideal body weight, or adjusted body weight)
- C-G spinal cord injury (using correction factor of 0.7, representing median correction point reported in the original publication (parapalegic patients: 0.8; tetrapalegic patients: 0.6))
- Revised Lund-Malmo
- Modification of Diet in Renal Disease study (MDRD; with or without consideration of race, using either the original equation (published 2001) or the equation updated to reflect serum creatinine assay standardization (2006))
- CKD-EPI (with or without consideration of race, or 2021 re-fit without race)
- Schwartz
- Schwartz revised / bedside
- Jelliffe
- Jelliffe for unstable renal function. Note that the 15 P_adj recommended for hemodialysis patients is not included in this implementation.
- Wright equation for eGFR in cancer patients, with creatinine measured using the Jaffe assay.

Equations for estimation of eGFR from Cystatin C concentrations are available from the 'calc_egfr_cystatin()' function.

Usage

```
calc_egfr(  
  method = "cockcroft_gault",  
  sex = NULL,  
  age = NULL,  
  scr = NULL,  
  scr_unit = NULL,  
  race = "other",  
  weight = NULL,  
  height = NULL,  
  bsa = NULL,  
  preterm = FALSE,  
  ckd = FALSE,  
  times = NULL,  
  bsa_method = "dubois",  
  relative = NULL,  
  unit_out = "mL/min",  
  verbose = TRUE,  
  min_value = NULL,  
  max_value = NULL,  
  fail = TRUE,  
  ...  
)  
  
egfr_wright(age, bsa, sex, scr)  
  
egfr_jelliffe(age, sex, bsa, scr)  
  
egfr_jelliffe_unstable(weight, times, scr, age, sex)  
  
egfr_mdrd(sex, race, scr, age, use_race, original_expression)  
  
egfr_ckd_epi(sex, race, scr, age, use_race)  
  
egfr_ckd_epi_as_2021(sex, scr, age)  
  
egfr_cockcroft_gault_sci(sex, age, scr, weight)  
  
egfr_cockcroft_gault(sex, age, scr, weight)  
  
egfr_malmo_lund(sex, age, scr)  
  
egfr_bedside_schwartz(age, height, scr, verbose)  
  
egfr_schwartz(age, preterm, sex, height, scr)
```

Arguments

method	eGFR estimation method, choose from ‘cockcroft_gault’, ‘cockcroft_gault_ideal’, ‘cockcroft_gault_adjusted’, ‘cockcroft_gault_adaptive’, ‘mdrd’, ‘mdrd_ignore_race’, ‘mdrd_original’, ‘mdrd_original_ignore_race’, ‘ckd_epi’, ‘ckd_epi_ignore_race’, ‘ckd_epi_as_2021’, ‘malmo_lund_revised’, ‘schwartz’, ‘jelliffe’, ‘jellife_unstable’, ‘wright’.
sex	sex
age	age, in years
scr	serum creatinine (mg/dL)
scr_unit,	‘mg/dL’ or ‘micromol/L’ (==‘umol/L’)
race	‘black’ or ‘other’, Required for CKD-EPI and MDRD methods for estimating GFR. To use these methods without race, use ‘method = "ckd_epi_ignore_race"’, ‘method = "ckd_epi_as_2021"’, ‘method = "mdrd_ignore_race"’ or ‘method = "mdrd_original_ignore_race"’. See Note section below for important considerations when using race as a predictive factor in eGFR.
weight	weight, in ‘kg’
height	height, in ‘cm’, used for converting to/from BSA-normalized units.
bsa	body surface area
preterm	is patient preterm? Used for Schwartz method.
ckd	chronic kidney disease? Used for Schwartz method.
times	vector of sampling times (in days!) for creatinine (only used in Jelliffe equation for unstable patients)
bsa_method	BSA estimation method, see ‘calc_bsa()’ for details
relative	‘TRUE’/‘FALSE’. Report eGFR as per 1.73 m ² ? Requires BSA if re-calculation required. If ‘NULL’ (=default), will choose value typical for ‘method’.
unit_out	‘ml/min’ (default), ‘L/hr’, or ‘mL/hr’
verbose	verbosity, show guidance and warnings. ‘TRUE’ by default
min_value	minimum value (‘NULL’ by default). The cap is applied in the same unit as the ‘unit_out’.
max_value	maximum value (‘NULL’ by default). The cap is applied in the same unit as the ‘unit_out’.
fail	invoke ‘stop()’ if not all covariates available?
...	arguments passed on to ‘calc_abw’ or ‘calc_dosing_weight’
use_race	whether to include race as a factor in the calculation (TRUE or FALSE); see note
original_expression	whether the MDRD equation should use the 2001 coefficient (TRUE) or the 2006 coefficient (FALSE), which was updated for standardization of the creatinine assay.

Note

The MDRD and CKD-EPI equations use race as a factor in estimation of GFR. Racism has historically been and continues to be a problem in medicine, with racialized patients experiencing poorer outcomes. Given this context, the use of race in clinical algorithms should be considered carefully (Vyas et al., *NEJM* (2020)). Provided here are versions of the CKD-EPI and MDRD equations that do not consider the race of the patient. Removing race from GFR estimation may lead to worse outcomes for Black patients in some contexts (Casal et al., *The Lancet* (2021)). On the other hand, including race in GFR estimation may also prevent Black patients from obtaining procedures like kidney transplants (Zelnick, et al. *JAMA Netw Open.* (2021)). In 2021, the NKF/ASN Task Force on Reassessing the Inclusion of Race in Diagnosing Kidney Diseases published revised versions of the CKD-EPI equations refit on the original data but with race excluded, which may produce less biased estimates (Inker, et al., *NEJM* (2021)).

References

- Cockcroft-Gault: [Cockcroft & Gault, Nephron \(1976\)](#)
- Cockcroft-Gault for spinal cord injury: [Mirahmadi et al., Paraplegia \(1983\)](#)
- Revised Lund-Malmo: [Nyman et al., Clinical Chemistry and Laboratory Medicine \(2014\)](#)
- MDRD: [Manjunath et al., Curr. Opin. Nephrol. Hypertens. \(2001\)](#) and [Levey et al., Clinical Chemistry \(2007\)](#). (See Note.)
- CKD-EPI: [Levey et al., Annals of Internal Medicine \(2009\)](#). (See Note.)
- CKD-EPI (2021): [Inker, et al., NEJM \(2021\)](#).
- Schwartz: [Schwartz et al., Pediatrics \(1976\)](#)
- Schwartz revised / bedside: [Schwartz et al., Journal of the American Society of Nephrology \(2009\)](#)
- Jelliffe: [Jelliffe, Annals of Internal Medicine \(1973\)](#)
- Jelliffe for unstable renal function: [Jelliffe, American Journal of Nephrology \(2002\)](#)
- Wright: [Wright et al., British Journal of Cancer \(2001\)](#)

Examples

```
calc_egfr(sex = "male", age = 50, scr = 1.1, weight = 70)
calc_egfr(sex = "male", age = 50, scr = 1.1, weight = 70, unit_out = "L/hr")
calc_egfr(sex = "male", age = 50, scr = 1.1, weight = 70, bsa = 1.8, method = "ckd_epi")
calc_egfr(sex = "male", age = 50, scr = c(1.1, 0.8),
  weight = 70, height = 170, method = "jelliffe")
calc_egfr(sex = "male", age = 50, scr = c(1.1, 0.8),
  weight = 70, height = 170, method = "jelliffe_unstable")
calc_egfr(sex = "male", age = 50, scr = 1.1,
  weight = 70, bsa = 1.6, method = "malmo_lund_revised", relative = FALSE)
```

calc_egfr_cystatin *Calculate eGFR based on Cystatin C measurements*

Description

Calculate eGFR based on Cystatin C measurements

Usage

```
calc_egfr_cystatin(  
  cystatin = NULL,  
  cystatin_unit = "mg/L",  
  method = "grubb",  
  unit_out = "mL/min"  
)
```

Arguments

cystatin serum cystatin concentration (mg/L)
cystatin_unit,
 only 'mg/L' available
method eGFR estimation method, choose from 'grubb', 'larsson'
unit_out eGFR output unit, choose from 'ml/min', 'ml/hr', 'l/min', 'l/hr'

Examples

```
calc_egfr_cystatin(1.0)  
calc_egfr_cystatin(1.0, method = "larsson")  
calc_egfr_cystatin(1.0, unit_out = "l/hr")
```

calc_ffm *Calculate fat-free mass*

Description

Get an estimate of fat-free mass (FFM, in kg) based on weight, height, and sex (and age for Storset equation).

Usage

```

calc_ffm(
  weight = NULL,
  bmi = NULL,
  sex = NULL,
  height = NULL,
  age = NULL,
  method = c("janmahasatian", "green", "al-sallami", "storset", "bucaloiu", "hume",
    "james", "garrow_webster"),
  digits = 1
)

ffm_janmahasatian_green(weight, sex, height = NULL, bmi = NULL)

ffm_al_sallami(weight, sex, age, height = NULL, bmi = NULL)

ffm_storset(weight, sex, height, age)

ffm_bucaloiu(weight, sex, height, age)

ffm_hume(weight, sex, height)

ffm_james(weight, sex, height)

ffm_garrow_webster(weight, sex, height)

```

Arguments

weight	total body weight in kg
bmi	BMI, only used in 'green' method. If 'weight' and 'height' are both specified, 'bmi' will be calculated on-the-fly.
sex	sex, either 'male' of 'female'
height	height in cm, only required for 'holford' method, can be used instead of 'bmi' for 'green' method
age	age, only used for Storset equation
method	estimation method, one of 'janmahasatian' (default), 'green', 'al-sallami', 'storset', 'bucaloiu', 'hume', 'james', or 'garrow_webster'.
digits	round to number of digits

Details

References: 'janmahasatian', 'green': Janmahasatian et al. Clin Pharmacokinet. 2005;44(10):1051-65) 'al-sallami': Al-Sallami et al. Clin Pharmacokinet 2015 'storset': Storset E et al. TDM 2016 'bucaloiu': Bucaloiu ID et al. Int J of Nephrol Renovascular Dis. 2011 (Morbidly obese females) 'hume': Hume R. J Clin Pathol 1966 'james': James WPT et al. Research on obesity: a report of the DHSS/MRC Group 1976 'garrow_webster': Garrow JS, Webster J. Quetelet's index (W/H²) as a measure of fatness. Int J Obesity 1984

Overview: - Sinha J, Duffull SB, Al-Sallami HS. Clin Pharmacokinet 2018. <https://doi.org/10.1007/s40262-017-0622-5>

Value

Returns a list of the following elements:

value	Fat-free Mass (FFM) in units of kg
unit	Unit describing FFM, (kg)
method	Method used to calculate FFM

Examples

```
calc_ffm(weight = 70, bmi = 25, sex = "male")
calc_ffm(weight = 70, height = 180, age = 40, sex = "female", method = "storset")
```

calc_ibw	<i>Calculate ideal body weight in kg for children and adults</i>
----------	------------------------------------------------------------------

Description

Get an estimate of ideal body weight. This function allows several commonly used equations

Usage

```
calc_ibw(
  weight = NULL,
  height = NULL,
  age = NULL,
  sex = "male",
  method_children = "standard",
  method_adults = "devine"
)
```

Arguments

weight	weight in kg
height	height in cm
age	age in years
sex	sex
method_children	method to use for children >1 and <18 years. Currently "standard" is the only method that is supported.
method_adults	method to use for >=18 years. Currently "devine" is the only method that is supported (Devine BJ. Drug Intell Clin Pharm. 1974;8:650-655).

Details

Equations:

<1yo Use actual body weight

1-17 years old ('standard'): if height < 5ft: $IBW = (\text{height in cm}^2 \times 1.65) / 1000$ if height > 5ft: IBW (male) = $39 + (2.27 \times \text{height in inches over 5 feet})$ IBW (female) = $42.2 + (2.27 \times \text{height in inches over 5 feet})$

Methods not implemented yet: McLaren: $IBW = -$ step1: $x = 50\text{th percentile height for given age}$ - step2: $IBW = 50\text{th percentile weight for } x \text{ on weight-for-height scale}$ Moore: $IBW = \text{weight at percentile } x \text{ for given age, where } x \text{ is percentile of height for given age}$ BMI: $IBW = 50\text{th percentile of BMI for given age } x \text{ (height in m)}^2$ ADA: $IBW = 50\text{th percentile of WT for given age}$

≥ 18 years old (Devine equation) IBW (male) = $50 + (2.3 \times \text{height in inches over 5 feet})$ IBW (female) = $45.5 + (2.3 \times \text{height in inches over 5 feet})$

Examples

```
calc_ibw(weight = 70, height = 170, age = 40, sex = "female")
calc_ibw(weight = 30, height = 140, age = 10, sex = "female")
```

calc_kel_double_tdm *Calculate elimination rate when given two TDM samples*

Description

Calculate elimination rate when given two TDM samples

Usage

```
calc_kel_double_tdm(
  dose = 1000,
  t = c(2, 11.5),
  dv = c(30, 10),
  tau = 12,
  t_inf = 1,
  V = NULL,
  steady_state = TRUE,
  return_parameters = FALSE
)
```

Arguments

dose	dose amount
t	time or time after dose, vector of size 2
dv	observed value, vector of size 2
tau	dosing interval

t_inf	infusion time
V	if specified, use that (empiric) value and don't estimate from data. Default 'NULL'.
steady_state	samples taken at steady state? Only influences AUCtau.
return_parameters	return all parameters instead of only kel?

Examples

```
calc_kel_double_tdm(dose = 1000, t = c(3, 18), dv = c(30, 10))
```

calc_kel_single_tdm *Calculate elimination rate when given a single TDM sample*

Description

Using iterative k_{el} calculation, and based on given Volume

Usage

```
calc_kel_single_tdm(
  dose = 1000,
  V = 50,
  t = 10,
  dv = 10,
  tau = 12,
  t_inf = 1,
  kel_init = 0.1,
  n_iter = 25,
  learn_rate = 0.2
)
```

Arguments

dose	dose amount
V	volume of distribution
t	time or time after dose
dv	observed value
tau	dosing interval
t_inf	infusion time
kel_init	estimate of elimination rate
n_iter	number of iterations to improve estimate of elimination rate
learn_rate	default is 0.2

Examples

```
calc_kel_single_tdm(dose = 1000, t = 18)
```

calc_kgfr	<i>Calculate kinetic GFR</i>
-----------	------------------------------

Description

Calculate the kinetic GFR based on a patients first two serum creatinine measurements. Kinetic GFR may be more predictive of future AKI for patients whose serum creatinine is changing quickly. Briefly, an increase in SCr over the course of a day indicates an effective GFR lower than the most recent SCr measurement may indicate if steadystate is assumed, while a decrease in SCr over a short time indicates a higher effective GFR than the most recent SCr would indicate. There are several ways of approximating maximum theoretical creatinine accumulation rate; here the method used by Pianta et al., (PLoS ONE, 2015) has been implemented.

Usage

```
calc_kgfr(
  scr1 = NULL,
  scr2 = NULL,
  scr_unit = "mg/dl",
  time_delay = NULL,
  weight = NULL,
  vd = NULL,
  egfr = NULL,
  egfr_method = NULL,
  sex = NULL,
  age = NULL,
  height = NULL,
  ...
)
```

Arguments

scr1	baseline scr
scr2	second scr measurement
scr_unit	scr unit, defaults to mg/dl
time_delay	time between scr1 and scr2 in hours
weight	patient weight in kg
vd	volume of distribution in L, defaults to 0.6 * weight
egfr	eGFR in ml/min at the time of scr1, or leave blank to call calc_egfr
egfr_method	string, only necessary if egfr is not specified.
sex	string (male or female), only necessary if egfr is not specified.

age age in years, only necessary if egfr is not specified.
 height in m, necessary only for some egfr calculation methods.
 ... further arguments (optional) to be passed to calc_egfr.

Value

kGFR, in ml/min

References

[Pianta et al., PLoS ONE \(2015\)](#)

Examples

```
calc_kgfr(weight = 100, scr1 = 150, scr2 = 200, scr_unit = 'umol/l',
          time_delay = 24, egfr = 30)
calc_kgfr(weight = 70, scr1 = 350, scr2 = 300, scr_unit = 'umol/l',
          time_delay = 24, egfr_method = 'mdrd', age = 70, sex = 'male')
```

calc_lbw

Calculate lean body weight

Description

Get an estimate of lean body weight (LBW, in kg) based on weight, height, and sex.

Usage

```
calc_lbw(
  weight = NULL,
  bmi = NULL,
  sex = NULL,
  height = NULL,
  method = "green",
  digits = 1
)
```

Arguments

weight total body weight in kg
 bmi bmi
 sex sex, either 'male' of 'female'
 height height in cm
 method estimation method, either 'green' (default), 'boer', 'james', 'hume'
 digits round to number of digits

Details

Note: technically not the same as fat-free mass, although difference is small.

References: 'green': Green and Duffull. Clin Pharmacol Ther 2002; 'james': Absalom AR et al. Br J Anaesth 2009; 103:26-37. James W. Research on obesity. London: Her Majesty's Stationary Office, 1976. 'hume' : Hume R et al. J Clin Pathol. 1966 Jul; 19(4):389-91. 'boer' : Boer P et al. Am J Physiol 1984; 247: F632-5

Value

Returns a list of the following elements:

value	Lean Body Weight (LBW) in units of kg
unit	Unit describing LBW, (kg)

Examples

```
calc_lbw(weight = 80, height = 170, sex = "male")
calc_lbw(weight = 80, height = 170, sex = "male", method = "james")
```

 calc_t12

Calculate half-life based on two points

Description

based on two sampling points (in same interval)

Usage

```
calc_t12(t1, t2, y1, y2)
```

Arguments

t1	first sampling timepoint
t2	second sampling timepoint
y1	first sample value
y2	second sample value

Examples

```
calc_t12(3, 24, 30, 10)
```

check_covs_available *Returns parameters needed to calculate eGFR according to the method specified.*

Description

returns true if all patient covs specified in required covs are non-null, non-NA and not a 0-character string. See 'is.nil' for missing data types checked. Returns TRUE if no covariates are required.

Usage

```
check_covs_available(
  cov_reqs = NULL,
  patient_covs = NULL,
  verbose = TRUE,
  fail = TRUE
)
```

Arguments

cov_reqs	vector of covariates required for calculating derived covariate
patient_covs	named list of covariates
verbose	stop and describe missing covariate(s)?
fail	invoke 'stop()' if not all covariates available?

Examples

```
check_covs_available(
  egfr_cov_reqs('cockcroft_gault_ideal')[[1]],
  list(creat = 1, weight = 100, height = 160, sex = 'female', age = 90))
```

cm2inch

Convert cm to inch

Description

Convert cm to inch

Usage

```
cm2inch(cm)
```

Arguments

cm	vector
----	--------

Examples

```
cm2inch(2.54)
```

```
conc2mol          Convert concentration to molar
```

Description

Convert concentration to molar

Usage

```
conc2mol(conc = NULL, unit_conc = NULL, mol_weight = NULL, unit_mol = NULL)
```

Arguments

conc	concentration in e.g. g/L
unit_conc,	one of 'g/l', 'mg/l', 'microg/l', 'mcg/l', 'ng/l', 'mg/ml', 'microg/ml', 'mcg/ml', 'ng/ml'
mol_weight	concentration in g/mol
unit_mol	one of 'mol/L', 'mmol/mL', 'mmol/L'

Examples

```
conc2mol(100, unit_conc = "g/l", mol_weight = 180.15588)
```

```
convert_creat_assay  Convert serum creatinine from various assays to Jaffe
```

Description

Based on equations as reported in Srivastava et al. 2009 (Pediatr Res. 2009 Jan;65(1):113-6. doi: 10.1203/PDR.0b013e318189a6e8)

Usage

```
convert_creat_assay(scr, from = "idms", to = "jaffe")
```

Arguments

scr	vector of serum creatinine values
from	assay type, either 'jaffe', 'enzymatic' or 'idms'
to	assay type, either 'jaffe', 'enzymatic' or 'idms'

Examples

```
convert_creat_assay(scr = c(1.1, 0.8, 0.7), from = "enzymatic", to = "jaffe")
```

convert_creat_unit *Convert creatinine to different unit*

Description

Convert creatinine to different unit

Usage

```
convert_creat_unit(value = NULL, unit_in = "mg/dL")
```

Arguments

value	serum creatinine in either mg/dL or micromol/L
unit_in	unit, either 'mg/dL' or 'micromol/L'

Examples

```
convert_creat_unit(1)
convert_creat_unit(88.42, unit_in = "micromol/l")
```

convert_flow_unit *Convert flow (e.g. clearance) from / to units*

Description

Flow units are expected to be specified as a combination of volume per time units, potentially specified per kg body weight, e.g. "mL/min", or "L/hr/kg".

Usage

```
convert_flow_unit(value = NULL, from = "l", to = "ml", weight = NULL)
```

Arguments

value	flow value
from	from flow unit, e.g. 'L/hr'.
to	to flow unit, e.g. 'mL/min'
weight	for performing per weight (kg) conversion

Details

Accepted volume units are "L", "dL", and "mL". Accepted time units are "min", "hr", and "day". The only accepted weight unit is "kg".

The function is not case-sensitive.

Examples

```
## single values
convert_flow_unit(60, "L/hr", "ml/min")
convert_flow_unit(1, "L/hr/kg", "ml/min", weight = 80)

## vectorized
convert_flow_unit(
  c(10, 20, 30),
  from = c("L/hr", "mL/min", "L/hr"),
  to = c("ml/min/kg", "L/hr", "L/hr/kg"),
  weight = c(70, 80, 90))
```

dose2auc	<i>Convert dose to expected AUCinf or AUCt for 1 compartment linear PK model</i>
----------	----------------------------------------------------------------------------------

Description

Convert dose to expected AUCinf or AUCt for 1 compartment linear PK model

Usage

```
dose2auc(dose, CL, V, t_auc = NULL)
```

Arguments

dose	dose amount
CL	Clearance
V	Volume of distribution
t_auc	if AUC_t is desired, 't_auc' specifies time until which AUC_t is calculated

Examples

```
dose2auc(dose = 1000, CL = 5, V = 50)
dose2auc(dose = 1000, CL = 5, V = 50, t_auc = c(12, 24, 48, 72))
```

egfr_cov_reqs	<i>Returns parameters needed to calculate eGFR according to the method specified.</i>
---------------	---------------------------------------------------------------------------------------

Description

returns a named list, with the name being the eGFR method after being checked for certain typos or misspecifications, and the values being the required covariates.

Usage

```
egfr_cov_reqs(method, relative = NULL)
```

Arguments

method	egfr calculation method
relative	if egfr calculations should be relative or not

Examples

```
egfr_cov_reqs('schwartz_revised')
```

find_factor	<i>Helper function to grab the conversion factor from an input unit and given list</i>
-------------	----------------------------------------------------------------------------------------

Description

Helper function to grab the conversion factor from an input unit and given list

Usage

```
find_factor(full_unit, units = NULL, prefix = "")
```

Arguments

full_unit	full unit, e.g. "mL/min/kg"
units	unit specification list, e.g. 'list("ml" = 1/1000, "dl" = 1/10, "l" = 1)'
prefix	prefix used in matching units, e.g. "^" only matches at start of string while "_" matches units specified as "/"

find_nearest_dose	<i>Generic function to calculate the dose nearest to a specific dose unit increment</i>
-------------------	-----------------------------------------------------------------------------------------

Description

Generic function to calculate the dose nearest to a specific dose unit increment

Usage

```
find_nearest_dose(dose = NULL, increment = 250, type = "round")
```

Arguments

dose	dose value
increment	available increments of dose
type	how to round, one of 'round', 'floor', or 'ceiling'

Examples

```
find_nearest_dose(573)
find_nearest_dose(573, increment = 50)
```

find_nearest_interval	<i>Generic function to calculate the interval nearest to a possible dosing interval</i>
-----------------------	-----------------------------------------------------------------------------------------

Description

Generic function to calculate the interval nearest to a possible dosing interval

Usage

```
find_nearest_interval(
  interval = NULL,
  possible = c(4, 6, 8, 12, 24, 36, 48),
  type = "absolute"
)
```

Arguments

interval	dose value
possible	available increments of dose
type	pick either 'nearest' absolute interval, or nearest 'lower', or nearest 'higher' interval.

Examples

```
find_nearest_interval(19.7)
find_nearest_interval(19.7, c(6, 8, 12))
```

fraction_of_ss	<i>Calculate fraction of steady state at particular time after start of dosing</i>
----------------	------------------------------------------------------------------------------------

Description

Calculate fraction of steady state at particular time after start of dosing

Usage

```
fraction_of_ss(kel = NULL, halflife = NULL, t = NULL, n = NULL, tau = NULL)
```

Arguments

kel	drug elimination rate
halflife	halflife. Either 'kel' or 'halflife' is required.
t	time at which to calculate fraction of steady state
n	number of dosing intervals after which to calculate fraction of steady state. Requires 'tau' as well, cannot be used together with 't' argument.
tau	dosing interval

Examples

```
fraction_of_ss(halflife = 24, t = 72)
fraction_of_ss(halflife = 36, n = 3, tau = 24)
```

ibw_devine	<i>Calculate IBW using "devine" equation</i>
------------	----------------------------------------------

Description

Calculate IBW using "devine" equation

Usage

```
ibw_devine(age, height = NULL, sex = NULL)
```

Arguments

age	age in years
height	height in cm
sex	sex

ibw_standard	<i>Calculate IBW using "standard" equation</i>
--------------	------------------------------------------------

Description

Calculate IBW using "standard" equation

Usage

```
ibw_standard(age, height = NULL, sex = NULL)
```

Arguments

age	age in years
height	height in cm
sex	sex

inch2cm	<i>Convert inch to cm</i>
---------	---------------------------

Description

Convert inch to cm

Usage

```
inch2cm(inch)
```

Arguments

inch	vector
------	--------

Examples

```
inch2cm(1)
```

<code>is.nil</code>	<i>Check if values in vector are empty</i>
---------------------	--------------------------------------------

Description

Check if values in vector are empty

Usage

```
is.nil(x = NULL)
```

Arguments

<code>x</code>	vector
----------------	--------

<code>kdigo_stage</code>	<i>Calculate AKI stage according to KDIGO criteria</i>
--------------------------	--------------------------------------------------------

Description

Calculate AKI stage according to KDIGO criteria

Usage

```
kdigo_stage(dat, baseline_scr, age)
```

Arguments

<code>dat</code>	Data frame containing at least the following columns: <ul style="list-style-type: none"> • <code>scr</code>: serum creatinine • <code>t</code>: creatinine sample times in hours • <code>baseline_scr_diff</code>: difference between baseline scr and scr at current timepoint • <code>egfr</code>: eGFR at timepoint
<code>baseline_scr</code>	Baseline serum creatinine value (numeric)
<code>age</code>	Patient age

kg2lbs

Convert kg to lbs

Description

Convert kg to lbs

Usage

kg2lbs(kg)

Arguments

kg vector

Examples

kg2lbs(1)

kg2oz

Convert kg to oz

Description

Convert kg to oz

Usage

kg2oz(kg)

Arguments

kg vector

Examples

kg2oz(1)

lbs2kg	<i>Convert lbs to kg</i>
--------	--------------------------

Description

Convert lbs to kg

Usage

```
lbs2kg(lbs)
```

Arguments

lbs	vector
-----	--------

Examples

```
lbs2kg(2.20462)
```

mol2conc	<i>Convert molar to concentration</i>
----------	---------------------------------------

Description

Convert molar to concentration

Usage

```
mol2conc(mol = NULL, unit_mol = NULL, unit_conc = NULL, mol_weight = NULL)
```

Arguments

mol	concentration in molar
unit_mol	unit of input concentration (molar), one of 'mol/L', 'mmol/mL', 'mmol/L'
unit_conc,	output unit, one of 'g/l', 'mg/l', 'microg/l', 'mcg/l', 'ng/l', 'mg/ml', 'microg/ml', 'mcg/ml', 'ng/ml'
mol_weight	concentration in g/mol

Examples

```
mol2conc(1, unit_mol = "mmol/l", mol_weight = 180)
```

nca	<i>Perform an NCA based on a NONMEM-style dataset</i>
-----	-------------------------------------------------------

Description

Perform an NCA based on a NONMEM-style dataset

Usage

```
nca(
  data = NULL,
  dose = 100,
  tau = 24,
  method = c("log_linear", "log_log", "linear"),
  scale = list(auc = 1, conc = 1),
  dv_min = 0.001,
  t_inf = NULL,
  fit_samples = NULL,
  weights = NULL,
  extend = TRUE,
  has_baseline = TRUE,
  route = c("iv", "oral", "im", "sc")
)
```

Arguments

<code>data</code>	data.frame with time and dv columns
<code>dose</code>	dose amount
<code>tau</code>	dosing frequency, default is 24.
<code>method</code>	'linear', 'log_linear' (default), or 'log_log'
<code>scale</code>	list with scaling for auc and concentration ('conc')
<code>dv_min</code>	minimum concentrations, lower observations will be set to this value
<code>t_inf</code>	infusion time, defaults to 0
<code>fit_samples</code>	vector of sample indexes used in fit to calculate elimination rate, e.g. 'c(3,4,5)'. If not specified (default), it will evaluate which of the last n samples shows the largest adjusted R ² when log-transformed data is fitted using linear regression, and use those samples in the estimation of the elimination rate.
<code>weights</code>	vector of weights to be used in linear regression (same size as specified concentration data), or function with concentration as argument.
<code>extend</code>	perform an 'extended' NCA, i.e. for the calculation of the AUCs, back-extend to the expected true C _{max} to also include that area.
<code>has_baseline</code>	does the included data include a baseline? If 'FALSE', baseline is set to zero.
<code>route</code>	administration route, 'iv' (intravenous, default), 'oral', 'sc' (sub-cutaneous), or 'im' (intra-muscular).

Value

Returns a list of three lists:

`pk` Lists pk parameters.

- `kel`: elimination constant
- `t_12`: half-life
- `v`: distribution volume
- `cl`: clearance

`descriptive` Lists exposure parameters.

- `cav_t`: the average concentration between the first observation and the last observation without extrapolating to tau
- `cav_tau`: the average concentration from 0 to tau
- `cmin`: the extrapolated concentration at time = tau
- `c_max_true`: only available if `extend = TRUE`, the extrapolated peak concentration
- `c_max`: only available if `extend = FALSE`, the observed maximum concentration
- `auc_inf`: the extrapolated AUC as time goes to infinity
- `auc_24`: the extrapolated AUC after 24 hours, provided no further doses are administered
- `auc_tau`: the extrapolated AUC at the end of the dosing interval
- `auc_t`: the AUC at the time of the last observation

`settings` Lists dosing information.

- `dose`: dose quantity
- `tau`: dosing interval

Examples

```
data <- data.frame(time = c(0, 2, 4, 6, 8, 12, 16),
                  dv    = c(0, 10, 14, 11, 9, 5, 1.5))
nca(data, t_inf = 2)
```

nca_trapezoid

NCA core function to perform log-linear trapezoid calculations for post-infusion

Description

NCA core function to perform log-linear trapezoid calculations for post-infusion

Usage

```
nca_trapezoid(data)
```

Arguments

`data` dataset passed from `nca()` with 'time' and 'dv' columns

oz2kg	<i>Convert oz to kg</i>
-------	-------------------------

Description

Convert oz to kg

Usage

```
oz2kg(oz)
```

Arguments

oz	vector
----	--------

Examples

```
oz2kg(2.20462)
```

pct_bmi_for_age	<i>Percentile BMI for age for children</i>
-----------------	--------------------------------------------

Description

Based on tables from WHO: http://www.who.int/growthref/who2007_bmi_for_age/en/

Usage

```
pct_bmi_for_age(  
  age = NULL,  
  bmi = NULL,  
  sex = NULL,  
  height = NULL,  
  return_median = FALSE,  
  ...  
)
```

Arguments

age	age in years
bmi	bmi Optional, if specified, will calculate closest percentile and return in list as 'percentile'
sex	either 'male' or 'female'
height	height
return_median	just return the median expected value
...	parameters passed to 'read_who_table()'

Examples

```
pct_bmi_for_age(age = 8, sex = "male")
pct_bmi_for_age(age = 8, bmi = 15, sex = "male")
```

pct_for_age_generic *Percentile height or weight for age for children*

Description

This is the underlying function, the exposed functions are pct_weight_for_age() and pct_height_for_age()
 Based on tables from WHO: http://www.who.int/childgrowth/standards/height_for_age/en/

Usage

```
pct_for_age_generic(
  age = NULL,
  value = NULL,
  sex = NULL,
  variable = "weight",
  ...
)
```

Arguments

age	age in years
value	height in kg. Optional, if specified, will calculate closest percentile and return in list as 'percentile'
sex	either 'male' or 'female'
variable	weight or height?
...	parameters passed to 'read_who_table()'

pct_height_for_age *Percentile height for age for children*

Description

Based on tables from WHO: http://www.who.int/childgrowth/standards/height_for_age/en/

Usage

```
pct_height_for_age(
  age = NULL,
  height = NULL,
  sex = NULL,
  return_median = FALSE,
  ...
)
```


Arguments

age	age in years
height	height in kg. Optional, if specified, will calculate closest percentile and return in list as 'percentile'
sex	either 'male' or 'female'
return_median	just return the median expected value
...	parameters passed to 'read_who_table()'

Examples

```
pct_height_for_age(age = 5, sex = "female")
pct_height_for_age(age = 5, height = 112, sex = "female")
```

pct_weight_for_age *Percentile weight for age for children*

Description

Based on tables from WHO: http://www.who.int/childgrowth/standards/weight_for_age/en/

Usage

```
pct_weight_for_age(
  age = NULL,
  weight = NULL,
  sex = NULL,
  return_median = FALSE,
  ...
)
```

Arguments

age	age in years
weight	weight in kg. Optional, if specified, will calculate closest percentile and return in list as 'percentile'
sex	either 'male' or 'female'
return_median	just return the median expected value
...	parameters passed to 'read_who_table()'

Examples

```
pct_weight_for_age(age = 5, sex = "female")
pct_weight_for_age(age = 5, weight = 20, sex = "female")
```

pk_1cmt_bolus	<i>Concentration predictions for 1-compartmental PK model after single or multiple bolus doses</i>
---------------	----------------------------------------------------------------------------------------------------

Description

Concentration predictions for 1-compartmental PK model after single or multiple bolus doses

Usage

```
pk_1cmt_bolus(t = c(0:24), dose = 100, tau = 12, CL = 3, V = 30, ruv = NULL)
```

Arguments

t	vector of time
dose	dose
tau	dosing interval
CL	clearance
V	volume of distribution
ruv	residual error (list)

Examples

```
pk_1cmt_bolus(dose = 500, tau = 12, CL = 5, V = 50)
pk_1cmt_bolus(dose = 500, tau = 12, CL = 5, V = 50, t = 24)
pk_1cmt_bolus(
  dose = 500, tau = 12, CL = 5, V = 50,
  ruv = list(prop = 0.1, add = 0.1))
```

pk_1cmt_bolus_cmax_ss	<i>Cmax for linear 1-compartment PK model at steady state, bolus dosing</i>
-----------------------	-----------------------------------------------------------------------------

Description

Takes single values for dose or model parameters, or vector of either dose or parameters (but not both).

Usage

```
pk_1cmt_bolus_cmax_ss(dose = 100, tau = 12, CL = 3, V = 30, ruv = NULL)
```

Arguments

dose	dose
tau	dosing interval
CL	clearance
V	volume of distribution
ruv	residual variability, specified as list with optional arguments for proportional, additive, or exponential components, e.g. 'list(prop=0.1, add=1, exp=0)'

Examples

```
pk_1cmt_bolus_cmax_ss(
  dose = 500, tau = 12, CL = 5, V = 50)
```

pk_1cmt_bolus_cmin_ss *Cmin (trough) for linear 1-compartment PK model at steady state, bolus dosing*

Description

Takes single values for dose or model parameters, or vector of either dose or parameters (but not both).

Usage

```
pk_1cmt_bolus_cmin_ss(dose = 100, tau = 12, CL = 3, V = 30, ruv = NULL)
```

Arguments

dose	dose
tau	dosing interval
CL	clearance
V	volume of distribution
ruv	residual variability, specified as list with optional arguments for proportional, additive, or exponential components, e.g. 'list(prop=0.1, add=1, exp=0)'

Examples

```
pk_1cmt_bolus_cmin_ss(
  dose = 500, tau = 12, CL = 5, V = 50)
```

pk_1cmt_bolus_dose_from_cmax

Calculate dose to achieve steady state Cmax for 1-compartmental PK model bolus dosing at steady state

Description

Calculate dose to achieve steady state Cmax for 1-compartmental PK model bolus dosing at steady state

Usage

```
pk_1cmt_bolus_dose_from_cmax(cmax = 1, tau = 12, CL = 3, V = 30)
```

Arguments

cmax	desired trough concentration
tau	dosing interval
CL	clearance
V	volume of distribution

Examples

```
dos <- pk_1cmt_bolus_dose_from_cmax(  
  cmax = 10, tau = 12, CL = 5, V = 50)  
find_nearest_dose(dos, 100)
```

pk_1cmt_bolus_dose_from_cmin

Calculate dose to achieve steady state trough for 1-compartmental PK model bolus dosing at steady state

Description

Calculate dose to achieve steady state trough for 1-compartmental PK model bolus dosing at steady state

Usage

```
pk_1cmt_bolus_dose_from_cmin(cmin = 1, tau = 12, CL = 3, V = 30)
```

Arguments

cmin	desired trough concentration
tau	dosing interval
CL	clearance
V	volume of distribution

Examples

```
dos <- pk_1cmt_bolus_dose_from_cmin(
  cmin = 5, tau = 12, CL = 5, V = 50)
find_nearest_dose(dos, 100)
```

pk_1cmt_bolus_ss	<i>Concentration predictions for 1-compartmental PK model with bolus dosing at steady state</i>
------------------	-------------------------------------------------------------------------------------------------

Description

Concentration predictions for 1-compartmental PK model with bolus dosing at steady state

Usage

```
pk_1cmt_bolus_ss(t = c(0:24), dose = 100, tau = 12, CL = 3, V = 30, ruv = NULL)
```

Arguments

t	vector of time
dose	dose
tau	dosing interval
CL	clearance
V	volume of distribution
ruv	residual variability, specified as list with optional arguments for proportional, additive, or exponential components, e.g. 'list(prop=0.1, add=1, exp=0)'

Examples

```
pk_1cmt_bolus_ss(dose = 500, tau = 12, CL = 5, V = 50)
pk_1cmt_bolus_ss(
  dose = 500, tau = 12, CL = 5, V = 50,
  ruv = list(prop = 0.1, add = 0.1))
```

pk_1cmt_inf	<i>Concentration predictions for 1-compartmental PK model after single or multiple bolus doses</i>
-------------	----------------------------------------------------------------------------------------------------

Description

Concentration predictions for 1-compartmental PK model after single or multiple bolus doses

Usage

```
pk_1cmt_inf(  
  t = c(0:24),  
  dose = 100,  
  tau = 12,  
  t_inf = 2,  
  CL = 3,  
  V = 30,  
  ruv = NULL  
)
```

Arguments

t	vector of time
dose	dose
tau	dosing interval
t_inf	infusion time
CL	clearance
V	volume of distribution
ruv	residual error (list)

Examples

```
pk_1cmt_inf(dose = 500, tau = 12, t_inf = 2, CL = 5, V = 50)  
pk_1cmt_inf(  
  dose = 500, tau = 12, t_inf = 2, CL = 5, V = 50,  
  ruv = list(prop = 0.1, add = 0.1))
```

pk_1cmt_inf_cmax_ss *Cmax for linear 1-compartment PK model at steady state*

Description

Takes single values for dose or model parameters, or vector of either dose or parameters (but not both).

Usage

```
pk_1cmt_inf_cmax_ss(dose, tau, CL, V, t_inf, ruv = NULL)
```

Arguments

dose	dose
tau	dosing interval
CL	clearance
V	volume of distribution
t_inf	infusion time
ruv	residual variability, specified as list with optional arguments for proportional, additive, or exponential components, e.g. 'list(prop=0.1, add=1, exp=0)'

Examples

```
pk_1cmt_inf_cmax_ss(dose = 500, tau = 12, t_inf = 2, CL = 5, V = 50)
```

pk_1cmt_inf_cmin_ss *Cmin (trough) for linear 1-compartment PK model at steady state*

Description

Takes single values for dose or model parameters, or vector of either dose or parameters (but not both).

Usage

```
pk_1cmt_inf_cmin_ss(  
  dose = 100,  
  tau = 12,  
  CL = 3,  
  V = 30,  
  t_inf = 2,  
  ruv = NULL  
)
```

Arguments

dose	dose
tau	dosing interval
CL	clearance
V	volume of distribution
t_inf	infusion time
ruv	residual variability, specified as list with optional arguments for proportional, additive, or exponential components, e.g. 'list(prop=0.1, add=1, exp=0)'

Examples

```
pk_1cmt_inf_cmin_ss(dose = 500, tau = 12, t_inf = 2, CL = 5, V = 50)
```

```
pk_1cmt_inf_dose_for_range
```

Calculate dose based on a given AUC24, Cmax, and Cmin, assuming 1-compartment model

Description

Calculate dose based on a given AUC24, Cmax, and Cmin, assuming 1-compartment model

Usage

```
pk_1cmt_inf_dose_for_range(  
  target = 500,  
  type = "auc",  
  conc_range = c(10, 40),  
  parameters = list(),  
  interval = 24,  
  t_inf = 1,  
  optimize_interval = TRUE,  
  round_interval = TRUE  
)
```

Arguments

target	numeric value of target
type	target type, one of 'auc', 'auc24', 'ctrough', 'cmin'
conc_range	concentration range to stay within, vector of length 2
parameters	list of 'CL' and 'V', or 'KEL' and 'CL'
interval	dosing interval
t_inf	infusion time
optimize_interval	find optimal interval (to stay within 'conc_range'?)
round_interval	round interval to nearest nominal interval?

pk_1cmt_inf_dose_from_cmax

Calculate dose to achieve steady state Cmax for 1-compartmental PK model with infusion dosing at steady state

Description

Calculate dose to achieve steady state Cmax for 1-compartmental PK model with infusion dosing at steady state

Usage

```
pk_1cmt_inf_dose_from_cmax(cmax = 1, tau = 12, t_inf = 1, CL = 3, V = 30)
```

Arguments

cmax	desired trough concentration
tau	dosing interval
t_inf	infusion time
CL	clearance
V	volume of distribution

Examples

```
pk_1cmt_inf_dose_from_cmax(cmax = 20, tau = 12, t_inf = 2, CL = 5, V = 50)
```

pk_1cmt_inf_dose_from_cmin

Calculate dose to achieve steady state trough for 1-compartmental PK model with infusion dosing at steady state

Description

Calculate dose to achieve steady state trough for 1-compartmental PK model with infusion dosing at steady state

Usage

```
pk_1cmt_inf_dose_from_cmin(cmin = 1, tau = 12, t_inf = 1, CL = 3, V = 30)
```

Arguments

cmin	desired trough concentration
tau	dosing interval
t_inf	infusion time
CL	clearance
V	volume of distribution

Examples

```
dos <- pk_1cmt_inf_dose_from_cmin(
  cmin = 20, tau = 12, t_inf = 2,
  CL = 5, V = 50)
find_nearest_dose(dos, 100)
```

pk_1cmt_inf_ss	<i>Concentration predictions for 2-compartmental PK model with infusion dosing at steady state</i>
----------------	----------------------------------------------------------------------------------------------------

Description

Concentration predictions for 2-compartmental PK model with infusion dosing at steady state

Usage

```
pk_1cmt_inf_ss(
  t = c(0:24),
  dose = 100,
  t_inf = 1,
  tau = 12,
  CL = 3,
  V = 30,
  ruv = NULL
)
```

Arguments

t	vector of time
dose	dose
t_inf	infusion time
tau	dosing interval
CL	clearance
V	volume of distribution
ruv	residual variability, specified as list with optional arguments for proportional, additive, or exponential components, e.g. 'list(prop=0.1, add=1, exp=0)'

Examples

```
pk_1cmt_inf_ss(dose = 500, tau = 12, t_inf = 2, CL = 5, V = 50)
pk_1cmt_inf_ss(
  dose = 500, tau = 12, t_inf = 2, CL = 5, V = 50,
  ruv = list(prop = 0.1, add = 0.1))
```

pk_1cmt_oral	<i>Concentration predictions for 1-compartmental oral PK model after single or multiple bolus doses</i>
--------------	---------------------------------------------------------------------------------------------------------

Description

Concentration predictions for 1-compartmental oral PK model after single or multiple bolus doses

Usage

```
pk_1cmt_oral(
  t = c(0:24),
  dose = 100,
  tau = 12,
  KA = 1,
  CL = 3,
  V = 30,
  F = 1,
  ruv = NULL
)
```

Arguments

t	vector of time
dose	dose
tau	dosing interval
KA	absorption rate
CL	clearance
V	volume of distribution
F	bioavailability, commonly between 0 and 1.
ruv	residual error (list)

References

Garrett ER. The Bateman function revisited: a critical reevaluation of the quantitative expressions to characterize concentrations in the one compartment body model as a function of time with first-order invasion and first-order elimination. *J Pharmacokinet Biopharm* (1994) 22(2):103-128.

Bialer M. A simple method for determining whether absorption and elimination rate constants are equal in the one-compartment open model with first-order processes. *J Pharmacokinet Biopharm* (1980) 8(1):111-113

Nielsen JC, Hutmacher MM et al. *J Pharmacokinet Pharmacodyn*. 2012 Dec;39(6):619-34. doi: 10.1007/s10928-012-9274-0. Epub 2012 Sep 23.

<https://static-content.springer.com/esm/art>

Examples

```
pk_1cmt_oral(dose = 500, tau = 12, CL = 5, V = 50, KA = 1)
```

pk_1cmt_t12	<i>Calculate terminal half-life for 1-compartment model</i>
-------------	-------------------------------------------------------------

Description

Calculate terminal half-life for 1-compartment model

Usage

```
pk_1cmt_t12(CL = 3, V = 30)
```

Arguments

CL	clearance
V	volume of central compartment

Examples

```
pk_1cmt_t12(CL = 5, V = 50)
```

pk_2cmt_bolus	<i>Concentration predictions for 2-compartmental PK model, single or multiple bolus doses</i>
---------------	-----------------------------------------------------------------------------------------------

Description

Concentration predictions for 2-compartmental PK model, single or multiple bolus doses

Usage

```
pk_2cmt_bolus(  
  t = c(0:24),  
  dose = 100,  
  tau = 12,  
  CL = 3,  
  V = 30,  
  Q = 2,  
  V2 = 20,  
  ruv = NULL  
)
```

Arguments

t	vector of time
dose	dose
tau	dosing interval
CL	clearance
V	volume of central compartment
Q	inter-compartmental clearance
V2	volume of peripheral compartment
ruv	residual error (list)

Examples

```
pk_2cmt_bolus(dose = 1000, tau = 24, CL = 5, V = 50, Q = 15, V2 = 200)
```

pk_2cmt_bolus_cmax_ss *Cmax for 2-compartmental PK model, bolus dosing at steady state*

Description

Cmax for 2-compartmental PK model, bolus dosing at steady state

Usage

```
pk_2cmt_bolus_cmax_ss(  
  dose = 100,  
  tau = 12,  
  CL = 3,  
  V = 30,  
  Q = 2,  
  V2 = 20,  
  ruv = NULL  
)
```

Arguments

dose	dose
tau	dosing interval
CL	clearance
V	volume of central compartment
Q	inter-compartmental clearance
V2	volume of peripheral compartment
ruv	residual error (list)

Examples

```
pk_2cmt_bolus_cmax_ss(dose = 1000, tau = 12, CL = 5, V = 50, Q = 20, V2 = 200)
```

```
pk_2cmt_bolus_cmin_ss Cmin (trough) for 2-compartmental PK model, bolus dosing at steady state
```

Description

Cmin (trough) for 2-compartmental PK model, bolus dosing at steady state

Usage

```
pk_2cmt_bolus_cmin_ss(  
  dose = 100,  
  tau = 12,  
  CL = 3,  
  V = 30,  
  Q = 2,  
  V2 = 20,  
  ruv = NULL  
)
```

Arguments

dose	dose
tau	dosing interval
CL	clearance
V	volume of central compartment
Q	inter-compartmental clearance
V2	volume of peripheral compartment
ruv	residual error (list)

Examples

```
pk_2cmt_bolus_cmin_ss(dose = 1000, tau = 12, CL = 5, V = 50, Q = 20, V2 = 200)
```

`pk_2cmt_bolus_dose_from_cmax`

Calculate dose to achieve steady state Cmax for 2-compartmental PK model bolus dosing at steady state

Description

Calculate dose to achieve steady state Cmax for 2-compartmental PK model bolus dosing at steady state

Usage

```
pk_2cmt_bolus_dose_from_cmax(  
  cmax = 1,  
  tau = 12,  
  CL = 3,  
  V = 30,  
  Q = 2,  
  V2 = 20  
)
```

Arguments

cmax	desired trough concentration
tau	dosing interval
CL	clearance
V	volume of distribution
Q	inter-compartmental clearance
V2	volume of peripheral compartment

Examples

```
dos <- pk_2cmt_bolus_dose_from_cmax(  
  cmax = 10, tau = 12,  
  CL = 5, V = 50, Q = 20, V2 = 200)  
find_nearest_dose(dos, 100)
```

pk_2cmt_bolus_dose_from_cmin

Calculate dose to achieve steady state trough for 2-compartmental PK model bolus dosing at steady state

Description

Calculate dose to achieve steady state trough for 2-compartmental PK model bolus dosing at steady state

Usage

```
pk_2cmt_bolus_dose_from_cmin(  
  cmin = 1,  
  tau = 12,  
  CL = 3,  
  V = 30,  
  Q = 2,  
  V2 = 20  
)
```

Arguments

cmin	desired trough concentration
tau	dosing interval
CL	clearance
V	volume of distribution
Q	inter-compartmental clearance
V2	volume of peripheral compartment

Examples

```
dos <- pk_2cmt_bolus_dose_from_cmin(  
  cmin = 5, tau = 12,  
  CL = 5, V = 50, Q = 20, V2 = 200)  
find_nearest_dose(dos, 100)
```

pk_2cmt_bolus_ss	<i>Concentration predictions for 2-compartmental PK model, bolus dosing at steady state</i>
------------------	---------------------------------------------------------------------------------------------

Description

Concentration predictions for 2-compartmental PK model, bolus dosing at steady state

Usage

```
pk_2cmt_bolus_ss(  
  t = c(0:24),  
  dose = 100,  
  tau = 12,  
  CL = 3,  
  V = 30,  
  Q = 2,  
  V2 = 20,  
  ruv = NULL  
)
```

Arguments

t	vector of time
dose	dose
tau	dosing interval
CL	clearance
V	volume of central compartment
Q	inter-compartmental clearance
V2	volume of peripheral compartment
ruv	residual error (list)

Examples

```
pk_2cmt_bolus_ss(dose = 1000, tau = 12, CL = 5, V = 50, Q = 20, V2 = 200)
```

pk_2cmt_inf	<i>Concentration predictions for 2-compartmental PK model, single or multiple infusions</i>
-------------	---------------------------------------------------------------------------------------------

Description

Concentration predictions for 2-compartmental PK model, single or multiple infusions

Usage

```
pk_2cmt_inf(
  t = c(0:24),
  dose = 100,
  tau = 12,
  t_inf = 1,
  CL = 3,
  V = 30,
  Q = 2,
  V2 = 20,
  ruv = NULL
)
```

Arguments

t	vector of time
dose	dose
tau	dosing interval
t_inf	infusion time
CL	clearance
V	volume of central compartment
Q	inter-compartmental clearance
V2	volume of peripheral compartment
ruv	residual error (list)

pk_2cmt_inf_cmax_ss	<i>C_{max} (trough) for 2-compartmental PK model, bolus dosing at steady state</i>
---------------------	--------------------------------------------------------------------------------------------

Description

C_{max} (trough) for 2-compartmental PK model, bolus dosing at steady state

Usage

```
pk_2cmt_inf_cmax_ss(
  dose = 100,
  tau = 12,
  t_inf = 1,
  CL = 3,
  V = 30,
  Q = 2,
  V2 = 20,
  ruv = NULL
)
```

Arguments

dose	dose
tau	dosing interval
t_inf	infusion time
CL	clearance
V	volume of central compartment
Q	inter-compartmental clearance
V2	volume of peripheral compartment
ruv	residual error (list)

Examples

```
pk_2cmt_inf_cmax_ss(
  dose = 1000, tau = 12, t_inf = 2,
  CL = 5, V = 50, Q = 20, V2 = 200)
```

pk_2cmt_inf_cmin_ss *Cmin (trough) for 2-compartmental PK model, bolus dosing at steady state*

Description

Cmin (trough) for 2-compartmental PK model, bolus dosing at steady state

Usage

```
pk_2cmt_inf_cmin_ss(
  dose = 100,
  tau = 12,
  t_inf = 1,
  CL = 3,
  V = 30,
```

```

    Q = 2,
    V2 = 20,
    ruv = NULL
)

```

Arguments

dose	dose
tau	dosing interval
t_inf	infusion time
CL	clearance
V	volume of central compartment
Q	inter-compartmental clearance
V2	volume of peripheral compartment
ruv	residual error (list)

Examples

```

pk_2cmt_inf_cmin_ss(
  dose = 1000, tau = 12, t_inf = 2,
  CL = 5, V = 50, Q = 20, V2 = 200)

```

pk_2cmt_inf_dose_from_cmax

Calculate dose to achieve steady state Cmax for 2-compartmental PK model with infusion dosing at steady state

Description

Calculate dose to achieve steady state Cmax for 2-compartmental PK model with infusion dosing at steady state

Usage

```

pk_2cmt_inf_dose_from_cmax(
  cmax = 1,
  tau = 12,
  t_inf = 1,
  CL = 3,
  V = 30,
  Q = 2,
  V2 = 20
)

```

Arguments

cmax	desired trough concentration
tau	dosing interval
t_inf	infusion time
CL	clearance
V	volume of distribution
Q	inter-compartmental clearance
V2	volume of peripheral compartment

Examples

```
dos <- pk_2cmt_inf_dose_from_cmax(  
  cmax = 25, tau = 12, t_inf = 2,  
  CL = 5, V = 50, Q = 20, V2 = 200)  
find_nearest_dose(dos, 100)
```

pk_2cmt_inf_dose_from_cmin

Calculate dose to achieve steady state trough for 2-compartmental PK model with infusion dosing at steady state

Description

Calculate dose to achieve steady state trough for 2-compartmental PK model with infusion dosing at steady state

Usage

```
pk_2cmt_inf_dose_from_cmin(  
  cmin = 1,  
  tau = 12,  
  t_inf = 1,  
  CL = 3,  
  V = 30,  
  Q = 2,  
  V2 = 20  
)
```

Arguments

cmin	desired trough concentration
tau	dosing interval
t_inf	infusion time
CL	clearance

V volume of distribution
 Q inter-compartmental clearance
 V2 volume of peripheral compartment

Examples

```
dos <- pk_2cmt_inf_dose_from_cmin(
  cmin = 10, tau = 12, t_inf = 2,
  CL = 5, V = 50, Q = 20, V2 = 200)
find_nearest_dose(dos, 100)
```

pk_2cmt_inf_ss	<i>Concentration predictions for 2-compartmental PK model with infusion dosing at steady state</i>
----------------	----------------------------------------------------------------------------------------------------

Description

Concentration predictions for 2-compartmental PK model with infusion dosing at steady state

Usage

```
pk_2cmt_inf_ss(
  t = c(0:24),
  dose = 100,
  t_inf = 1,
  tau = 12,
  CL = 3,
  V = 30,
  Q = 2,
  V2 = 20,
  ruv = NULL
)
```

Arguments

t vector of time
 dose dose
 t_inf infusion time
 tau dosing interval
 CL clearance
 V volume of distribution
 Q inter-compartmental clearance
 V2 volume of peripheral compartment
 ruv residual variability, specified as list with optional arguments for proportional, additive, or exponential components, e.g. 'list(prop=0.1, add=1, exp=0)'

Examples

```
pk_2cmt_inf_ss(
  dose = 1000, tau = 12, t_inf = 2,
  CL = 5, V = 50, Q = 20, V2 = 200)
```

pk_2cmt_t12

Calculate half-life(s) for 2-compartment model

Description

Calculate half-life(s) for 2-compartment model

Usage

```
pk_2cmt_t12(CL = 3, V = 30, Q = 2, V2 = 20, phase = c("both", "alpha", "beta"))
```

Arguments

CL	clearance
V	volume of central compartment
Q	inter-compartmental clearance
V2	volume of peripheral compartment
phase	'alpha', 'beta' (default) or 'both' to indicate initial (distribution) or terminal (elimination) phase.

Examples

```
pk_2cmt_t12(CL = 5, V = 50, Q = 20, V2 = 200)
```

pk_2cmt_t12_interval

Calculate average half-life for 2-compartment model during a specific interval

Description

Calculate average half-life for 2-compartment model during a specific interval

Usage

```
pk_2cmt_t12_interval(CL = 3, V = 30, Q = 2, V2 = 20, tau = 12, t_inf = NULL)
```

Arguments

CL	clearance
V	volume of central compartment
Q	inter-compartmental clearance
V2	volume of peripheral compartment
tau	interval (hours)
t_inf	infusion time (hours)

Examples

```
pk_2cmt_t12_interval(CL = 5, V = 50, Q = 20, V2 = 200, tau = 12, t_inf = 2)
```

```
print.nca_output      Print function for output from nca()
```

Description

Print function for output from nca()

Usage

```
## S3 method for class 'nca_output'
print(x, ...)
```

Arguments

x	output object (list) from nca()
...	variables past on to print function

```
read_who_table      Read WHO growth tables
```

Description

Provides a data frame of the WHO growth table for a given age, sex, and type of measurement.

Usage

```
read_who_table(sex = NULL, age = NULL, type = "wfa")
```


Arguments

sex,	either male or female
age	age in years
type	table type, choose from wfa (weight for age), lhfa (length for age)

Details

This function uses files included in `system.file(package = "clinPK")`. Previously this function also gave the option to download the tables from WHO, but the original URL ("<http://www.who.int/entity/childgrowth/standards>") no longer exists as of 2021-05-19.

`relative2absolute_bsa` *Convert quantity expressed relative to BSA to absolute units*

Description

Often used for eGFR estimates

Usage

```
relative2absolute_bsa(quantity, bsa = NULL, ...)
```

Arguments

quantity	quantity expressed in units /1.73m ²
bsa	ideal body weight in kg
...	arguments passed on to 'calc_bsa', if bsa is NULL

Value

quantity expressed in absolute units

Examples

```
relative2absolute_bsa(quantity = 60, bsa = 1.6)
relative2absolute_bsa(quantity = 60, weight = 14, height = 90, method = "dubois")
```

remove_lt_gt	<i>Remove less-than/greater-than symbols and convert to numeric</i>
--------------	---------------------------------------------------------------------

Description

The following characters will be removed from strings: <, >, =, space. If string contains other characters, the original string will be returned.

Usage

```
remove_lt_gt(x)
```

Arguments

x	Vector of numbers possibly containing extraneous strings.
---	-----------------------------------------------------------

Value

If non-numeric characters were successfully removed, returns a numeric vector. If some elements of 'x' contained other characters, their original value will be returned and the result will be a character vector.

time_to_ss	<i>Time to steady state In either time units or number of doses</i>
------------	---------------------------------------------------------------------

Description

Time to steady state In either time units or number of doses

Usage

```
time_to_ss(kel = NULL, halflife = NULL, ss = 0.9, in_doses = FALSE, tau = NULL)
```

Arguments

kel	drug elimination rate
halflife	halflife. Either 'kel' or 'halflife' is required.
ss	level considered "steady state", e.g. '0.9' is 90% of true steady state.
in_doses	return the number of doses instead of time unit? Default 'FALSE'. Requires 'tau' as well.
tau	dosing interval

Examples

```
time_to_ss(halflife = 12, ss = 0.9)
time_to_ss(halflife = 16, ss = 0.95, in_doses = TRUE, tau = 12)
```

valid_units	<i>Valid units</i>
-------------	--------------------

Description

Return recognized units for height, weight, age, scr.

Usage

```
valid_units(covariate = c("height", "weight", "age", "scr"))
```

Arguments

covariate Covariate (one of "height", "weight", "age", "scr")

Value

Vector of valid units for the given covariate

Examples

```
valid_units("height")
valid_units("weight")
```

weight2kg	<i>Convert any weight unit to kg</i>
-----------	--------------------------------------

Description

Convert any weight unit to kg

Usage

```
weight2kg(value = NULL, unit = NULL)
```

Arguments

value weight in any allowed unit
unit unit of weight, one of "lb", "lbs", "pound", "pounds", "oz", "ounce", "ounces",
"gram", "grams"

Examples

```
weight2kg(250, unit = "oz")
weight2kg(250, unit = "pounds")
weight2kg(250, unit = "lbs")
```

%>=%	<i>Greater-than-or-equal-to with a little room for floating point precision issues</i>
------	----------------------------------------------------------------------------------------

Description

Greater-than-or-equal-to with a little room for floating point precision issues

Usage

x %>=% y

Arguments

x	Numeric vector
y	Numeric vector

%<=%	<i>Less-than-or-equal-to with a little room for floating point precision issues</i>
------	-------------------------------------------------------------------------------------

Description

Less-than-or-equal-to with a little room for floating point precision issues

Usage

x %<=% y

Arguments

x	Numeric vector
y	Numeric vector

Index

[%<=%](#), 68
[%>=%](#), 68

[absolute2relative_bsa](#), 4
[accumulation_ratio](#), 5
[add_ruv](#), 5
[as.num](#), 6
[auc2dose](#), 6

[calc_abw](#), 7
[calc_aki_stage](#), 7
[calc_amts_for_conc](#), 9
[calc_baseline_scr](#), 10
[calc_bmi](#), 11
[calc_bsa](#), 11
[calc_creat](#), 12
[calc_creat_neo](#), 13
[calc_dosing_weight](#), 13
[calc_egfr](#), 14
[calc_egfr_cystatin](#), 18
[calc_ffm](#), 18
[calc_ibw](#), 20
[calc_kel_double_tdm](#), 21
[calc_kel_single_tdm](#), 22
[calc_kgfr](#), 23
[calc_lbw](#), 24
[calc_t12](#), 25
[check_covs_available](#), 26
[clinPK-package](#), 4
[cm2inch](#), 26
[conc2mol](#), 27
[convert_creat_assay](#), 27
[convert_creat_unit](#), 28
[convert_flow_unit](#), 28

[dose2auc](#), 29

[egfr_bedside_schwartz](#) ([calc_egfr](#)), 14
[egfr_ckd_epi](#) ([calc_egfr](#)), 14
[egfr_ckd_epi_as_2021](#) ([calc_egfr](#)), 14
[egfr_cockcroft_gault](#) ([calc_egfr](#)), 14
[egfr_cockcroft_gault_sci](#) ([calc_egfr](#)), 14
[egfr_cov_reqs](#), 30
[egfr_jelliffe](#) ([calc_egfr](#)), 14
[egfr_jelliffe_unstable](#) ([calc_egfr](#)), 14
[egfr_malmo_lund](#) ([calc_egfr](#)), 14
[egfr_mdrd](#) ([calc_egfr](#)), 14
[egfr_schwartz](#) ([calc_egfr](#)), 14
[egfr_wright](#) ([calc_egfr](#)), 14

[ffm_al_sallami](#) ([calc_ffm](#)), 18
[ffm_bucaloiu](#) ([calc_ffm](#)), 18
[ffm_garrow_webster](#) ([calc_ffm](#)), 18
[ffm_hume](#) ([calc_ffm](#)), 18
[ffm_james](#) ([calc_ffm](#)), 18
[ffm_janmahasatian_green](#) ([calc_ffm](#)), 18
[ffm_storset](#) ([calc_ffm](#)), 18
[find_factor](#), 30
[find_nearest_dose](#), 31
[find_nearest_interval](#), 31
[fraction_of_ss](#), 32

[ibw_devine](#), 32
[ibw_standard](#), 33
[inch2cm](#), 33
[is.nil](#), 34

[kdigo_stage](#), 34
[kg2lbs](#), 35
[kg2oz](#), 35

[lbs2kg](#), 36

[mol2conc](#), 36

[nca](#), 37
[nca_trapezoid](#), 38

[oz2kg](#), 39
[pct_bmi_for_age](#), 39

`pct_for_age_generic`, [40](#)
`pct_height_for_age`, [40](#)
`pct_weight_for_age`, [41](#)
`pk_1cmt_bolus`, [42](#)
`pk_1cmt_bolus_cmax_ss`, [42](#)
`pk_1cmt_bolus_cmin_ss`, [43](#)
`pk_1cmt_bolus_dose_from_cmax`, [44](#)
`pk_1cmt_bolus_dose_from_cmin`, [44](#)
`pk_1cmt_bolus_ss`, [45](#)
`pk_1cmt_inf`, [46](#)
`pk_1cmt_inf_cmax_ss`, [47](#)
`pk_1cmt_inf_cmin_ss`, [47](#)
`pk_1cmt_inf_dose_for_range`, [48](#)
`pk_1cmt_inf_dose_from_cmax`, [49](#)
`pk_1cmt_inf_dose_from_cmin`, [49](#)
`pk_1cmt_inf_ss`, [50](#)
`pk_1cmt_oral`, [51](#)
`pk_1cmt_t12`, [52](#)
`pk_2cmt_bolus`, [52](#)
`pk_2cmt_bolus_cmax_ss`, [53](#)
`pk_2cmt_bolus_cmin_ss`, [54](#)
`pk_2cmt_bolus_dose_from_cmax`, [55](#)
`pk_2cmt_bolus_dose_from_cmin`, [56](#)
`pk_2cmt_bolus_ss`, [57](#)
`pk_2cmt_inf`, [58](#)
`pk_2cmt_inf_cmax_ss`, [58](#)
`pk_2cmt_inf_cmin_ss`, [59](#)
`pk_2cmt_inf_dose_from_cmax`, [60](#)
`pk_2cmt_inf_dose_from_cmin`, [61](#)
`pk_2cmt_inf_ss`, [62](#)
`pk_2cmt_t12`, [63](#)
`pk_2cmt_t12_interval`, [63](#)
`print.nca_output`, [64](#)

`read_who_table`, [64](#)
`relative2absolute_bsa`, [65](#)
`remove_lt_gt`, [66](#)

`time_to_ss`, [66](#)

`valid_units`, [67](#)

`weight2kg`, [67](#)